

**BUCKEYE PIPE LINE COMPANY, L.P.**  
**BUCKEYE PIPE LINE TRANSPORTATION, LLC**  
**LAUREL PIPE LINE COMPANY, L.P.**  
**NORCO PIPE LINE COMPANY, LLC**  
**WOOD RIVER PIPE LINES, LLC**

***FUNGIBLE***

**PRODUCT GRADE SPECIFICATIONS**

### 6.3 PRODUCT GRADE SPECIFICATIONS

This section contains specifications for products which are handled on a fungible or common-stream basis. A "fungible batch" is defined as a batch of petroleum product meeting Carrier's specifications which may be commingled with other batches of petroleum product meeting the same specifications.

<u>INDEX</u>	<u>PAGE</u>
Table 1	4
Approved Gum Inhibitors and Metal Deactivators for Gasoline	
Approved Corrosion Inhibitors and Lubricity Improvers for Gasoline, Diesel Fuel and Fuel Oil	
Table 2	5
Seasonal Gasoline Distillation and Volatility Classes	
Grade 132 - Low Sulfur Diesel/Fuel Oil - 0.042% Sulfur (Non-Road) – LM500	6
Grade 150 – Ultra Low Sulfur Diesel #1 (Non-Road) – DNR015	7
Grade 151 – Ultra Low Sulfur Diesel #1 (Motor Vehicle) – DMV015	8
Grade 152 – Aviation/Kerosene – 400 ppm Sulfur	9
Grade 154 – Kerosene Fuel – Non Aviation 400 ppm sulfur	11
Grade 155 – Multi-Purpose ULSD-1/Aviation/ULSK (Motor Vehicle) – DMV015	12
<del>Grade 159 – Heating Oil 500 PPM Sulfur Dyed</del>	<del>14</del>
Grade 164 – Heating Oil 15 PPM Sulfur (Undyed)	15
Grade 169 – Heating Oil 500 PPM Sulfur – Undyed	16
Grade 182 and Grade 188 - Aviation Kerosene	17
Grade 190 – Ultra Low Sulfur Diesel - 0.0015% Sulfur (Motor Vehicle) – DMV015	18
Grade 193 – Ultra Low Sulfur Diesel - 0.0015% Sulfur (Non-Road) – DNR015	19

**INDEX**

**PAGE**

Sub-Octane Conventional Gasoline (Regular and Premium Grades)	20
Grade 307 – Low RVP – 90 Octane Conventional Gasoline	
Grade 308 – Low RVP – Sub-Octane Conventional Gasoline	
Grade 317 – 90 Octane Conventional Gasoline	
Grade 318 – Sub-Octane Conventional Gasoline	
Grade 327 – Low RVP 90 Octane Conventional Gasoline	
Grade 328 – Low RVP Sub-Octane Conventional Gasoline	
Grade 337 – Low RVP 90 Octane Conventional Gasoline (S.E. Michigan Only)	
Grade 338 – Low RVP Sub-Octane Conventional Gasoline (S.E. Michigan Only)	
Grades 357, 358, 377, 378	
Regular VOC Controlled RBOB for 10% Ethanol Blending	23
Grade 522 (Region 2 Adjusted)	
Grade 532 (Region 2)	
Grade 552 (Region 1)	
Premium VOC Controlled RBOB for 10% Ethanol Blending	25
Grade 525 (Region 2 Adjusted)	
Grade 535 (Region 2)	
Grade 555 (Region 1)	
Non-VOC Controlled Regular RBOB for 10% Ethanol Blending (Grades 542, 572 and 582)	27
Non- VOC Controlled Premium RBOB for 10% Ethanol Blending (Grades 545, 575 and 585)	29

## TABLE 1

### **Approved GUM INHIBITORS AND METAL DEACTIVATORS**

#### For Gasoline

This product may, but is not required to, contain the following:

N, N'di-secondary butyl para-phenylenediamine	N, N'disalicylidene-1, 2 propanediamine
2, 6-di-tertiary butyl 4 methyl phenol	N, N'di (1-ethyl-2-methylpentyl) para-phenylenediamine
N, N'di-isopropyl-para-phenylenediamine	N, N'bis- (1, 4-diemethylpentyl) -p-phenylenediamine
N-Butyl para-aminophenol	2,4,6 - tritertiary butylphenol
Ortho-tertiary butylphenol	2,4-diamethyl-6-tertiary-butylphenol
2,4-di-tertiary butylphenol	2,6-di-tertiary butylphenol
N, secondary butyl, N' phenyl-para-phenylenediamine	Butylated ethyl, methyl and dimethyl phenols
Mixed propylated and butylated phenols	2,4,6 tri-isopropylphenol

### **Approved CORROSION INHIBITORS**

#### For Gasoline

This product may, but is not required to, contain the following:

Nalco 5403	Spec-Aid 8Q22	Innospec DCI-4A	Tolad 245	Lubrizol 541
Nalco 5405	Spec-Aid 8Q100	Innospec DCI-6A	Tolad 249	Lubrizol 8014
Nalco 5406	Spec-Aid 8Q101	Innospec DCI-11	Tolad 351	Lubrizol 8017
Nalco EC5624A	Spec-Aid 8Q102	Innospec DCI-30.N	Tolad 3232	Afton Chemical HiTEC 4875
Nalco EC5626A	Spec-Aid 8Q103	UOP Unicor	Tolad 3232D	Afton Chemical HiTEC 6455
Unichem 7500	Spec-Aid 8Q106	UOP Unicor J	Tolad 4410	Mobil C-605
Unichem 7501	Spec-Aid 8Q109	UOP Unicor PL	Tolad 9711	Aqua Process 11CH77
Unichem 7510	Spec-Aid 8Q110	Champion RPS-622	Tolad 9715	Corexit 5267
MidContinental Chem. MCC5001	Spec-Aid 8Q112ULS	Champion RPS-807	Tolad 9719	
Athlon RPS-661	Spec-Aid 8Q123ULS	Ethyl HiTec 580		

#### For Diesel Fuels and Fuel Oil

In addition to the above additives, the following may be used:

	-1		
Dupont	AFA	Innospec	DMA-4
Nalco	EC 5407-A	Nalco	5400-A
Tolad	3032	Infineum	R511
Athlon	RPS-661		

**NOTE:** All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).

### **STATIC DISSIPATOR ADDITIVE (SDA) OR CONDUCTIVITY IMPROVER**

Product shipments may, but are not required to, contain static dissipator/electrical conductivity additive (SDA). The only approved SDAs for use on Buckeye Pipe Line is Innospec Stadis 450 and AvGuard SDA. SDA is prohibited from all jet fuel / aviation kerosene grades. The origin maximum concentration of Stadis 450 or AvGuard SDA is 0.75 mg/l, and the origin maximum conductivity allowed is 250 pS/m at 70°F by ASTM D2624.

### **AVIATION (JET FUEL) ADDITIVES**

Product shall only contain antioxidants and metal deactivators specified and within the concentration noted in the latest ASTM D1655 with advance approval from Buckeye prior to shipment. Use of these additives is expected to be short term at reasonable treat levels, and is to be clearly indicated on the CoA. All other additives are prohibited. Buckeye reserves the right to deny shipment of product containing these additives. In addition, scheduling and Measurement & Quality Control must be notified at least 72 hours prior to the scheduled shipment of any batches containing Metal Deactivator Additive (MDA). If MDA has been added to the product, Buckeye reserves the right to refuse shipment. If requesting to move a batch that has been treated with MDA, supply the following information to Buckeye Measurement & Quality Control: (1) the purpose for adding MDA, (2) a breakdown of total metals present in the jet fuel before treating with MDA, (3) JFTOT test results both prior to and after adding MDA, (4) MDA treat rate, and (5) MDA product used.

## TABLE 2 - SEASONAL GASOLINE REQUIREMENTS

### REID VAPOR PRESSURE (RVP)

The following schedule denotes the volatility properties as required by Buckeye and may not coincide with dates specified by appropriate government agencies. Some systems within Buckeye may require earlier dates for summer RVP limits in order to ensure compliance with EPA federal regulations. Shippers will be advised in advance of the date that fungible gasolines must be input into the Buckeye System via the scheduling calendar. Buckeye will use a Grabner vapor pressure instrument to monitor RVP compliance, per ASTM D5191, but will use the coefficients recommended by EPA, i.e. 956X - 0.347.

### DISTILLATION CLASSES: ASTM D-86

CLASS	A	C	D	E
10% Evap., Deg F (Deg C) Max.	158 (70)	140 (60)	131 (55)	122 (50)
50% Evap., Deg F (Deg C) Min. <sup>(1)</sup>	170 (77)	170 (77)	170 (77)	170 (77)
50% Evap., Deg F (Deg C) Max.	250 (121)	240 (116)	235 (113)	230 (110)
90% Evap., Deg F (Deg C) Max.	374 (190)	365 (185)	365 (185)	365 (185)
<b>End Point, Deg F (Deg C) Max.</b>	<b>430 (221)</b>	<b>430 (221)</b>	<b>430 (221)</b>	<b>430 (221)</b>
Driveability Index Deg F (Deg C) Max. <sup>(2)</sup>	1250 (597)	1230 (586)	1220 (580)	1200 (569)

CLASS	1	2	3	4	5
Min Vapor/Liquid Ratio (TV/L) 20 °F (°C) [ASTM D-5188] <sup>1</sup>	133 (56)	133 (56)	124 (51)	116 (47)	105 (41)

### Approximate Origin Maximum RVP and Distillation Requirements<sup>1</sup>

Destination		Jan	Feb	Mar 1-14	Mar 15-31	Apr 1-15	Apr 16-30	May	Jun	Jul	Aug	Sep 1-15	Sep 16-30	Oct	Nov	Dec
LIS and JET (NYC/MA/CT) <sup>4</sup>	psi	15.0	15.0	15.0	13.5	13.5	7.80	7.80	7.80	7.80	7.80	7.80	13.5	13.5	15.0	15.0
	dist	E-5	E-5	E-5	D-4	A-4	A-4	A-3	A-3	A-3	A-3	A-3	D-4	D-4	E-5	E-5
EPS/LPL/PPS (PA)	psi	15.0	15.0	13.5	13.5	9.00	9.00	9.00	9.00	9.00	9.00	9.00	13.5	13.5	15.0	15.0
	dist	E-5	E-5	D-4	D-4	A-4	A-4	A-3	A-3	A-3	A-3	A-3	D-4	D-4	E-5	E-5
EPS/PPS (Upstate NY)	psi	15.0	15.0	13.5	13.5	7.80	7.80	7.80	7.80	7.80	7.80	7.80	13.5	13.5	15.0	15.0
	dist	E-5	E-5	D-4	D-4	A-4	A-4	A-3	A-3	A-3	A-3	A-3	D-4	D-4	E-5	E-5
Maine (To Bangor)	psi	15.0	15.0	15.0	13.5	7.80	7.80	7.80	7.80	7.80	7.80	7.80	13.5	13.5	15.0	15.0
	dist	E-5	E-5	E-5	D-4	A-4	A-4	A-3	A-3	A-3	A-3	A-3	D-4	D-4	E-5	E-5
Midwest (SE Michigan)	psi	15.0	15.0	13.5	13.5	7.00	7.00	7.00	7.00	7.00	7.00	7.00	13.5	13.5	15.0	15.0
	dist	E-5	E-5	D-4	D-4	A-4	A-4	A-3	A-3	A-3	A-3	A-3	D-4	D-4	E-5	E-5
Midwest (Michigan)	psi	15.0	15.0	13.5	13.5	9.00	9.00	9.00	9.00	9.00	9.00	9.00	13.5	13.5	15.0	15.0
	dist	E-5	E-5	D-4	D-4	A-4	A-4	A-3	A-3	A-3	A-3	A-3	D-4	D-4	E-5	E-5
Wood River (St. Louis) <sup>4</sup>	psi	15.0	15.0	13.5	13.5	8.00	8.00	8.00	8.00	8.00	8.00	8.00	11.5	13.5	13.5	15.0
	dist	E-5	E-5	D-4	D-4	D-4	A-3	A-3	A-3	A-3	A-2	A-2	C-3	D-4	D-4	E-5
Midwest and Wood River (All other)	psi	15.0	15.0	13.5	13.5	9.00	9.00	9.00	9.00	9.00	9.00	9.00	11.5	13.5	15.0	15.0
	dist	E-5	E-5	D-4	D-4	A-4	A-4	A-3	A-3	A-3	A-3	A-3	C-3	D-4	E-5	E-5
Lower V (Dubuque to IA)	psi	15.0	15.0	13.5	13.5	9.00	9.00	9.00	9.00	9.00	9.00	9.00	11.5	13.5	15.0	15.0
	dist	E-5	E-5	D-4	D-4	A-3	A-3	A-3	A-3	A-3	A-3	A-3	C-3	D-4	E-5	E-5
Lower V (Dubuque to MO and KS)	psi	15.0	13.5	13.5	11.5	9.00	9.00	9.00	9.00	9.00	9.00	9.00	11.5	13.5	13.5	15.0
	dist	E-5	D-4	D-4	C-3	A-3	A-3	A-2	A-2	A-2	A-2	A-2	C-3	D-4	D-4	E-5
Lower V (Low RVP Areas)	psi	15.0	13.5	11.5	11.5	6.80	6.80	6.80	6.80	6.80	6.80	6.80	11.5	13.5	13.5	15.0
	dist	E-5	D-4	C-3	C-3	A-2	A-2	A-2	A-2	A-2	A-2	A-2	C-3	D-4	D-4	E-5

(1) Computer and Linear methods may be used to determine TV/L value. D5188 will be the referee method. TV/L and T50 limits provided in Table 2 are for the base gasoline only; additional TV/L and T50 limits for ethanol blended gasoline are found in individual Grade Code specifications. T50, TV/L and RVP limits for all RBOB's and gasoline must comply with the applicable requirements of the area in which the fuel is destined for retail. Maximum Distillation residue is 2% Vol for all base gasoline.

(2) The DI (Driveability Index) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2 and are not subject to correction for precision of the test method.

(3) Refer to Product Grade Specification for specific RVP requirements. For products blended to meet EPA or state imposed volatility requirements, RVP test must be performed in accordance with methods published in 40 CFR Part 80.

(4) The 7.8 lb. RVP limit for NYC, MA, & CT, is after 10% ethanol blend. The 8.0 lb RVP limit for St. Louis is after 10% ethanol blend.

**BUCKEYE PARTNERS, L.P.**  
**SPECIFICATIONS FOR FUNGIBLE LOW SULFUR DIESEL (LM500)**  
**GRADE 132**

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Gravity, API @ 60°F	D287, D4052	30		
Flash Point, °F (at Origin)	D93, D56, D7094	130		1
Color, ASTM	D1500		2.5	
Viscosity, cst @ 104°F	D445	1.9	3.4	
Cloud Point, °F (Sept thru March)	D2500, D5771, D5772,		+15 °F	
(April thru August)	D5773, D3117		+20 °F	
Pour Point, °F (Sept thru March)	D5985, D5949, D5950, D97		0 °F	
(April thru August)			+10°F	
Total Sulfur, wt. %	D1266, D2622 or D4294 D5453		0.042	
Corrosion, 3 hrs. @ 122°F	D130		1	
Oxidation Stability, mg/100 ml or	D2274		2.5	
Thermal Stability, 90 minutes				
150°C Pad rating	DuPont		7	
Carbon Residue, wt. % on 10% bottom	D524 or D4530		0.35	
Ash, wt. %	D482		0.01	
Sediment and Water, % by volume	D2709		0.05	
Cetane Number or Index	D4737, D613, D6890, D7170	40		
Aromatics (Vol%)	D1319		35.0	
or Aromatics by Cetane Index	D976	40		
Physical Distillation, °F	D86			
50% recovered		Report		
90% recovered		540	640	
End Point			700 <del>690</del>	
OR Simulated Distillation, °F	D2887			
50% recovered		Report		
90% recovered		572	673	
End Point			790	
Haze Rating @ 77°F	D4176		2	
Procedure 2				
Color Visual		Undyed		4
Additives				5, 6
Electrical Conductivity, pS/m @ 70°F	D2624		250 Report	5
NACE	TM0172-2001	B+		7

**NOTES:**

1. Test method D-93 is the referee method. Minimum flash at delivery is 125 °F.
2. Intended to be consistent with ASTM D975 Grade No. 2 middle distillate fuels, unless otherwise noted.
3. Reserved
4. Product must exhibit no visible evidence of dye.
5. Use of static dissipater/conductivity improver is restricted (See Table 1).
6. The use of lubricity improver additives is prohibited.
7. All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).
8. This product is for Non-Road use and is designated as LM500 in the EPA's Designate and Track reporting system.
9. Biofuel Components (e.g. biodiesel) are not permitted in this product.
10. Shipments of this Grade Code are limited to less than 5.0% renewable diesel. Renewable diesel is a liquid fuel derived from 100% hydrotreated biomass that meets the registration requirements for fuels and fuel additives established by the EPA under Section 211 of the Clean Air Act and the requirements of ASTM D975. Fuel containing fatty acid esters (FAME, FAEE, or other esters) is prohibited.

**BUCKEYE PARTNERS, L.P.**  
**SPECIFICATIONS FOR ULTRA LOW SULFUR DIESEL #1 (NON-ROAD)**  
**GRADE 150**

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Appearance	White Bucket	Report		1
Gravity, API @ 60°F	D287, D1298 or D4052	37	51	
Color, at origin	D156, D6045	18		1
at delivery		+16		
Corrosion, 2 hrs. @ 212°F	D130		1	
Cetane (Number or Index)	D976, D4737, D613, D6890	40		
Total Sulfur, ppm (at receipt)	D5453, D4294		11	5,7,8,9
Doctor Test	D4952		Negative	
OR				
Mercaptan Sulfur, wt. %	D3227		0.003	3
Aromatics, vol. %	D1319		25	
Flash Point, °F	D56, D3828	108		
Distillation, °F	D86			
10% recovered		Report	400	
50% recovered		Report		
90% recovered		Report	550	
95% recovered		Report		
End Point			572	
or Simulated Distillation, °C(°F)	D2887			
10% recovered			185(365)	
50% recovered		Report		
90% recovered			304(579)	
End Point			340(644)	
Residue, %			1.5	
Loss, %			1.5	
Freezing Point, °F	D5972, D7153, D7154, D2386		-22	
Viscosity, cst. @ 104°F	D445	1.3	1.9	
Ash, wt %	D482		0.01	
Carbon residue, wt % on 10% bottom	D524		0.15	
Thermal Stability, 90 minutes				
150°C Pad rating	DuPont		7	
Burning Quality	D187	Report		
Electrical Conductivity	D2624	Report		2
Additives		Report		2
NACE	TM0172-2001	B+		4

**NOTES:**

- Product shall be clear (referring to clarity, not color) and bright and free of suspended matter, and must not exhibit various shades of green, blue or red. No peacock or abnormal color deposits.
- Only those additives accepted in Table 1 of this section will be permitted by Buckeye. Use of all additives must be approved by Buckeye prior to shipment and must be reported on the Certificate of Analysis and Preshipment Fax of Key Properties.
- Mercaptan Sulfur waived if fuel is negative by Doctor test.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).
- This product is for Non-Road use and should be designated as such in the EPA's Designate and Track reporting system: DNRLM015.
- Biofuel Components (e.g. biodiesel) are not permitted in this product.
- Intended to be consistent with ASTM Grade No. 1 middle distillate fuels, unless otherwise noted.
- Receipts from Wolverine Pipe Line will be accepted at a maximum of 12.0 ppm sulfur.
- Sulfur level at delivery will vary depending upon the origin and delivery location.

**BUCKEYE PARTNERS, L.P.**  
**SPECIFICATIONS FOR ULTRA LOW SULFUR DIESEL #1 (MOTOR VEHICLE)**  
**GRADE 151**

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Appearance	White Bucket	Report		1
Gravity, API @ 60°F	D287, D1298 or D4052	37	51	
Color, at origin	D156, D6045	18		
at delivery		+16		
Corrosion, 2 hrs. @ 212°F	D130		1	
Cetane (Number or Index)	D976, D4737, D613, D6890	40		
Total Sulfur, ppm (at receipt)	D5453, D4294		11	4,5,8,9
Doctor Test	D4952		Negative	
OR				
Mercaptan Sulfur, wt. %	D3227		0.003	3
Aromatics, vol. %	D1319		25	
Flash Point, °F	D56, D3828	108		
Distillation, °F	D86			
10% recovered		Report	400	
50% recovered		Report		
90% recovered		Report	550	
95% recovered		Report		
End Point			572	
or Simulated Distillation, °C(°F)	D2887			
50% recovered			Report	
90% recovered		300(572)	356(673)	
End Point			421(790)	
Residue, %			1.5	
Loss, %			1.5	
Freezing Point, °F	D5972, D7153, D7154, D2386		-22	
Viscosity, cst. @ 104°F	D445	1.3	1.9	
Ash, wt %	D482		0.01	
Carbon residue, wt % on 10% bottom	D524		0.15	
Thermal Stability, 90 minutes				
150°C Pad rating	DuPont		7	
Burning Quality	D187	Report		
Electrical Conductivity	D2624	Report		2
Additives		Report		2
NACE	TM0172-2001	B+		6

**NOTES:**

- Product shall be clear (referring to clarity, not color) and bright and free of suspended matter, and must not exhibit various shades of green, blue or red.
- Only those additives accepted in Table 1 of this section will be permitted by Buckeye. Use of all additives must be approved by Buckeye prior to shipment and must be reported on the Certificate of Analysis and Preshipment Fax of Key Properties.
- Mercaptan Sulfur waived if fuel is negative by Doctor test.
- This product is for Motor Vehicle use and should be designated as such in the EPA's Designate and Track reporting system: DMV015.
- Receipts from Wolverine Pipe Line will be accepted at a maximum of 12.0 ppm sulfur.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).
- Biofuel Components (e.g. biodiesel) are not permitted in this product.
- Intended to be consistent with ASTM Grade No. 1 middle distillate fuels, unless otherwise noted.
- Sulfur level at delivery will vary depending upon the origin and delivery location.



**BUCKEYE PARTNERS, L.P.**  
**SPECIFICATIONS FOR FUNGIBLE AVIATION/KEROSENE**  
**GRADE 152**  
 (Page 1 of 2)

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Appearance	White Bucket	Report		
Color, at origin	D156, D6045	18		1
at delivery		+16		
Gravity, API @ 60°F	D287, D1298, D4052	37	51	
Net Heat of Combustion, BTU/lb.	D3338, D4809, D4529	18,400		
Corrosion, 2 hrs. @ 212°F	D130		1	
Cetane Index	D976, D4737	40		
MSEP (refinery origin)	D3948	85		
(downstream of refinery)	D7224, D3948	85		
Sulfur, wt. %	D2622, D4294, D5453		0.04	
Doctor Test, OR	D1266,			
Mercaptan Sulfur, wt. %	D4952		Negative	
Aromatics, vol. %	D3227		0.003	3
Total Acidity, mg. KOH/g	D1319		25	
Existent Gum, mg/100 ml.	D3242		0.10	
THERMAL STABILITY (JFTOT)	D381		7	
(2.5 hrs at control temperature 275°C)	D3241			4
Filter Pressure drop, mm/Hg			25	
Tube Rating: One of the following requirements shall be met:				
(1) Annex A1 VTR, VTR color code			Less than 3	
(2) Annex A2 ITR or Annex 3 ETR			No peacock or abnormal color deposits	
nm average over area of 2.5 mm <sup>2</sup>			85	
Flash Point, °F	D56, D3828	108		
Physical Distillation, °F	D86			
10% recovered		Report	400	
50% recovered		Report		
90% recovered		Report		
End Point			572	
Residue, %			1.5	
Loss, %			1.5	
OR Simulated Distillation, °F	D2887			
10% recovered			365	
50% recovered		Report		
90% recovered			579	
End Point			644	
Freezing Point, °F	D5972, D7153, D7154, D2386		-40	
Viscosity, cst. @ -4°F	D445, D7945		8.0	
Viscosity, cst. @ 104°F	D445	1.0	1.9	
One of the following shall be met				
(1) Smoke Point, mm, or	D1322	25.0		
(2) Smoke Point, mm, and	D1322	18.0		
Naphthalenes, vol. %	D1840		3.0	
Ash, wt %	D482		0.01	
Carbon residue, wt % on 10% bottom	D524		0.15	
Burning Quality				
Time of Burning	D187		Min 16 h continuous after first weighing	
Burning Quality	IP 10		18 to 26 g/h after first weighing	
Chimney Appearance	D187		Max light white deposit (at end of test)	
Flame Characteristics	D187		Maximum variance of flame width (6mm) & flame height lowered (5 mm)	
Electrical Conductivity	D2624	Report		2
Additives		Report		2

**BUCKEYE PARTNERS, L.P.**  
**SPECIFICATIONS FOR FUNGIBLE AVIATION/KEROSENE**  
**GRADE 152**

(Page 2 of 2)

**NOTES:**

1. Product shall be clear (referring to clarity, not color) and bright and free of suspended matter, and must not exhibit various shades of green, blue or red.
2. Product shall only contain antioxidants and metal deactivators specified and within the concentration noted in the latest ASTM D1655 with advance approval from Buckeye prior to shipment. Use of these additives is expected to be short term at reasonable treat levels, and is to be clearly indicated on the CoA. All other additives are prohibited. Buckeye reserves the right to deny shipment of product containing these additives. In addition, scheduling and Measurement & Quality Control must be notified at least 72 hours prior to the scheduled shipment of any batches containing Metal Deactivator Additive (MDA). If MDA has been added to the product, Buckeye reserves the right to refuse shipment. If requesting to move a batch that has been treated with MDA, supply the following information to Buckeye Measurement & Quality Control: (1) the purpose for adding MDA, (2) JFTOT test results both prior to and after adding MDA, (3) MDA treat rate, and (4) MDA product used.
3. Mercaptan Sulfur waived if fuel is negative by Doctor test.
4. Refer to ASTM D1655 note M for referee method.
5. Product must comply with ASTM D1655 specifications in addition to Buckeye product specifications. Buckeye will accept test methods that are listed in ASTM D1655. Test methods listed above are considered referee methods by Buckeye Pipe Line.
6. This product is for use as aviation fuel or home heat and should be designated as "Kerosene" in the EPA's Designate and Track reporting system.
7. Biofuel Components (e.g. biodiesel) are not permitted in this product.
8. Intended to be consistent with ASTM D3699 and D1655, unless otherwise noted

**BUCKEYE PARTNERS, L.P.**  
**SPECIFICATIONS FOR FUNGIBLE No. 1 KEROSENE FUEL OIL 400 PPM SULFUR**  
**GRADE 154**

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color, at origin	D156, D6045	18		1
at delivery		+16		
Gravity, API @ 60°F	D287, D1298, D4052	37	51	
Corrosion, 3 hrs. @ 212°F	D130		1	
Sulfur, ppm (at receipt)	D2622, D4294, D1266, D1552		400	
Doctor Test	D4952		Negative	
OR				
Mercaptan Sulfur, mass %	D3227		0.003	2
Flash Point, °F	D56, D3828	108		
Physical Distillation, °F	D86			
10% recovered			419	
90% recovered			550	
End Point			572	
Freezing Point, °F	D5972, D7153, D7154, D2386		-22	
Viscosity, cst. @ 104°F	D445	1.0	1.9	
Carbon residue, wt % on 10% bottom	D524		0.15	
Burn Quality				
Time of Burning	D187		Min 16 h continuous after first weighing	
Burning Quality	IP 10		18 to 26 g/h after first weighing	
Chimney Appearance	D187		Max light white deposit (at end of test)	
Flame Characteristics	D187		Maximum variance of flame width (6mm) & flame height lowered (5 mm)	
Pour Point, °F	D5985, D5949, D5950, D97		0 °F /-18 °C	
Sediment and Water, % by volume	D2709		0.05	
NACE	TM0172-2001	B+		3
Smoke Point	D1322	18		

**NOTES:**

1. Product shall be clear (referring to clarity, not color) and bright and free of suspended matter.
2. Mercaptan Sulfur waived if fuel is negative by Doctor test.
3. All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).
4. This product should be designated as "Kerosene" in the EPA's Designate and Track reporting system.
5. Biofuel Components (e.g. biodiesel) are not permitted in this product.
6. Intended to be consistent with ASTM D3699, unless otherwise noted

**BUCKEYE PARTNERS, L.P.**  
**SPECIFICATIONS FOR FUNGIBLE ULSD-1(MOTOR VEHICLE)/AVIATION/ULSK**  
**GRADE 155**  
 (Page 1 of 2)

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Appearance	White Bucket	Report		
Color, at origin	D156, D6045	18		1
at delivery		+16		
Gravity, API @ 60°F	D287, D1298 or D4052	37	51	
Net Heat of Combustion, BTU/lb.	D3338, D4809, D4529	18,400		
Corrosion, 2 hrs. @ 212°F	D130		1	
Cetane Index	D976, D4737	40		
MSEP (refinery origin)	D3948	85		
(downstream of refinery)	D7224, D3948	85		
Sulfur, ppm (at receipt)	D2622, D4294, D5453		11	5,9
D1266,				
Doctor Test, OR	D4952		Negative	
Mercaptan Sulfur, wt. %	D3227		0.003	3
Aromatics, vol. %	D1319		25	
Total Acidity, mg. KOH/g	D3242		0.10	
Existent Gum, mg/100 ml.	D381		7	
THERMAL STABILITY (JFTOT)	D3241			4
(2.5 hrs at control temperature 275°C)				
Filter Pressure drop, mm/Hg			25	
Tube Rating: One of the following requirements shall be met:				
(1) Annex A1 VTR, VTR color code			Less than 3	
(2) Annex A2 ITR or Annex 3 ETR			No peacock or abnormal color deposits	
nm average over area of 2.5 mm <sup>2</sup>			85	
Flash Point, °F	D56, D3828	108		
Distillation, °F	D86			
10% recovered		Report	400	
50% recovered		Report		
90% recovered		Report	550	
End Point			572	
Residue, %			1.5	
Loss, %			1.5	
OR Simulated Distillation, °F	D2887			
10% recovered			365	
50% recovered		Report		
90% recovered			579	
End Point			644	
Freezing Point, °F	D5972, D7153, D7154, D2386		-40	
Viscosity, cst. @ -4°F	D445, D7945		8.0	
Viscosity, cst. @ 104°F	D445	1.3	1.9	
Smoke Point or	D1322	25.0		
Smoke Point and	D1322	18.0		
Naphthalenes, vol. %	D1840		3.0	
Ash, wt %	D482		0.01	
Carbon residue, wt % on 10% bottom	D524		0.15	
Burn Quality				
Time of Burning	D187		Min 16 h continuous after first weighing	
Burning Quality	IP 10		18 to 26 g/h after first weighing	
Chimney Appearance	D187		Max light white deposit (at end of test)	
Flame Characteristics	D187		Maximum variance of flame width (6mm) & flame height lowered (5 mm)	
Electrical Conductivity	D2624	Report		2
Additives		Report		2

**BUCKEYE PARTNERS, L.P.**  
**SPECIFICATIONS FOR FUNGIBLE ULSD-1 (MOTOR VEHICLE) / AVIATION / ULSK**  
**GRADE 155**  
(Page 2 of 2)

**NOTES:**

1. Product shall be clear (referring to clarity, not color) and bright and free of suspended matter, and must not exhibit various shades of green, blue or red.
2. Product shall only contain antioxidants and metal deactivators specified and within the concentration noted in the latest ASTM D1655 with advance approval from Buckeye prior to shipment. Use of these additives is expected to be short term at reasonable treat levels, and is to be clearly indicated on the CoA. All other additives are prohibited. Buckeye reserves the right to deny shipment of product containing these additives. In addition, Scheduling and Measurement & Quality Control must be notified at least 72 hours prior to the scheduled shipment of any batches containing Metal Deactivator Additive (MDA). If MDA has been added to the product, Buckeye reserves the right to refuse shipment. If requesting to move a batch that has been treated with MDA, supply the following information to Buckeye Measurement & Quality Control: (1) the purpose for adding MDA, (2) JFTOT test results both prior to and after adding MDA, (3) MDA treat rate, and (4) MDA product used.
3. Mercaptan Sulfur waived if fuel is negative by Doctor test.
4. Refer to ASTM D1655 note M for referee method.
5. Sulfur level at delivery will vary depending upon the origin and delivery location.
6. Product must comply with ASTM D1655 specifications in addition to Buckeye product specifications. Buckeye will accept test methods that are listed in ASTM D1655. Test methods listed above are considered referee methods by Buckeye Pipe Line.
7. This product is for Motor Vehicle use and should be designated as such in the EPA's Designate and Track reporting system: DMV015.
8. Biofuel Components (e.g. biodiesel) are not permitted in this product.
9. Receipts from Wolverine Pipe Line will be accepted at a maximum of 12.0 ppm sulfur.

**BUCKEYE PARTNERS, L.P.**  
**SPECIFICATIONS FOR FUNGIBLE HEATING OIL – DYED HIGH SULFUR**  
**GRADE 159 (500 PPM)**

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Gravity, API @ 60°F	D287, D4052	30		
Flash Point, °F(at Origin)	D93, D56, D7094	116	1	
Viscosity, cst @ 104°F	D445	1.9	4.1	
Cloud Point, °F (Sept thru March)	D2500, D5771, D5772,		+15°F	
(April thru August)	D5773, D3117		+20°F	
Pour Point, °F (Sept thru March)	D5985, D5949, D5950, D97		0°F	
(April thru August)			+10°F	
Total Sulfur, wt. %	D7039, D2622, D4294, D5453			See below Table

**High Sulfur Heating Oil Maximum Sulfur Table**

<b>Grade Code</b>	<b>Max Sulfur, wt %</b>
159	0.045

Corrosion, 3 hrs. @ 122°F	D130		1	
Oxidation Stability, mg/100 ml or	D2274			2.5
Thermal Stability, 90 minutes				
150°C Pad rating	DuPont			7
Carbon Residue, wt. % on				
10% bottom	D524 or D4530			0.35
Ash, wt. %	D482			0.01
Sediment and Water, % by volume	D2709			0.05
Physical Distillation, °F	D86			
50% recovered		Report		
90% recovered		540	640	
End Point			690	
OR Simulated Distillation, °F	D2887			
50% recovered		Report		
90% recovered		572	673	
End Point			790	
Haze Rating @ 77°F	D4176 (Procedure 2)			2
Biodiesel (FAME) %	D7371, EN14078			0.0 5, 8
Dye Content, ppm (at Origin)	D6258 or	13.0	16.0	2
	Petrospec-DT100			
NACE	TM0172-2001	B+		4

**NOTES:**

1. Test method D-93 is the referee method. Minimum flash at delivery is 108°F.
2. This product must contain red dye, standard solvent Red 26 or solvent Red 164, in concentrations of 4.6 lbs. or 6.6 lbs., respectively, of active dry ingredient per 1,000 barrels. Product must meet a maximum color of 2.5 per ASTM D1500 prior to introduction of dye.
3. The use of lubricity improver additives is prohibited.
4. All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).
5. Biofuel Components (e.g. biodiesel, FAME) are not permitted in this product. Results must be <LDL of the test method (i.e. <1.0% per D7371, or <0.50% per EN14078). FAME limits go into effect at Linden, NJ; Booth, PA; Macungie, PA; and New Haven, CT on June 1, 2014. FAME Limits will apply to all other receipt locations on September 5, 2014.
6. This product is for heating oil use and should be designated as HOUHRK per EPA's Designate & Track system.
7. Intended to be consistent with ASTM D396 Grade No. 2 middle distillate fuels, unless otherwise noted.
8. Shipments of this Grade Code are limited to less than 5.0% renewable diesel. Renewable diesel is a liquid fuel derived from 100% hydrotreated biomass that meets the registration requirements for fuels and fuel additives established by the EPA under Section 211 of the Clean Air Act and the requirements of ASTM D975. Fuel containing fatty acid esters (FAME, FAEE, or other esters) is prohibited.

**BUCKEYE PARTNERS, L.P.**  
**SPECIFICATIONS FOR FUNGIBLE HEATING OIL 15 PPM SULFUR (UNDYED)**  
**GRADE 164**

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Gravity, API @ 60°F	D287, D4052, D1298	30		
Flash Point, °F(at Origin)	D93, D56, D7094	130		1
Color, ASTM	D1500		2.5	
Viscosity, cst @ 104°F	D445, D7042	1.9	4.1	
Cloud Point, °F (Sept thru March)	D2500, D5771, D5772,		+15 °F	
(April thru August)	D5773, D3117, D7683		+20 °F	
Pour Point, °F (Sept thru March)	D5985, D5949, D5950, D97		0 °F	
(April thru August)			+10°F	
Total Sulfur, ppm (at receipt)	D5453, D3120, D4294		11	3,7,10
	D2622, D7039			
Corrosion, 3 hrs. @ 122°F	D130		1	
Oxidation Stability, mg/100 ml OR	D2274		2.5	
Thermal Stability, 90 minutes				
150°C Pad rating OR	DuPont		7	
Thermal Stability, Y/Green	D6468	73%		
W Unit		65%		
Carbon Residue, wt. % on 10% bottom	D524 or D4530		0.35	
Ash, wt. %	D482		0.01	
Sediment and Water, % by volume	D2709		0.05	
Cetane Number or Index	D4737,D613,D6890,D7170	40		
Aromatics (Vol%)	D1319		35.0	
or Aromatics by Cetane Index	D976	40		
Distillation, °F	D86			
50% recovered		Report		
90% recovered		540	640	
End Point			<del>700-690</del>	
or Simulated Distillation, °C(°F)	D2887			
50% recovered			Report	
90% recovered		300(572)	356(673)	
End Point			421(790)	
Haze Rating @ 77°F	D4176		2	
Procedure 2				
Biodiesel (FAME) %	D7371, EN14078		0.0	9, 11
Color Visual		Undyed		4
Additives				5, 6
Electrical Conductivity, pS/m @ 70°F	D2624		<del>250 Report</del>	5
NACE	TM0172-2001	B+		8

**NOTES:**

1. Test method D-93 is the referee method. Minimum flash at delivery is 125 °F.
2. Intended to be consistent with ASTM D975 Grade No. 2 middle distillate fuels, unless otherwise noted.
3. Receipts from Wolverine Pipe Line will be accepted at a maximum of 12.0 ppm sulfur.
4. Product must exhibit no visible evidence of dye.
5. Use of static dissipater/conductivity improver is restricted (See Table 1).
6. The use of lubricity improver additives is prohibited.
7. This product is for heating oil use and should be designated as HOUMRK in the EPA's Designate and Track reporting system.
8. All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).
9. Biofuel Components (e.g. biodiesel, FAME) are not permitted in this product. Results must be <LDL of the test method (i.e. <1.0% per D7371, or <0.50% per EN14078). FAME limits go into effect at Linden, NJ; Booth, PA; Macungie, PA; and New Haven, CT on June 1, 2014. FAME Limits will apply to all other receipt locations on September 5, 2014.
10. Sulfur level at delivery will vary depending upon the origin and delivery location.
11. Shipments of this Grade Code are limited to less than 5.0% renewable diesel. Renewable diesel is a liquid fuel derived from 100% hydrotreated biomass that meets the registration requirements for fuels and fuel additives established by the EPA under Section 211 of the Clean Air Act and the requirements of ASTM D975. Fuel containing fatty acid esters (FAME, FAEE, or other esters) is prohibited.

**BUCKEYE PARTNERS, L.P.**  
**SPECIFICATIONS FOR FUNGIBLE HEATING OIL - HIGH SULFUR UNDYED**  
**GRADE 169 (500 PPM)**

<b>PRODUCT PROPERTY</b>	<b>ASTM TEST METHODS</b>	<b>TEST RESULTS</b>		<b>NOTE</b>
		<b>MINIMUM</b>	<b>MAXIMUM</b>	
Gravity, API @ 60°F	D287, D4052	30		
Flash Point, °F(at Origin)	D93, D56, D7094	116	1	
Viscosity, cst @ 104°F	D445	1.9	4.1	
Color, ASTM	D1500, D6045		2.5	
Cloud Point, °F (Sept thru March)	D2500, D5771, D5772,		+15 °F	
(April thru August)	D5773, D3117		+20 °F	
Pour Point, °F (Sept thru March)	D5985, D5949, D5950, D97		0 °F	
(April thru August)			+10°F	
Total Sulfur, wt. %	D7039, D2622, D4294, D5453		See below Table	

**High Sulfur Heating Oil Maximum Sulfur Table**

<b>Grade Code</b>	<b>Max Sulfur, wt %</b>
169	0.045

Corrosion, 3 hrs. @ 122°F	D130		1	
Oxidation Stability, mg/100 ml or	D2274		2.5	
Thermal Stability, 90 minutes				
150°C Pad rating	DuPont		7	
Carbon Residue, wt. % on				
10% bottom	D524 or D4530		0.35	
Ash, wt. %	D482		0.01	
Sediment and Water, % by volume	D2709		0.05	
Physical Distillation, °F	D86			
50% recovered		Report		
90% recovered		540	640	
End Point			690	
OR Simulated Distillation, °F	D2887			
50% recovered		Report		
90% recovered		572	673	
End Point			790	
Haze Rating @ 77°F	D4176 (Procedure 2)		2	
Biodiesel (FAME) %	D7371, EN14078		0.0	5, 8
Color Visual		Undyed		
Electrical Conductivity, pS/m @ 70°F	D2624		Report	
NACE	TM0172-2001	B+		4

**NOTES:**

1. Test method D-93 is the referee method. Minimum flash at delivery is 108 °F.
2. Product must exhibit no visible evidence of dye.
3. The use of lubricity improver additives is prohibited.
4. All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).
5. Biofuel Components (e.g. biodiesel, FAME) are not permitted in this product. Results must be <LDL of the test method (i.e. <1.0% per D7371, or <0.50% per EN14078). FAME limits go into effect at Linden, NJ; Booth, PA; Macungie, PA; and New Haven, CT on June 1, 2014. FAME Limits will apply to all other receipt locations on September 5, 2014.
6. This product is for heating oil use and should be designated as HOUMRK in the EPA's Designate and Track reporting system.
7. Intended to be consistent with ASTM D396 Grade No. 2 middle distillate fuels, unless otherwise noted.
8. Shipments of this Grade Code are limited to less than 5.0% renewable diesel. Renewable diesel is a liquid fuel derived from 100% hydrotreated biomass that meets the registration requirements for fuels and fuel additives established by the EPA under Section 211 of the Clean Air Act and the requirements of ASTM D975. Fuel containing fatty acid esters (FAME, FAEE, or other esters) is prohibited.



**BUCKEYE PARTNERS, L.P.**  
**SPECIFICATIONS FOR FUNGIBLE AVIATION KEROSENE - GRADE 182 & 188**

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Appearance	White Bucket	Undyed		1
Color	D156, D6045	18		1
Gravity, API @ 60°F	D287, D1298, D4052	37	51	
Net Heat of Combustion, BTU/lb.	D3338, D4529, D4809	18,400		
Corrosion, 2 hrs. @ 212°F	D130		1	
MSEP (refinery origin)	D3948	85		
(downstream of refinery)	D7224, D3948	85		
Sulfur, wt. %	D2622, D4294, D5453, D1266		See below Table	

**Jet Fuel Maximum Sulfur Table**

Grade Code	Max Sulfur, wt %
182	0.30
188	0.0011

Doctor Test OR	D4952		Negative (Sweet)	
Mercaptan Sulfur, wt. %	D3227		0.003	3
Aromatics, vol. %	D1319		25	
Total Acidity, mg. KOH/g	D3242		0.10	
Existent Gum, mg/100 ml.	D381		7	
THERMAL STABILITY (JFTOT)	D3241			4
(2.5 hrs at control temperature 275°C)				
Filter Pressure drop, mm/Hg			25	
Tube Rating: One of the following requirements shall be met:				
(1) Annex A1 VTR, VTR color code			Less than 3	
(2) Annex A2 ITR or Annex 3 ETR			No peacock or abnormal color deposits	
nm average over area of 2.5 mm <sup>2</sup>			85	
Flash Point, °F	D56, D3828	108		
Distillation, °F	D86			
10% recovered			400	
50% recovered		Report		
90% recovered		Report		
End Point			572	
Residue, %			1.5	
Loss, %			1.5	
OR Simulated Distillation, °F	D2887			
10% recovered			365	
50% recovered		Report		
End Point			644	
Freezing Point, °F	D5972, D7153, D7154, D2386		-40	
Viscosity, cst. @ -4°F	D445, D7945		8.0	
One of the following shall be met				
(1) Smoke Point, mm, or	D1322	25.0		
(2) Smoke Point, mm, and	D1322	18.0		
Naphthalenes, vol. %	D1840		3.0	
Electrical Conductivity	D2624	Report		2
Additives		Report		2

**NOTES:**

- Product shall be clear (referring to clarity, not color) and bright and free of suspended matter, and must not exhibit various shades of green, blue or red.
- Product shall only contain antioxidants and metal deactivators specified and within the concentration noted in the latest ASTM D1655 with advance approval from Buckeye prior to shipment. Use of these additives is expected to be short term at reasonable treat levels, and is to be clearly indicated on the CoA. All other additives are prohibited. Buckeye reserves the right to deny shipment of product containing these additives. In addition, Scheduling and Measurement & Quality Control must be notified at least 72 hours prior to the scheduled shipment of any batches containing Metal Deactivator Additive (MDA). If MDA has been added to the product, Buckeye reserves the right to refuse shipment. If requesting to move a batch that has been treated with MDA, supply the following information to Buckeye Measurement & Quality Control: (1) the purpose for adding MDA, (2) JFTOT test results both prior to and after adding MDA, (3) MDA treat rate, and (4) MDA product used.
- Mercaptan Sulfur waived if fuel is negative by Doctor test.
- Refer to ASTM D1655 note M for referee method.
- Product must comply with ASTM D1655 specifications in addition to Buckeye product specifications. Buckeye will accept test methods that are listed in ASTM D1655. Test methods listed above are considered referee methods by Buckeye Pipe Line.

**BUCKEYE PARTNERS, L.P.**  
**SPECIFICATIONS FOR FUNGIBLE ULTRA LOW SULFUR DIESEL (MOTOR VEHICLE)**  
**GRADE 190**

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Gravity, API @ 60°F	D287, D4052, D1298	30		
Flash Point, °F(at Origin)	D93, D56, D7094	130		1
(Maine only - Dec thru March 14)		120		6
Color, ASTM	D1500		2.5	
Viscosity, cst @ 104°F	D445, D7042	1.9	4.1	
(Maine only - Dec thru March 14)		1.7		6
Cloud Point, °F (Sept thru March)	D2500, D5771, D5772,		+15 °F	
(April thru August)	D5773, D3117, D7683		+20 °F	
(Maine only - Dec thru March 14)			-16 °F	6
Pour Point, °F (Sept thru March)	D5985, D5949, D5950, D97		0 °F	
(April thru August)			+10°F	
Total Sulfur, ppm (at receipt)	D5453, D3120, D2622, D7039, D4294		11	3,7,8
Corrosion, 3 hrs. @ 122°F	D130		1	
Oxidation Stability, mg/100 ml OR	D2274		2.5	
Thermal Stability, 90 minutes				
150°C Pad rating OR	DuPont		7	
Thermal Stability, Y/Green	D6468	73%		
W Unit		65%		
Carbon Residue, wt. % on 10% bottom	D524 or D4530		0.35	
Ash, wt. %	D482		0.01	
Sediment and Water, % by volume	D2709		0.05	
Cetane Number or Index	D4737,D613,D6890,D7170	40		
Aromatics (Vol%)	D1319		35.0	
or Aromatics by Cetane Index	D976	40		
Distillation, °F	D86			
50% recovered		Report		
90% recovered		540	640	
End Point			700 <del>690</del>	
or Simulated Distillation, °C(°F)	D2887			
50% recovered			Report	
90% recovered		300(572)	356(673)	
End Point			421(790)	
Haze Rating @ 77°F	D4176		2	
Procedure 2				
Biodiesel (FAME) %	D7371, EN14078		0.0	10,11
Color Visual		Undyed		4
Additives				5
Electrical Conductivity, pS/m @ 70°F	D2624		250 <del>Report</del>	5
NACE	TM0172-2001	B+		9

**NOTES:**

1. Test method D-93 is the referee method. Minimum flash at delivery is 125 °F.
2. Intended to be consistent with ASTM D975 Grade No. 2 middle distillate fuels, unless otherwise noted.
3. Receipts from Wolverine Pipe Line will be accepted at a maximum of 12.0 ppm sulfur.
4. Product must exhibit no visible evidence of dye.
5. Use of static dissipater/conductivity improver is restricted (See Table 1). Lubricity improver additive is prohibited.
6. For winter (December 1 through March 14) receipt of ULSD in State of Maine only.
7. This product is for Motor Vehicle use and designated as such in EPA's Designate and Track reporting system: DMV015.
8. Sulfur level at delivery will vary depending upon the origin and delivery location.
9. All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).
10. Biofuel Components (e.g. biodiesel, FAME) are not permitted in this product. Results must be <LDL of the test method (i.e. <1.0% per D7371, or <0.50% per EN14078). FAME limits go into effect at Linden, NJ; Booth, PA; Macungie, PA; and New Haven, CT on June 1, 2014. FAME Limits will apply to all other receipt locations on September 5, 2014.
11. Shipments of this Grade Code are limited to less than 5.0% renewable diesel. Renewable diesel is a liquid fuel derived from 100% hydrotreated biomass that meets the registration requirements for fuels and fuel additives established by the EPA under Section 211 of the Clean Air Act and the requirements of ASTM D975. Fuel containing fatty acid esters (FAME, FAEE, or other esters) is prohibited.

**BUCKEYE PARTNERS, L.P.**  
**SPECIFICATIONS FOR FUNGIBLE ULTRA LOW SULFUR DIESEL (NON-ROAD)**  
**GRADE 193**

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Gravity, API @ 60°F	D287, D4052, D1298	30		
Flash Point, °F(at Origin)	D93, D56, D7094	130		1
Color, ASTM	D1500		2.5	
Viscosity, cst @ 104°F	D445, D7042	1.9	4.1	
Cloud Point, °F (Sept thru March)	D2500, D5771, D5772,		+15 °F	
(April thru August)	D5773, D3117, D7683		+20 °F	
Pour Point, °F (Sept thru March)	D5985, D5949, D5950, D97		0 °F	
(April thru August)			+10°F	
Total Sulfur, ppm (at receipt)	D5453, D312, D4294		11	3,7,8
	D2622, D7039			
Corrosion, 3 hrs. @ 122°F	D130		1	
Oxidation Stability, mg/100 ml OR	D2274		2.5	
Thermal Stability, 90 minutes				
150°C Pad rating OR	DuPont		7	
Thermal Stability, Y/Green	D6468	73%		
W Unit		65%		
Carbon Residue, wt. % on 10% bottom	D524 or D4530		0.35	
Ash, wt. %	D482		0.01	
Sediment and Water, % by volume	D2709		0.05	
Cetane Number or Index	D4737,D613,D6890,D7170	40		
Aromatics (Vol%)	D1319		35.0	
or Aromatics by Cetane Index	D976	40		
Distillation, °F	D86			
50% recovered		Report		
90% recovered		540	640	
End Point			700 <del>690</del>	
or Simulated Distillation, °C(°F)	D2887			
50% recovered			Report	
90% recovered		300(572)	356(673)	
End Point			421(790)	
Haze Rating @ 77°F	D4176		2	
Procedure 2				
Biodiesel (FAME) %	D7371, EN14078		0.0	10,11
Color Visual		Undyed		4
Additives				5, 6
Electrical Conductivity, pS/m @ 70°F	D2624		250 Report	5
NACE	TM0172-2001	B+		9

**NOTES:**

1. Test method D-93 is the referee method. Minimum flash at delivery is 125 °F.
2. Intended to be consistent with ASTM D975 Grade No. 2 middle distillate fuels, unless otherwise noted.
3. Receipts from Wolverine Pipe Line will be accepted at a maximum of 12.0 ppm sulfur.
4. Product must exhibit no visible evidence of dye.
5. Use of static dissipater/conductivity improver **is restricted (See Table 1)**.
6. The use of lubricity improver additives is prohibited.
7. This product is for Non-Road use and should be designated as DNR015 in the EPA's Designate and Track system.
8. Sulfur level at delivery will vary depending upon the origin and delivery location.
9. All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).
10. Biofuel Components (e.g. biodiesel, FAME) are not permitted in this product. Results must be <LDL of the test method (i.e. <1.0% per D7371, or <0.50% per EN14078). FAME limits go into effect at Linden, NJ; Booth, PA; Macungie, PA; and New Haven, CT on June 1, 2014. FAME Limits will apply to all other receipt locations on September 5, 2014.
11. Shipments of this Grade Code are limited to less than 5.0% renewable diesel. Renewable diesel is a liquid fuel derived from 100% hydrotreated biomass that meets the registration requirements for fuels and fuel additives established by the EPA under Section 211 of the Clean Air Act and the requirements of ASTM D975. Fuel containing fatty acid esters (FAME, FAEE, or other esters) is prohibited.

**BUCKEYE PARTNERS, L.P.**  
**SPECIFICATIONS FOR FUNGIBLE CONVENTIONAL GASOLINE**  
**SUB-OCTANE REGULAR GRADES 308, 318, 328, 338, 358, 378**  
**PREMIUM GRADES 307, 317, 327, 337, 357, 377**  
 (Page 1 of 3)

**SPECIFICATIONS FOR SUBGRADE GASOLINE PRIOR TO ETHANOL ADDITION**

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		
Haze Rating @ 77°F (Procedure 2)	D4176		2	
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating for 90 Octane Grades (Neat) (307, 317, 327, 337, 347, 357, 377)				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	Report		
Index, (R+M)/2		90.0		13
Oxygenates, vol. %	D4815, D5599, D5845		Report	2
Benzene, vol. %	D3606, D4053, D5443		3.8	
Sulfur, wt. %	D2622, D5453, D3120, D7039		0.0080	
Doctor Test	D4952		Negative	3
Or Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237, D5059		0.01	
Phosphorous, gms/gal	D3231		0.004	
Solvent washed Gum, mg/100ml	D381		4	
Oxidation Stability, minutes	D525	240		
Odor		Nonoffensive		4
Port Fuel Injector, Intake Valve Detergent Additives and MMT				5, 6
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators - Refer to Table 1				
Distillation	D86	Refer to Table 2 (pg 5)		
TV/L 20, Deg F	D5188	Refer to Table 2 (pg 5)		10
Driveability Index	D4814	Refer to Table 2 (pg 5)		7
Silver Strip Corrosion	D7667, D7671		1	
NACE	TM0172-2001	B+		8
RVP, psi (without ethanol)	D5191, D5482		See below Table	9,11,12

**Subgrade RVP Maximum Table**

Grade Code	Max RVP, psi (without ethanol)
307, 308	9.00 <sup>A</sup>
317, 318	15.0 14.5 (East, Laurel, Paulsboro)*
327, 328	7.80 <sup>B</sup>
337, 338	7.00
357, 358	13.5 12.9 (East, Laurel, Paulsboro)*
377, 378	11.5

\* **Eastern Products, Paulsboro and Laurel:** RVP limit for 13.5 months is 12.9 psi; RVP limit for 15 psi months is 14.5 psi. **Wood River, NORCO, Lower V & Midwest (excluding MI delivery locations):** RVP limit for Sept 16 through Sept 30 is 11.5 psi (refer to Table 2). **For all other product systems,** RVP limit is 13.5 psi and 15.0 psi (refer to Table 2). See T4 Scheduling Calendar for RVP stepdown dates/cycles for each system.

<sup>A</sup> Max RVP of 8.8 psi (without ethanol) for batches receipted into Buckeye during March and April  
<sup>B</sup> Max RVP of 7.6 psi (without ethanol) for batches receipted into Buckeye during March and April

**BUCKEYE PARTNERS, L.P.**  
**SPECIFICATIONS FOR FUNGIBLE CONVENTIONAL GASOLINE**  
**SUB-OCTANE REGULAR GRADES 308, 318, 328, 338, 358, 378**  
**PREMIUM GRADES 307, 317, 327, 337, 357, 377**

(Page 2 of 3)

**SPECIFICATIONS WITH 10% DENATURED ETHANOL AS DEFINED IN ASTM D4806**

PRODUCT PROPERTY	ASTM TEST METHODS	TEST RESULTS		NOTE
		MINIMUM	MAXIMUM	
Octane Rating with 10% Denatured Fuel Ethanol				
Regular Grades (308, 318, 328, 338, 348, 358, 378)				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	82.0		
Index, (R+M)/2		87.0		
Premium Grades (307, 317, 327, 337, 347, 357, 377)				
Research Number	D2699, D2885	Report		13
Motor Number	D2700, D2885	Report		
Index, (R+M)/2		93.0		
RVP, psi with 10% Denatured Fuel Ethanol	D5191, D5482		See below Table	9,11,12

**Subgrade RVP Maximum Table (w/ 10% denatured ethanol)**

Grade Code	Max RVP, psi (with 10 vol% ethanol)
307, 308	10.00 <sup>C</sup>
317, 318	15.5 15.0 (East, Laurel, Paulsboro)*
327, 328	9.00 <sup>D</sup>
337, 338	8.00
357, 358	14.5 13.5 (East, Laurel, Paulsboro)*
377, 378	12.5

\* **Eastern Products, Paulsboro and Laurel:** RVP limit for 13.5 months is 13.5 psi; RVP limit for 15.0 months is 15.0 psi.  
**Wood River, NORCO, Lower V & Midwest (excluding MI delivery locations):** RVP limit for Sept 16 through Sept 30 is 12.5 psi (refer to Table 2). **For all other product systems,** RVP limit is 14.5 psi and 15.5 psi (refer to Table 2). See T4 Scheduling Calendar for RVP stepdown dates/cycles for each system.

<sup>C</sup> Max RVP of 9.8 psi (with 10% ethanol) for batches received into Buckeye during March and April

<sup>D</sup> Max RVP of 8.8 psi (with 10% ethanol) for batches received into Buckeye during March and April

Distillation**	D86			
50% Evap (T50) with 10% Denatured Fuel Ethanol, Deg F		150	Table 2 (pg 5)	
TV/L** with 10% Den Fuel Ethanol, Deg F	D5188	See below Table		10

**Subgrade TV/L Minimum Table**

Class (As depicted in Table 2)	Min TV/L = 20, °F (°C) (with 10 vol% ethanol)
1	129 (54)
2	122 (50)
3	116 (47)
4	107 (42)
5	102 (39)

\*\*Grades 337 and 338 do not require 10% Denatured Fuel Ethanol specifications for Distillation or TVL.

**BUCKEYE PARTNERS, L.P.**  
**SPECIFICATIONS FOR FUNGIBLE CONVENTIONAL GASOLINE**  
**SUB-OCTANE REGULAR GRADES 308, 318, 328, 338, 358, 378**  
**PREMIUM GRADES 307, 317, 327, 337, 357, 377**

(Page 3 of 3)

**NOTES:**

1. No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
2. This product may not contain oxygenates, such as ethers or alcohols. The use of non-hydrocarbon blending components is prohibited. The di minimis limit of MTBE, ETBE, and TAME allowed is 0.3 vol. % maximum for each compound at origin.
3. Mercaptan Sulfur waived if fuel is negative by Doctor test.
4. Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
5. The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
6. The use of MMT octane enhancing additive is prohibited.
7. The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2. DI limit can apply prior to *OR* after blending with 10% Denatured Fuel Ethanol.
8. All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).
9. Not all Grade Codes (and RVPs) are available on all pipeline systems.
10. Computer and Linear methods may be used to determine TV/L value. D5188 will be the referee method.
11. Beginning Sept 16 (Non-VOC season), low RVP grades may be comingled with corresponding next higher RVP grade. Buckeye reserves the right to regrade to higher RVP during seasonal RVP limit increases, provided destination RVP compliance is maintained at time of delivery.
12. Suitable for the special RVP provisions for ethanol blends that contain between 9 and 10 vol% ethanol. The use of this gasoline to manufacture a gasoline-ethanol blend containing anything other than between 9 and 10 volume percent ethanol may cause a summertime RVP violation. Base gasoline - Not for sale to the ultimate consumer.
13. When blended with 10% denatured ethanol, grades 307, 317, 327, 337, 357 and 377 are 93 Octane. These grades are 90 Octane minimum without 10% denatured ethanol and may not be considered premium in all areas as such.

**BUCKEYE PARTNERS, L.P.**  
**SPECIFICATIONS FOR FUNGIBLE VOC CONTROLLED**  
**REFORMULATED REGULAR GASOLINE BLENDSTOCK (RBOB) FOR BLENDING**  
**WITH 10% DENATURED FUEL ETHANOL AS DEFINED IN ASTM D4806**  
**GRADE 522, 532, AND 552**

(Page 1 of 2)

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		12
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	82.0		
Index, (R+M)/2		87.0		
Oxygen, wt. %	D5599, GC-OFID	Report		2, 3, 9
RVP, psi	D5191		Table 2	3
Benzene, vol. %	D3606		1.30	
Doctor Test OR	D4952		Negative	4
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237 or equiv.		0.01	
Phosphorous, gms/gal	D3231		0.004	
Solvent washed Gum, mg/100ml	D381		4	
Oxidation Stability, minutes	D525	240		
Aromatics, vol. %	GCMS, D5769, D1319		50.0	3
Emissions Performance Reductions				
Grade 532 - VOC Region 2, %	EPA	25.4		10
Grade 522 - VOC Reg 2 Adj (Chicago), %	EPA	23.4		
Grade 552 - VOC Region 1, %	EPA	27.0		
Olefins, vol. %	D1319, D6550		25.0	
Sulfur, wt. %	D2622, D5453, D3120, D7039		.0080	
Odor		Nonoffensive		5
Port Fuel Injector and Intake Valve Detergent Additives				6
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators - Refer to Table 1				
Distillation -	D86			
50% Evap (T50), Deg F		150	Table 2	
All other Volatility and Distillation – Refer to Table 2				
E200, vol. %	D86	30.0	70.0	
E300, vol. %	D86	70.0	100.0	
MMT				7
Driveability Index	D4814			8
Refer to Table 2				
Silver Strip Corrosion	D7667, D7671		1	
NACE	TM0172-2001	B+		11, 12
TV/L with 10% Ethanol, Deg F	D5188	See below Table		

**TV/L Minimum Table**

<b>Class (As depicted in Table 2)</b>	<b>Min TV/L = 20, °F (°C) (with 10 vol% ethanol)</b>
1	129 (54)
2	122 (50)
3	116 (47)
4	107 (42)
5	102 (39)

**BUCKEYE PARTNERS, L.P.  
SPECIFICATIONS FOR FUNGIBLE VOC CONTROLLED  
REFORMULATED REGULAR GASOLINE BLENDSTOCK (RBOB) FOR BLENDING  
WITH 10% DENATURED FUEL ETHANOL AS DEFINED IN ASTM D4806  
GRADE 522, 532, AND 552**

(Page 2 of 2)

**This RBOB may not be combined with any other RBOB except RBOB having the same requirement for oxygenate type and amount.**

**All parameters must be met after blending with denatured fuel ethanol unless otherwise noted.**

**NOTES:**

1. No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
2. This product may not contain oxygenates such as ethers or alcohols. The use of non-hydrocarbon blending components is prohibited. The maximum limit of MTBE, ETBE, and TAME allowed is 0.3 vol.% maximum for each compound at origin.
3. Refer to test methods published in 40 CFR Chapter 1, Part 80.46.
4. Mercaptan Sulfur waived if fuel is negative by Doctor test.
5. Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
6. The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
7. The use of MMT octane enhancing additive is prohibited.
8. The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2 and will apply after blending with 10% Denatured Fuel Ethanol.
9. Oxygen content must meet a minimum of 1.5 wt. % and a maximum of 4.0 wt. % after blending with Denatured Fuel Ethanol.
10. The listed VOC reduction is required at origin. The VOC reduction at delivery will meet EPA requirements.
11. All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).
12. Only applies before blending with ethanol.



**BUCKEYE PARTNERS, L.P.**  
**SPECIFICATIONS FOR FUNGIBLE VOC CONTROLLED**  
**REFORMULATED PREMIUM GASOLINE BLENDSTOCK (RBOB) FOR BLENDING**  
**WITH 10% DENATURED FUEL ETHANOL AS DEFINED IN ASTM D4806**  
**GRADE 525, 535 AND 555**

(Page 1 of 2)

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		12
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	Report		
Index, (R+M)/2		93.0		
Oxygen, wt. %	D5599, GC-OFID	Report		2,3, 9
RVP, psi	D5191		Table 2	3
Benzene, vol. %	D3606		1.30	
Doctor Test OR	D4952		Negative	4
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237 or equiv.		0.01	
Phosphorous, gms/gal	D3231		0.004	
Solvent washed Gum, mg/100ml	D381		4	
Oxidation Stability, minutes	D525	240		
Aromatics, vol. %	GCMS, D5769, D1319		50.0	3
Emissions Performance Reductions				
Grade 535 - VOC Region 2, %	EPA	25.4		10
Grade 525 - VOC Reg 2 Adj (Chicago), %	EPA	23.4		
Grade 555 - VOC Region 1, %	EPA	27.0		
Olefins, vol. %	D1319, D6550		25.0	
Sulfur, wt. %	D2622, D5453, D3120, D7039		.0080	
Odor		Nonoffensive		5
Port Fuel Injector and Intake Valve Detergent Additives				6
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators - Refer to Table 1				
Distillation -	D86			
50% Evap (T50), Deg F		150	Table 2	
All other Volatility and Distillation – Refer to Table 2				
E200, vol. %	D86	30.0	70.0	
E300, vol. %	D86	70.0	100.0	
MMT				7
Driveability Index	D4814			8
Refer to Table 2				
Silver Strip Corrosion	D7667, D7671		1	
NACE	TM0172-2001	B+		11, 12
TV/L with 10% Ethanol, Deg F	D5188	See below Table		

**TV/L Minimum Table**

<b>Class (As depicted in Table 2)</b>	<b>Min TV/L = 20, °F (°C) (with 10 vol% ethanol)</b>
1	129 (54)
2	122 (50)
3	116 (47)
4	107 (42)
5	102 (39)

**BUCKEYE PARTNERS, L.P.**  
**SPECIFICATIONS FOR FUNGIBLE VOC CONTROLLED**  
**REFORMULATED PREMIUM GASOLINE BLENDSTOCK (RBOB) FOR BLENDING**  
**WITH 10% DENATURED FUEL ETHANOL AS DEFINED IN ASTM D4806**  
**GRADE 525, 535 AND 555**

(Page 2 of 2)

**This RBOB may not be combined with any other RBOB except RBOB having the same requirement for oxygenate type and amount.**

**All parameters must be met after blending with denatured fuel ethanol unless otherwise noted.**

**NOTES:**

1. No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
2. This product may not contain oxygenates such as ethers or alcohols. The use of non-hydrocarbon blending components is prohibited. The di minimis limit of MTBE, ETBE, and TAME allowed is 0.3 vol.% maximum for each compound at origin.
3. Refer to test methods published in 40 CFR Chapter 1, Part 80.46.
4. Mercaptan Sulfur waived if fuel is negative by Doctor test.
5. Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
6. The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
7. The use of MMT octane enhancing additive is prohibited.
8. The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2 and will apply after blending with 10% Denatured Fuel Ethanol.
9. Oxygen content must meet a minimum of 1.5 wt. % and a maximum of 4.0 wt. % after blending with Denatured Fuel Ethanol.
10. The listed VOC reduction is required at origin. The VOC reduction at delivery will meet EPA requirements.
11. All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).
12. Only applies before blending with ethanol.

**BUCKEYE PARTNERS, L.P.**  
**SPECIFICATIONS FOR FUNGIBLE NON-VOC CONTROLLED**  
**REFORMULATED REGULAR GASOLINE BLENDSTOCK (RBOB) FOR BLENDING**  
**WITH 10% DENATURED FUEL ETHANOL AS DEFINED IN ASTM D4806**  
**GRADE 542, 572 AND 582**

(Page 1 of 2)

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		11
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	82.0		
Index, (R+M)/2		87.0		
Oxygen, wt. %	D5599, GC-OFID	Report		2,3, 9
RVP, psi	D5191			3
Grade 542 - Non-VOC, psi			15.0	
Grade 582 - Non-VOC, psi			13.5	
Grade 572 - Non-VOC, psi			11.5	
Benzene, vol. %	D3606		1.30	
Doctor Test OR		D4952	Negative	4
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237 or equiv.		0.01	
Phosphorous, gms/gal	D3231		0.004	
Solvent washed Gum, mg/100ml	D381		4	
Oxidation Stability, minutes	D525	240		
Aromatics, vol. %	GCMS, D5769, D1319		Report	3
Olefins, vol. %	D1319, D6550		Report	
Sulfur, wt. %	D2622, D5453, D3120, D7039		.0080	
Odor	Nonoffensive			5
Port Fuel Injector and Intake Valve Detergent Additives				6
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators - Refer to Table 1				
Distillation -	D86			
50% Evap (T50), Deg F		150	Table 2	
All other Volatility and Distillation – Refer to Table 2				
E200, vol. %	D86	30.0	70.0	
E300, vol. %	D86	70.0	100.0	
MMT				7
Driveability Index (DI)	D4814			8
Refer to Table 2				
Silver Strip Corrosion	D7667, D7671		1	
NACE	TM0172-2001	B+		10, 11
TV/L with 10% Ethanol, Deg F	D5188	See below Table		

**TV/L Minimum Table**

<b>Class (As depicted in Table 2)</b>	<b>Min TV/L = 20, °F (°C) (with 10 vol% ethanol)</b>
1	129 (54)
2	122 (50)
3	116 (47)
4	107 (42)
5	102 (39)

**BUCKEYE PARTNERS, L.P.  
SPECIFICATIONS FOR FUNGIBLE NON-VOC CONTROLLED  
REFORMULATED REGULAR GASOLINE BLENDSTOCK (RBOB) FOR BLENDING  
WITH 10% DENATURED FUEL ETHANOL AS DEFINED IN ASTM D4806  
GRADE 542, 572 AND 582**

(Page 2 of 2)

**This RBOB may not be combined with any other RBOB except RBOB having the same requirement for oxygenate type and amount.**

**All parameters must be met after blending with denatured fuel ethanol unless otherwise noted.**

**NOTES:**

1. No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
2. This product may not contain oxygenates such as ethers or alcohols. The use of non-hydrocarbon blending components is prohibited. The maximum limit of MTBE, ETBE, and TAME allowed is 0.3 vol.% maximum for each compound at origin.
3. Refer to test methods published in 40 CFR Chapter 1, Part 80.46.
4. Mercaptan Sulfur waived if fuel is negative by Doctor test.
5. Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
6. The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
7. The use of MMT octane enhancing additive is prohibited.
8. The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2 and will apply after blending with 10% Denatured Fuel Ethanol.
9. Oxygen content must meet a minimum of 1.5 wt. % and a maximum of 4.0 wt. % after blending with Denatured Fuel Ethanol.
10. All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).
11. Only applies before blending with ethanol.

**BUCKEYE PARTNERS, L.P.**  
**SPECIFICATIONS FOR FUNGIBLE NON-VOC CONTROLLED**  
**REFORMULATED PREMIUM GASOLINE BLENDSTOCK (RBOB) FOR BLENDING**  
**WITH 10% DENATURED FUEL ETHANOL AS DEFINED IN ASTM D4806**  
**GRADE 545, 575 AND 585**

(Page 1 of 2)

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		11
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	Report		
Index, (R+M)/2		93.0		
Oxygen, wt. %	D5599, GC-OFID	Report		2,3, 9
RVP, psi	D5191			3
Grade 545 – Non-VOC, psi			15.0	
Grade 585 – Non-VOC, psi			13.5	
Grade 575 – Non-VOC, psi			11.5	
Benzene, vol. %	D3606		1.30	
Doctor Test OR	D4952		Negative	4
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237 or equiv.		0.01	
Phosphorous, gms/gal	D3231		0.004	
Solvent washed Gum, mg/100ml	D381		4	
Oxidation Stability, minutes	D525	240		
Aromatics, vol. %	GCMS, D5769, D1319		Report	3
Olefins, vol. %	D1319, D6550		Report	
Sulfur, wt. %	D2622, D5453, D3120, D7039		.0080	
Odor	Nonoffensive			5
Port Fuel Injector and Intake Valve Detergent Additives			6	
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators - Refer to Table 1				
Distillation -	D86			
50% Evap (T50), Deg F		150	Table 2	
All other Volatility and Distillation – Refer to Table 2				
E200, vol. %	D86	30.0	70.0	
E300, vol. %	D86	70.0	100.0	
MMT				7
Driveability Index (DI)	D4814			8
Refer to Table 2				
Silver Strip Corrosion	D7667, D7671		1	
NACE	TM0172-2001	B+		10, 11
TV/L with 10% Ethanol, Deg F	D5188	See below Table		

**TV/L Minimum Table**

<b>Class (As depicted in Table 2)</b>	<b>Min TV/L = 20, °F (°C) (with 10 vol% ethanol)</b>
1	129 (54)
2	122 (50)
3	116 (47)
4	107 (42)
5	102 (39)

**BUCKEYE PARTNERS, L.P.**  
**SPECIFICATIONS FOR FUNGIBLE NON-VOC CONTROLLED**  
**REFORMULATED PREMIUM GASOLINE BLENDSTOCK (RBOB) FOR BLENDING**  
**WITH 10% DENATURED FUEL ETHANOL AS DEFINED IN ASTM D4806**  
**GRADE 545, 575 AND 585**

(Page 2 of 2)

**This RBOB may not be combined with any other RBOB except RBOB having the same requirement for oxygenate type and amount.**

**All parameters must be met after blending with denatured fuel ethanol unless otherwise noted.**

**NOTES:**

1. No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
2. This product may not contain oxygenates such as ethers or alcohols. The use of non-hydrocarbon blending components is prohibited. The di minimis limit of MTBE, ETBE, and TAME allowed is 0.3 vol.% maximum for each compound at origin.
3. Refer to test methods published in 40 CFR Chapter 1, Part 80.46.
4. Mercaptan Sulfur waived if fuel is negative by Doctor test.
5. Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
6. The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
7. The use of MMT octane enhancing additive is prohibited.
8. The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2 and will apply after blending with 10% Denatured Fuel Ethanol.
9. Oxygen content must meet a minimum of 1.5 wt. % and a maximum of 4.0 wt. % after blending with Denatured Fuel Ethanol.
10. All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).
11. Only applies before blending with ethanol.