

BUCKEYE PIPE LINE COMPANY, L.P.
BUCKEYE PIPE LINE TRANSPORTATION LLC
LAUREL PIPE LINE COMPANY, L.P.
NORCO PIPE LINE COMPANY, LLC
WOOD RIVER PIPE LINES LLC

FUNGIBLE

PRODUCT GRADE SPECIFICATIONS

6.3 PRODUCT GRADE SPECIFICATIONS

This section contains specifications for products which are handled on a fungible or common-stream basis. A "fungible batch" is defined as a batch of petroleum product meeting Carrier's specifications which may be commingled with other batches of petroleum product meeting the same specifications.

<u>INDEX</u>	<u>PAGE NO.</u>
Table 1 Approved Gum Inhibitors and Metal Deactivators for Gasoline Approved Corrosion Inhibitors and Lubricity Improvers for Gasoline, Diesel Fuel and Fuel Oil	5
Table 2 Seasonal Gasoline Distillation and Volatility Classes	6
Grade 086 – Normal Butane (Midwest Origin to Fungible Destinations)	7
Grade 088 – Propane (Midwest Origin to Fungible Destinations)	8
Grade 130 - Low Sulfur Diesel/Fuel Oil - 0.042% Sulfur (Off Road) – DNRLM500	9
Grade 132 - Low Sulfur Diesel/Fuel Oil - 0.042% Sulfur (Off Road) – DNRLM500 (Buckeye-Midwest Pipeline System and Wood River System)	10
Grade 150 – Ultra Low Sulfur Kerosene (Off Road) – DNRLM015	11
Grade 151 – Ultra Low Sulfur Diesel #1 (On Road) – DMV1D015	12
Grade 152 – Aviation/Kerosene (Off Road) – DNRLM500	13
Grade 153 - Aviation/Low Sulfur Diesel #1 (On Road) – DMV1D500	15
Grade 155 – Multi-Purpose ULSD-1/Aviation/ULSK (On Road) – DMV1D015	17
Grade 160 - Fuel Oil - 0.20% Sulfur (Linden, NJ and Boothwyn, PA Area Origins Only)	19
Grade 161 - Fuel Oil - 0.50% Sulfur	20
Grade 162 – Fuel Oil - 0.50% Sulfur	21
Grade 163 – High Sulfur NRLM - 0.50% Sulfur – DNRLMHS	22
Grade 170 - Low Sulfur Diesel/Fuel Oil - 0.042% Sulfur (On Road) – DMV2D500 (Linden, NJ and Boothwyn, PA Area Origins Only)	23
Grade 172 - Low Sulfur Diesel/Fuel Oil - 0.042% Sulfur (On Road) – DMV2D500 (Buckeye-Midwest Pipeline System and Wood River System)	24
Grade 182 - Aviation Kerosene	25
Grade 190 – Ultra Low Sulfur Diesel - 0.0015% Sulfur (On Road) – DMV2D015	26

<u>INDEX</u>	<u>PAGE NO.</u>
Grade 302 - Low RVP — 87 Octane MTBE-FREE Conventional Gasoline	27
Grade 305 - Low RVP — 93 Octane MTBE-FREE Conventional Gasoline	28
Grade 307 – Low RVP – 91 Octane MTBE-FREE Conventional Gasoline	29
Grade 308 – Low RVP – Sub-Octane MTBE-FREE Conventional Gasoline	30
Grade 312 - 87 Octane MTBE-FREE Conventional Gasoline	31
Grade 315 - 93 Octane MTBE-FREE Conventional Gasoline	32
Grade 317 – 91 Octane MTBE-FREE Conventional Gasoline	33
Grade 318 – Sub-Octane MTBE-FREE Conventional Gasoline	34
Grade 322 – Low RVP 87 Octane MTBE-FREE Conventional Gasoline	35
Grade 325 – Low RVP 93 Octane MTBE-FREE Conventional Gasoline	36
Grade 327 – Low RVP 91 Octane MTBE-FREE Conventional Gasoline	37
Grade 328 – Low RVP Sub-Octane MTBE-FREE Conventional Gasoline	38
Grade 332 – Low RVP 87 Octane MTBE-FREE Conventional Gasoline (S.E. Michigan Only)	39
Grade 335 – Low RVP 93 Octane MTBE-FREE Conventional Gasoline (S.E. Michigan Only)	40
Grade 337 – Low RVP 91 Octane MTBE-FREE Conventional Gasoline (S.E. Michigan Only)	41
Grade 338 – Low RVP Sub-Octane MTBE-FREE Conventional Gasoline (S.E. Michigan Only)	42
Grade 502 - VOC Controlled Region 2 — 87 Octane Reformulated Gasoline (Long Island System Only)	43
Grade 503 - VOC Controlled Region 2 — 89 Octane Reformulated Gasoline (Long Island System Only)	44
Grade 505 - VOC Controlled Region 2 — 93 Octane Reformulated Gasoline (Long Island System Only)	45
Grade 512 - Non-VOC Controlled Region 2 — 87 Octane Reformulated Gasoline (Long Island System Only)	46
Grade 513 - Non-VOC Controlled Region 2 — 89 Octane Reformulated Gasoline (Long Island System Only)	47

<u>INDEX</u>	<u>PAGE NO.</u>
Grade 515 - Non-VOC Controlled Region 2 — 93 Octane Reformulated Gasoline (Long Island System Only)	48
Grade 532 - VOC Controlled Region 2 — Regular RBOB for 10% Ethanol Blending (Long Island System Only)	49
Grade 535 - VOC Controlled Region 2 — Premium RBOB for 10% Ethanol Blending (Long Island System Only)	51
Grade 542 - Non-VOC Controlled Region 1 & 2 — Regular RBOB for 10% Ethanol Blending (Long Island System and Wood River System)	53
Grade 545 - Non-VOC Controlled Region 1 & 2 — Premium RBOB for 10% Ethanol Blending (Long Island System and Wood River System)	55
Grade 552 - VOC Controlled Region 1 — Regular RBOB for 10% Ethanol Blending (Wood River System Only)	57
Grade 555 - VOC Controlled Region 1 — Premium RBOB for 10% Ethanol Blending (Wood River System Only)	59
Grade 732 - VOC Controlled Region 2 — Regular RBOB for 5.7% Ethanol Blending (Long Island System Only)	61
Grade 735 - VOC Controlled Region 2 — Premium RBOB for 5.7% Ethanol Blending (Long Island System Only)	63
Grade 742 - Non-VOC Controlled Region 2 — Regular RBOB for 5.7% Ethanol Blending (Long Island System Only)	65
Grade 745 - Non-VOC Controlled Region 2 — Premium RBOB for 5.7% Ethanol Blending (Long Island System Only)	67

TABLE 1

Approved GUM INHIBITORS AND METAL DEACTIVATORS

For Gasoline

This product may, but is not required to, contain the following:

N, N'di-secondary butyl para-phenylenediamine
N, N'disalicylidene-1, 2 propanediamine
2, 6-di-tertiary butyl 4 methyl phenol
N, N'di (1-ethyl-2-methylpentyl) para-phenylenediamine
N, N'di-isopropyl-para-phenylenediamine
N, N'bis- (1, 4-diemethylpentyl) -p-phenylenediamine
N-Butyl para-aminophenol
2,4,6 - tritertiary butylphenol
Ortho-tertiary butylphenol
2,4-diamethyl-6-tertiary-butylphenol
2,4-di-tertiary butylphenol
2,6-di-tertiary butylphenol
N, secondary butyl, N' phenyl-para-phenylenediamine
Butylated ethyl, methyl and dimethyl phenols
Mixed propylated and butylated phenols
2,4,6 tri-isopropylphenol

Approved CORROSION INHIBITORS

For Gasoline

This product may, but is not required to, contain the following:

Aqua Process 11CH77	Mobil—C-605	Spec-Aid 8Q22
Corexit — 5267	OndeoNalco—5403	TOLAD 4410
Innospec—DCI-4A	OndeoNalco 5405	TOLAD 245
Innospec—DCI-6A	OndeoNalco 5406	TOLAD 249
Innospec—DCI-11	Spec-Aid 8Q100	TOLAD 351
Innospec—DCI-30.n	Spec-Aid 8Q101	Unichem 7500
Ethyl Hi Tec 580	Spec-Aid 8Q102	Unichem 7501
Lubrizol – 8014	Spec-Aid 8Q103	Unichem 7510
Lubrizol – 8017	Spec-Aid 8Q106	UOP—Unicor
MidContinental	Spec-Aid 8Q109	UOP—Unicor J
Chemical MCC5001	Spec-Aid 8Q110	UOP—Unicor PL
Tolad 9715	Tolad 3232	
Tolad 9719		

For Diesel Fuels and Fuel Oil

In addition to the above additives, the following may be used:

Dupont	AFA-1
Innospec	DC1-30.n
Nalco	EC 5407-A
Tolad	3032
Infineum	R511

NOTE: All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).

TABLE 2 SEASONAL GASOLINE REQUIREMENTS

REID VAPOR PRESSURE

The following schedule denotes the volatility properties as required by Buckeye and may not coincide with dates specified by appropriate government agencies. Some systems within Buckeye may require earlier dates for summer RVP limits in order to ensure compliance with EPA federal regulations. Shippers will be advised in advance of the date that fungible gasolines must be input into the Buckeye System. Buckeye will use a Grabner vapor pressure instrument to monitor RVP compliance, per ASTM D5191, but will use the coefficients recommended by EPA, i.e. 956X - 0.347.

DISTILLATION CLASSES: ASTM D-86

CLASS	A	C	D	E
10% Evap., Deg F (Deg C) Max.	158 (70)	140 (60)	131 (55)	122 (50)
50% Evap., Deg F (Deg C) Min. ⁽¹⁾	170 (77)	170 (77)	170 (77)	170 (77)
50% Evap., Deg F (Deg C) Max.	250 (121)	240 (116)	235 (113)	230 (110)
90% Evap., Deg F (Deg C) Max.	374 (190)	365 (185)	365 (185)	365 (185)
End Point, Deg F (Deg C) Max.	437 (225)	437 (225)	437 (225)	437 (225)
Driveability Index Deg F (Deg C) Max. ⁽²⁾	1250 (597)	1230 (586)	1220 (580)	1200 (569)

CLASS	1	2	3	4	5
Min deg F (deg C) for Vapor/Liquid Ratio (V/L) = 20 [ASTM D-2533, D-5188]	140 (60)	133 (56)	124 (51)	116 (47)	105 (41)
Residue Vol %	2.0	2.0	2.0	2.0	2.0

Origin Maximum RVP and Distillation Requirements

		Jan	Feb	Mar 1-14	Mar 15-31	Apr 1-9	Apr 10-30	May	Jun	Jul	Aug	Sep 1-15	Sep 16-30	Oct	Nov	Dec
LIS and JET (NYC, MA and CT)	psi	15.0	15.0	15.0	15.0	13.5	7.8	7.8	7.8	7.8	7.8	7.8	13.5	13.5	15.0	15.0
	(kPa) dist	(103) E-5	(103) E-5	(103) E-5	(103) E-5	(93) A-4	(54) A-4	(54) A-4	(54) A-3	(54) A-3	(54) A-3	(54) A-3	(93) D-4	(93) D-4	(103) E-5	(103) E-5
EPS/LPL (PA and upstate NY)	psi	15.0	15.0	15.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	13.5	13.5	15.0	15.0
	(kPa) dist	(103) E-5	(103) E-5	(103) E-5	(62) A-4	(62) A-4	(62) A-4	(62) A-4	(62) A-3	(62) A-3	(62) A-3	(62) A-3	(93) D-4	(93) D-4	(103) E-5	(103) E-5
LPL (Pittsburgh)	psi	15.0	15.0	15.0	15.0	7.8	7.8	7.8	7.8	7.8	7.8	7.8	13.5	13.5	15.0	15.0
	(kPa) dist	(103) E-5	(103) E-5	(103) E-5	(103) E-5	(54) A-4	(54) A-4	(54) A-4	(54) A-3	(54) A-3	(54) A-3	(54) A-3	(93) D-4	(93) D-4	(103) E-5	(103) E-5
Midwest (Southeast Michigan)	psi	15.0	15.0	15.0	15.0	6.8	6.8	6.8	6.8	6.8	6.8	6.8	13.5	13.5	15.0	15.0
	(kPa) dist	(103) E-5	(103) E-5	(103) E-5	(103) E-5	(47) A-4	(47) A-4	(47) A-4	(47) A-3	(47) A-3	(47) A-3	(47) A-3	(93) D-4	(93) D-4	(103) E-5	(103) E-5
* Midwest (Michigan)	psi	15.0	15.0	15.0	15.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	13.5	13.5	15.0	15.0
	(kPa) dist	(103) E-5	(103) E-5	(103) E-5	(103) E-5	(62) A-4	(62) A-4	(62) A-4	(62) A-3	(62) A-3	(62) A-3	(62) A-3	(93) D-4	(93) D-4	(103) E-5	(103) E-5
Wood River (St. Louis)	psi	15.0	15.0	13.5	13.5	13.5	8.0	8.0	8.0	8.0	8.0	8.0	11.5	13.5	15.0	15.0
	(kPa) dist	(103) E-5	(103) E-5	(93) D-4	(93) D-4	(93) D-4	(62) A-3	(62) A-3	(62) A-3	(62) A-2	(62) A-2	(62) A-2	(79) C-3	(93) D-4	(103) E-5	(103) E-5
Midwest and Wood River (All other)	psi	15.0	15.0	15.0	15.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	11.5	13.5	15.0	15.0
	(kPa) dist	(103) E-5	(103) E-5	(103) E-5	(103) E-5	(62) A-4	(62) A-4	(62) A-4	(62) A-3	(62) A-3	(62) A-3	(62) A-3	(79) C-3	(93) D-4	(103) E-5	(103) E-5

(1) The minimum T50 and maximum V/L for all RBOB's must comply with the applicable requirements of the state in which the fuel is destined for retail.

(2) The DI (Driveability Index) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2 and are not subject to correction for precision of the test method.

(3) For products blended to meet EPA or state imposed volatility requirements, RVP test must be performed in accordance with methods published in 40 CFR Part 80.

BUCKEYE PARTNERS, L.P.
(MIDWEST PRODUCTS SYSTEM ONLY)
SPECIFICATIONS FOR FUNGIBLE NORMAL BUTANE
GRADE 086

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Vapor Pressure, psig @ 100° F	D1267		50	
Relative Density @ 60/60° F	D1657	0.560	0.600	
Volatile Residue				
Temperature @ 95% evaporated, °F	D1837		36	
Corrosion, copper	D1838		1	
Sulfur, ppmw	D2784		140	
Fluorides, ppmw	UOP619		1.4	
Analysis, liq. Vol. % - ASTM-2163				
Propane			2.5	
Isobutane			6.0	
Normal butane		94.0		
Pentanes and Heavier			2.0	
Butadiene			0.01	
Total Olefins			0.35	
Free Water		None		

BUCKEYE PARTNERS, L.P.
(MIDWEST PRODUCTS SYSTEM ONLY)
SPECIFICATIONS FOR FUNGIBLE PROPANE
GRADE 088

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Vapor Pressure, psig @ 100° F	D1267		208	
Relative Density @ 60/60° F	D1657	0.500	0.515	
Volatile Residue				
Temperature @ 95% evaporated, °F	D1837		-37	
Butanes and heavier	D2163		2.5	
OR				
Residual Matter				
Residue on evaporation of 100 ml., ml	D2158		0.05	
Oil Stain			Pass	1
Corrosion, copper	D1838		1	
Sulfur, ppmw	D2784		123	
Fluorides, ppmw	UOP619		1	
Analysis, liq. Vol. %				
Propylene			5.0	
Propane		90.0		
Free Water		None		

NOTES:

1. An acceptable product shall not yield a persistent oil ring when 0.3 ml of solvent residue is added in 0.1 ml increments; after examination in daylight after 2 minutes as described in D2158.

BUCKEYE PARTNERS, L.P.
SPECIFICATIONS FOR FUNGIBLE LOW SULFUR DIESEL/FUEL OIL (OFF ROAD)
GRADE 130 (EPA DESIGNATION: DNRLM500)

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Gravity, API @ 60°F	D287, D4052	30		
Flash Point, °F (at Origin)	D93 or D56	130		1
Color, ASTM	D1500		2.5	
Viscosity, cst @ 104°F	D445	1.9	3.4	
Cloud Point, °F	D2500, D5771, D5772, D5773, D3117			2
Pour Point, °F	D5985, D5949, D5950, D97			3
Total Sulfur, wt. %	D1266, D2622, D4294 D5453		0.042	
Corrosion, 3 hrs. @ 122°F	D130		1	
Oxidation Stability, mg/100 ml or	D2274		2.5	
Thermal Stability, 90 minutes				
150°C Pad rating	DuPont		7	
Carbon Residue, wt. % on 10% bottom	D524 or D4530		0.35	
Ash, wt. %	D482		0.01	
Sediment and Water, % by volume	D2709		0.05	
Cetane Number	D613, D6890	40		
or				
Cetane Index	D4737	40		
Aromatics (Vol%)	D1319		31.7	
Or Aromatics by Cetane Index	D976	40		
Physical Distillation, °F	D86			
50% recovered		Report		
90% recovered		540	640	
End Point			690	
OR Simulated Distillation, °F	D2887			
50% recovered		Report		
90% recovered		572	673	
End Point			790	
Haze Rating @ 77°F	D4176		2	
Procedure 2				
Color Visual		Undyed		4
Additives				5
NACE	TM0172-2001	B+		7

NOTES:

- Test method D-56 may be used as an alternate to D-93 with the same limits. Test method D-93 is the referee method. Minimum flash at delivery is 125 °F.
- Cloud Point - September thru March
Cloud Point - April thru August
- Pour Point - September thru March
Pour Point - April thru August
- Product must exhibit no visible evidence of dye.
- Use of static dissipater additive or conductivity improver is prohibited.
- The use of lubricity improver additives is prohibited.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).
- This product is for Off-Road use only and should be designated as such in the EPA's Designate and Track reporting system (DNRLM500).
- Biofuel Components (e.g. biodiesel) are not permitted in this product.

BUCKEYE PARTNERS, L.P.
SPECIFICATIONS FOR FUNGIBLE LOW SULFUR DIESEL/FUEL OIL (OFF ROAD)
GRADE 132 (EPA DESIGNATION: DNRLM500)
(BUCKEYE-MIDWEST PIPELINE SYSTEM AND WOOD RIVER SYSTEM)

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Gravity, API @ 60°F	D287, D4052	30		
Flash Point, °F (at Origin)	D93 or D56	130		1
Color, ASTM	D1500		2.5	
Viscosity, cst @ 104°F	D445	1.9	3.4	
Cloud Point, °F	D2500, D5771, D5772, D5773, D3117			2
Pour Point, °F	D5985, D5949, D5950, D97			3
Total Sulfur, wt. %	D1266, D2622 or D4294 D5453		0.042	
Corrosion, 3 hrs. @ 122°F	D130		1	
Oxidation Stability, mg/100 ml or Thermal Stability, 90 minutes 150°C Pad rating	D2274		2.5	
Carbon Residue, wt. % on 10% bottom	DuPont D524 or D4530		7	
Ash, wt. %	D482		0.35	
Sediment and Water, % by volume	D2709		0.01	
Cetane Number	D613, D6890	40		
or Cetane Index	D4737	40		
Aromatics (Vol%)	D1319		31.7	
Or Aromatics by Cetane Index	D976	40		
Physical Distillation, °F	D86			
50% recovered		Report		
90% recovered		540	640	
End Point			690	
OR Simulated Distillation, °F	D2887			
50% recovered		Report		
90% recovered		572	673	
End Point			790	
Haze Rating @ 77°F Procedure 2	D4176		2	
Color Visual		Undyed		4
Additives				5
NACE	TM0172-2001	B+		7

NOTES:

- Test method D-56 may be used as an alternate to D-93 with the same limits. Test method D-93 is the referee method. Minimum flash at delivery is 125°F.
- Cloud Point - September thru March
Cloud Point - April thru August
Maximum +10°F / -12°C
- Pour Point - September thru March
Pour Point - April thru August
Maximum +20°F / -7°C
Maximum -10°F / -23°C
Maximum +10°F / -12°C
- Product must exhibit no visible evidence of dye.
- Use of static dissipater additive or conductivity improver is prohibited.
- The use of lubricity improver additives is prohibited.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).
- This product is for Off-Road use only and should be designated as such in the EPA's Designate and Track reporting system (DNRLM500).
- Biofuel Components (e.g. biodiesel) are not permitted in this product.

BUCKEYE PARTNERS, L.P.
SPECIFICATIONS FOR ULTRA LOW SULFUR KEROSENE (OFF ROAD)
GRADE 150 (EPA DESIGNATION: DNRLM015)

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Appearance	White Bucket	Report		1,4
Gravity, API @ 60°F	D287, D1298 or D4052	37	51	
Net Heat of Combustion, BTU/lb.	D3338, D4809, D4529	18,400		
Corrosion, 2 hrs. @ 212°F	D130		1	
Total Sulfur, ppm (at Origin)	D5453			
Receipt from Refinery			8.0	
Receipt from Connecting Pipeline			10.0	
Doctor Test	D4952		Negative	
OR				
Mercaptan Sulfur, wt. %	D3227		0.003	3
Aromatics, vol. %	D1319		25	
Existent Gum, mg/100 ml.	D381		7	
Flash Point, °F	D56, D3828	123		
Distillation, °F	D86			
10% recovered		348	400	
50% recovered		Report		
90% recovered		Report	550	
95% recovered		465		
End Point			572	
or Simulated Distillation, °C(°F)	D2887			
10% recovered			185(365)	
50% recovered		Report		
90% recovered			304(579)	
End Point			340(644)	
Residue, %			1.5	
Loss, %			1.5	
Freezing Point, °F	D2386, D4305, D5901, D5972		-40	
Viscosity, cst. @ -4°F	D445		8.0	
Viscosity, cst. @ 100°F	D445	1.4	2.2	
Smoke Point or	D1322	25		
Smoke Point and	D1322	18		
Naphthalenes, vol. %	D1840		3.0	
Ash, wt %	D482		0.01	
Carbon residue, wt % on 10% bottom	D524		0.15	
Burning Quality	D187	Report		
Electrical Conductivity	D2624	Report		2
Additives		Report		2
NACE	TM0172-2001	B+		5

NOTES:

- Product shall be clear and bright and free of suspended matter, and must not exhibit various shades of green, blue or red.
- Only those additives accepted in Table 1 of this section will be permitted by Buckeye. Use of all additives must be approved by Buckeye prior to shipment and must be reported on the Certificate of Analysis and Preshipment Fax of Key Properties.
- Mercaptan Sulfur waived if fuel is negative by Doctor test.
- No peacock or abnormal color deposits.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).
- This product is for Off-Road use only and should be designated as such in the EPA's Designate and Track reporting system (DNRLM015).
- Biofuel Components (e.g. biodiesel) are not permitted in this product.

BUCKEYE PARTNERS, L.P.
SPECIFICATIONS FOR ULTRA LOW SULFUR DIESEL #1 (ON ROAD)
GRADE 151 (EPA DESIGNATION: DMV1D015)

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Appearance	White Bucket	Report		1,4
Gravity, API @ 60°F	D287, D1298 or D4052	37	51	
Net Heat of Combustion, BTU/lb.	D3338, D4809, D4529	18,400		
Corrosion, 2 hrs. @ 212°F	D130		1	
Cetane Index	D976, D4737	40		
Total Sulfur, ppm (at Origin)	D5453			
Receipt from Refinery			8.0	
Receipt from Connecting Pipeline			10.0	5,6
Doctor Test	D4952		Negative	
OR				
Mercaptan Sulfur, wt. %	D3227		0.003	3
Aromatics, vol. %	D1319		25	
Existent Gum, mg/100 ml.	D381		7	
Flash Point, °F	D56, D3828	123		
Distillation, °F	D86			
10% recovered		348	400	
50% recovered		Report		
90% recovered		Report	550	
95% recovered		465		
End Point			572	
or Simulated Distillation, °C(°F)	D2887			
50% recovered			Report	
90% recovered		300(572)	356(673)	
End Point			421(790)	
Residue, %			1.5	
Loss, %			1.5	
Freezing Point, °F	D2386, D4305, D5901, D5972		-40	
Viscosity, cst. @ -4°F	D445		8.0	
Viscosity, cst. @ 100°F	D445	1.4	2.2	
Smoke Point or	D1322	25		
Smoke Point and	D1322	18		
Naphthalenes, vol. %	D1840		3.0	
Ash, wt %	D482		0.01	
Carbon residue, wt % on 10% bottom	D524		0.15	
Burning Quality	D187	Report		
Electrical Conductivity	D2624	Report		2
Additives		Report		2
NACE	TM0172-2001	B+		7

NOTES:

- Product shall be clear and bright and free of suspended matter, and must not exhibit various shades of green, blue or red.
- Only those additives accepted in Table 1 of this section will be permitted by Buckeye. Use of all additives must be approved by Buckeye prior to shipment and must be reported on the Certificate of Analysis and Preshipment Fax of Key Properties.
- Mercaptan Sulfur waived if fuel is negative by Doctor test.
- No peacock or abnormal color deposits.
- This product is for On-Road use and should be designated as such in the EPA's Designate and Track reporting system (DMV1D015).
- Sulfur level at delivery will vary depending upon the origin and delivery location
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).
- Biofuel Components (e.g. biodiesel) are not permitted in this product.

BUCKEYE PARTNERS, L.P.
SPECIFICATIONS FOR FUNGIBLE AVIATION/KEROSENE (OFF ROAD)
GRADE 152 (EPA DESIGNATION: DNRLM500)
(BUCKEYE-NORCO PIPELINE SYSTEM ONLY)

(Page 1 of 2)

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Appearance	White Bucket	Report		
Color, at origin	D156, D6045	18		1
at delivery		+16		
Gravity, API @ 60°F	D287, D1298, D4052	37	51	
Net Heat of Combustion, BTU/lb.	D3338, D4809, D4529	18,400		
Corrosion, 2 hrs. @ 212°F	D130		1	
Cetane Index	D976, D4737	40		
Water Reaction				
Interface Rating	D1094		1b	
MSEP (at Origin)	D3948	85		
Sulfur, wt. %	D2622, D4294, D1266, D1552		0.04	
Doctor Test	D4952		Negative	
OR				
Mercaptan Sulfur, wt. %	D3227		0.003	3
Aromatics, vol. %	D1319		25	
Total Acidity, mg. KOH/g	D3242		0.10	
Existent Gum, mg/100 ml.	D381		7	
Thermal Stability (JFTOT)	D3241			
Test duration 2.5 hrs.				
Heater temperature 275°C				
Flow rate 3ml/min.				
Pressure drop in mm/Hg			25	
Tube deposit less than			Code 3	4
Flash Point, °F	D56, D3828	123		
Physical Distillation, °F	D86			
10% recovered		348	400	
50% recovered		Report		
90% recovered		Report	550	
95% recovered		465		
End Point			572	
Residue, %			1.5	
Loss, %			1.5	
OR Simulated Distillation, °F	D2887			
10% recovered			365	
50% recovered		Report		
90% recovered			579	
End Point			644	
Freezing Point, °F	D2386, D4305, D5901, D5972		-40	
Viscosity, cst. @ -4°F	D445		8.0	
Viscosity, cst. @ 100°F	D445	1.4	2.2	
Smoke Point or	D1322	25		
Smoke Point and	D1322	18		
Naphthalenes, vol. %	D1840		3.0	
Ash, wt %	D482		0.01	
Carbon residue, wt % on 10% bottom	D524		0.15	
Burning Quality	D187	Report		
Electrical Conductivity	D2624	Report		2
Additives		Report		2

BUCKEYE PARTNERS, L.P.

SPECIFICATIONS FOR FUNGIBLE AVIATION/ KEROSENE (OFF ROAD) - GRADE 152

(Page 2 of 2)

NOTES:

1. Product shall be clear and bright and free of suspended matter, and must not exhibit various shades of green, blue or red.
2. Only those additives specified and within the concentration noted in Section 5.2 through 5.2.2.1 of ASTM D-1655 will be considered for acceptance. The use of any other additives is prohibited. Use of all additives must be approved by Buckeye prior to shipment and must be reported on the Certificate of Analysis and Preshipment Fax of Key Properties. In addition, scheduling and Measurement & Quality Control must be notified at least 48 hours prior to the scheduled shipment of any batches containing Metal Deactivator Additive (MDA). If MDA has been added to the product, Buckeye reserves the right to refuse shipment. If requesting to move a batch that has been treated with MDA, supply the following information to Buckeye Measurement & Quality Control: (1) the purpose for adding MDA, (2) a breakdown of total metals present in the jet fuel before treating with MDA, (3) JFTOT test results both prior to and after adding MDA, (4) MDA treat rate, and (5) MDA product used.
3. Mercaptan Sulfur waived if fuel is negative by Doctor test.
4. No peacock or abnormal color deposits.
5. Product must comply with ASTM D1655 specifications in addition to Buckeye product specifications.
6. This product is for Off-Road use only and should be designated as such in the EPA's Designate and Track reporting system (DNRLM500).
7. Biofuel Components (e.g. biodiesel) are not permitted in this product.

BUCKEYE PARTNERS, L.P.
SPECIFICATIONS FOR FUNGIBLE AVIATION/LSO #1 (ON ROAD)
GRADE 153 (EPA DESIGNATION: DMV1D500)

(Page 1 of 2)

PRODUCT PROPERTY	ASTM TEST METHODS	TEST RESULTS		NOTE
		MINIMUM	MAXIMUM	
Appearance	White Bucket	Report		
Color, at origin	D156, D6045	18		1
at delivery		+16		
Gravity, API @ 60°F	D287, D1298 or D4052	37	51	
Net Heat of Combustion, BTU/lb.	D3338, D4809, D4529	18,400		
Corrosion, 2 hrs. @ 212°F	D130		1	
Cetane Index	D976, D4737	40		
Water Reaction				
Interface Rating	D1094		1b	
MSEP (at Origin)	D3948	85		
Sulfur, wt. %	D2622, D4294, D1266, D1552		0.04	
Doctor Test	D4952		Negative	
OR				
Mercaptan Sulfur, wt. %	D3227		0.003	3
Aromatics, vol. %	D1319		25	
Total Acidity, mg. KOH/g	D3242		0.10	
Existent Gum, mg/100 ml.	D381		7	
Thermal Stability (JFTOT)	D3241			
Test duration 2.5 hrs.				
Heater temperature 275°C				
Flow rate 3ml/min.				
Pressure drop in mm/Hg			25	
Tube deposit less than			Code 3	4
Flash Point, °F	D56, D3828	123		
Distillation, °F	D86			
10% recovered		348	400	
50% recovered		Report		
90% recovered		Report	550	
95% recovered		465		
End Point			572	
Residue, %			1.5	
Loss, %			1.5	
OR Simulated Distillation, °F	D2887			
10% recovered			365	
50% recovered		Report		
90% recovered			579	
End Point			644	
Freezing Point, °F	D2386, D4305, D5901, D5972		-40	
Viscosity, cst. @ -4°F	D445		8.0	
Viscosity, cst. @ 100°F	D445	1.4	2.2	
Smoke Point or	D1322	25		
Smoke Point and	D1322	18		
Naphthalenes, vol. %	D1840		3.0	
Ash, wt %	D482		0.01	
Carbon residue, wt % on 10% bottom	D524		0.15	
Burning Quality	D187	Report		
Electrical Conductivity	D2624	Report		2
Additives		Report		2

BUCKEYE PARTNERS, L.P.

SPECIFICATIONS FOR FUNGIBLE AVIATION/LSD #1 (ON ROAD) - GRADE 153

(Page 2 of 2)

NOTES:

1. Product shall be clear and bright and free of suspended matter, and must not exhibit various shades of green, blue or red.
2. Only those additives specified and within the concentration noted in Section 5.2 through 5.2.2.1 of ASTM D-1655 will be considered for acceptance. The use of any other additives is prohibited. Use of all additives must be approved by Buckeye prior to shipment and must be reported on the Certificate of Analysis and Preshipment Fax of Key Properties. In addition, scheduling and Measurement & Quality Control must be notified at least 48 hours prior to the scheduled shipment of any batches containing Metal Deactivator Additive (MDA). If MDA has been added to the product, Buckeye reserves the right to refuse shipment. If requesting to move a batch that has been treated with MDA, supply the following information to Buckeye Measurement & Quality Control: (1) the purpose for adding MDA, (2) a breakdown of total metals present in the jet fuel before treating with MDA, (3) JFTOT test results both prior to and after adding MDA, (4) MDA treat rate, and (5) MDA product used.
3. Mercaptan Sulfur waived if fuel is negative by Doctor test.
4. No peacock or abnormal color deposits.
5. Product must comply with ASTM D1655 specifications in addition to Buckeye product specifications.
6. This product may be used for On-Road purposes and should be designated as such in the EPA's Designate and Track reporting system (DMV1D500).
7. Biofuel Components (e.g. biodiesel) are not permitted in this product.

BUCKEYE PARTNERS, L.P.
SPECIFICATIONS FOR FUNGIBLE ULSD-1/AVIATION/ULSK (ON ROAD)
GRADE 155 (EPA DESIGNATION: DMV1D015)
 (Page 1 of 2)

PRODUCT PROPERTY	ASTM TEST METHODS	TEST RESULTS		NOTE
		MINIMUM	MAXIMUM	
Appearance	White Bucket	Report		
Color, at origin	D156, D6045	18		1
at delivery		+16		
Gravity, API @ 60°F	D287, D1298 or D4052	37	51	
Net Heat of Combustion, BTU/lb.	D3338, D4809, D4529	18,400		
Corrosion, 2 hrs. @ 212°F	D130		1	
Cetane Index	D976, D4737	40		
Water Reaction				
Interface Rating	D1094		1b	
MSEP (at Origin)	D3948	85		
Sulfur, ppm (at Origin)	D5453, D2622			
Receipt from Refinery	D4294, D1266		8.0	
Receipt from Connecting Pipeline	D1552		10.0	5
Doctor Test OR	D4952		Negative	
Mercaptan Sulfur, wt. %	D3227		0.003	3
Aromatics, vol. %	D1319		25	
Total Acidity, mg. KOH/g	D3242		0.10	
Existent Gum, mg/100 ml.	D381		7	
Thermal Stability (JFTOT)	D3241			
Test duration 2.5 hrs.				
Heater temperature 275°C				
Flow rate 3ml/min.				
Pressure drop in mm/Hg			25	
Tube deposit less than			Code 3	4
Flash Point, °F	D56, D3828	123		
Distillation, °F	D86			
10% recovered		348	400	
50% recovered		Report		
90% recovered		Report	550	
95% recovered		465		
End Point			572	
Residue, %			1.5	
Loss, %			1.5	
OR Simulated Distillation, °F	D2887			
10% recovered			365	
50% recovered		Report		
90% recovered			579	
End Point			644	
Freezing Point, °F	D2386, D4305, D5901, D5972		-40	
Viscosity, cst. @ -4°F	D445		8.0	
Viscosity, cst. @ 100°F	D445	1.4	2.2	
Smoke Point or	D1322	25		
Smoke Point and	D1322	18		
Naphthalenes, vol. %	D1840		3.0	
Ash, wt %	D482		0.01	
Carbon residue, wt % on 10% bottom	D524		0.15	
Burning Quality	D187	Report		
Electrical Conductivity	D2624	Report		2
Additives		Report		2

BUCKEYE PARTNERS, L.P.

SPECIFICATIONS FOR FUNGIBLE ULSD-1/AVIATION/ULSK (ON ROAD) - GRADE 155

(Page 2 of 2)

NOTES:

1. Product shall be clear and bright and free of suspended matter, and must not exhibit various shades of green, blue or red.
2. Only those additives specified and within the concentration noted in Section 5.2 through 5.2.2.1 of ASTM D-1655 will be considered for acceptance. The use of any other additives is prohibited. Use of all additives must be approved by Buckeye prior to shipment and must be reported on the Certificate of Analysis and Preshipment Fax of Key Properties. In addition, scheduling and Measurement & Quality Control must be notified at least 48 hours prior to the scheduled shipment of any batches containing Metal Deactivator Additive (MDA). If MDA has been added to the product, Buckeye reserves the right to refuse shipment. If requesting to move a batch that has been treated with MDA, supply the following information to Buckeye Measurement & Quality Control: (1) the purpose for adding MDA, (2) a breakdown of total metals present in the jet fuel before treating with MDA, (3) JFTOT test results both prior to and after adding MDA, (4) MDA treat rate, and (5) MDA product used.
3. Mercaptan Sulfur waived if fuel is negative by Doctor test.
4. No peacock or abnormal color deposits.
5. Sulfur level at delivery will vary depending upon the origin and delivery location.
6. Product must comply with ASTM D1655 specifications in addition to Buckeye product specifications.
7. This product may be used for On-Road purposes and should be designated as such in the EPA's Designate and Track reporting system (DMV1D015).
8. Biofuel Components (e.g. biodiesel) are not permitted in this product.

BUCKEYE PARTNERS, L.P.
SPECIFICATIONS FOR FUNGIBLE FUEL OIL - GRADE 160
(Linden, NJ Area and Boothwyn, Pa. Area Origins Only)

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Gravity, API @ 60°F	D287, D4052	30		
Flash Point, °F(at Origin)	D93, D56	130		1
Viscosity, cst @ 104°F	D445	1.9	3.4	
Cloud Point, °F	D2500, D5771, D5772, D5773, DD3117			2
Pour Point, °F	D5985, D5949, D5950, D97			3
Total Sulfur, wt. %	D129 or D2622 or D4294 D5453		0.20	
Corrosion, 3 hrs. @ 122°F	D130		1	
Oxidation Stability, mg/100 ml or Thermal Stability, 90 minutes 150°C Pad rating	D2274 DuPont		2.5 7	
Carbon Residue, wt. % on 10% bottom	D524 or D4530		0.35	
Ash, wt. %	D482		0.01	
Sediment and Water, % by volume	D2709		0.05	
Cetane Number	D613 or D6890	Report		6
Physical Distillation, °F	D86			
50% recovered		Report		
90% recovered		540	640	
End Point			690	
OR Simulated Distillation, °F	D2887			
50% recovered		Report		
90% recovered		572	673	
End Point			790	
Haze Rating @ 77°F Procedure 2	D4176		2	
Color Visual		Dyed		4
Dye Content, ppm (at Origin)	D6258 or Petrospec DT100	13.0	16.0	
NACE	TM0172-2001	B+		7

NOTES:

- Test method D-56 may be used as an alternate to D-93 with the same limits. Test method D-93 is the referee method. Minimum flash at delivery is 125 °F.
- Cloud Point - September thru March
Cloud Point - April thru August
Maximum +15 °F / -9 °C
Maximum +20 °F / -7 °C
- Pour Point, - September thru March
Pour Point, - April thru August
Maximum 0 °F / -18 °C
Maximum +10 °F / -12 °C
- This product must contain red dye, standard solvent Red 26 or solvent Red 164, in concentrations of 4.6 lbs. or 6.6 lbs., respectively, of active dry ingredient per 1,000 barrels. Product must meet a maximum color of 2.5 per ASTM D1500 prior to introduction of dye.
- The use of lubricity improver additives is prohibited.
- Where Cetane Number is not available, Cetane Index (D4737B) may be used as an approximation.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).
- Biofuel Components (e.g. biodiesel) are not permitted in this product.

BUCKEYE PARTNERS, L.P.
SPECIFICATIONS FOR FUNGIBLE FUEL OIL - GRADE 161

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Gravity, API @ 60°F	D287, D4052	30		
Flash Point, °F(at Origin)	D93 or D56	130		1
Viscosity, cst @ 104°F	D445	1.9	3.4	
Cloud Point, °F	D2500, D5771, D5772, D5773, D3117			2
Pour Point, °F	D5985, D5949, D5950, D97			3
Total Sulfur, wt. %	D129 or D2622 or D4294 D5453		0.50	
Corrosion, 3 hrs. @ 122°F	D130		1	
Oxidation Stability, mg/100 ml or	D2274		2.5	
Thermal Stability, 90 minutes				
150°C Pad rating	DuPont		7	
Carbon Residue, wt. % on 10% bottom	D524 or D4530		0.35	
Ash, wt. %	D482		0.01	
Sediment and Water, % by volume	D2709		0.05	
Physical Distillation, °F	D86			
50% recovered		Report		
90% recovered		540	640	
End Point			690	
OR Simulated Distillation, °F	D2887			
50% recovered		Report		
90% recovered		572	673	
End Point			790	
Haze Rating @ 77°F	D4176		2	
Procedure 2				
Color Visual		Dyed		4
Dye Content, ppm (at Origin)	D6258 or	13.0	16.0	
Petrospec DT100				
Cetane Number	D613 or D6890	Report		6
NACE	TM0172-2001	B+		7

NOTES:

- Test method D-56 may be used as an alternate to D-93 with the same limits. Test method D-93 is the referee method. Minimum flash at delivery is 125 °F.
- Cloud Point - September thru March
 Cloud Point - April thru August
 Maximum +15 °F / -9 °C
 Maximum +20 °F / -7 °C
- Pour Point - September thru March
 Pour Point - April thru August
 Maximum 0 °F / -18 °C
 Maximum +10 °F / -12 °C
- This product must contain red dye, standard solvent Red 26 or solvent Red 164, in concentrations of 4.6 lbs or 6.6 lbs., respectively, of active dry ingredient per 1,000 barrels. Product must meet a maximum color of 2.5 per ASTM D1500 prior to introduction of dye.
- The use of lubricity improver additives is prohibited.
- Where Cetane Number is not available, Cetane Index (D4737B) may be used as an approximation.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).
- Biofuel Components (e.g. biodiesel) are not permitted in this product.

BUCKEYE PARTNERS, L.P.
SPECIFICATIONS FOR FUNGIBLE FUEL OIL - GRADE 162

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Gravity, API @ 60°F	D287, D4052	30		
Flash Point, °F(at Origin)	D93 or D56	130		1
Viscosity, cst @ 104°F	D445	1.9	3.4	
Cloud Point, °F	D2500, D5771, D5772, D5773, D3117			2
Pour Point, °F	D5985, D5949, D5950, D97			3
Total Sulfur, wt. %	D129 or D2622 or D4294 D5453		0.50	
Corrosion, 3 hrs. @ 122°F	D130		1	
Oxidation Stability, mg/100 ml or	D2274		2.5	
Thermal Stability, 90 minutes				
150°C Pad rating	DuPont		7	
Carbon Residue, wt. % on 10% bottom	D524 or D4530		0.35	
Ash, wt. %	D482		0.01	
Sediment and Water, % by volume	D2709		0.05	
Physical Distillation, °F	D86			
50% recovered		Report		
90% recovered		540	640	
End Point			690	
OR Simulated Distillation, °F	D2887			
50% recovered		Report		
90% recovered		572	673	
End Point			790	
Haze Rating @ 77°F	D4176		2	
Procedure 2				
Color Visual		Dyed		4
Dye Content, ppm (at Origin)	D6258 or	13.0	16.0	
Petrospec DT100				
Cetane Number	D613 or D6890	Report		6
NACE	TM0172-2001	B+		7

NOTES:

- Test method D-56 may be used as an alternate to D-93 with the same limits. Test method D-93 is the referee method. Minimum flash at delivery is 125 °F.
- Cloud Point - September thru March
 Cloud Point - April thru August
 Maximum +10 °F/ -12 °C
 Maximum +20 °F / -7 °C
- Pour Point - September thru March
 Pour Point - April thru August
 Maximum -10 °F /-23 °C
 Maximum +10°F/ -12 °C
- This product must contain red dye, standard solvent Red 26 or Red 164, in concentrations of 4.6 lbs. Or 6.6 lbs., respectively, of active dry ingredient per 1,000 barrels. Product must meet a maximum color of 2.5 per ASTM D1500 prior to introduction of dye.
- The use of lubricity improver additives is prohibited. .
- Where Cetane Number is not available, Cetane Index (D4737B) may be used as an approximation.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).
- Biofuel Components (e.g. biodiesel) are not permitted in this product.

BUCKEYE PARTNERS, L.P.
SPECIFICATIONS FOR FUNGIBLE HIGH SULFUR NRLM
GRADE 163 (EPA DESIGNATION: DNRLMHS)

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Gravity, API @ 60°F	D287, D4052	30		
Flash Point, °F(at Origin)	D93 or D56	130		1
Viscosity, cst @ 104°F	D445	1.9	3.4	
Cloud Point, °F	D2500, D5771, D5772, D5773, D3117			2
Pour Point, °F	D5985, D5949, D5950, D97			3
Total Sulfur, wt. %	D129 or D2622 or D4294 D5453		0.50	
Corrosion, 3 hrs. @ 122°F	D130		1	
Oxidation Stability, mg/100 ml or	D2274		2.5	
Thermal Stability, 90 minutes				
150°C Pad rating	DuPont		7	
Carbon Residue, wt. % on 10% bottom	D524 or D4530		0.35	
Ash, wt. %	D482		0.01	
Sediment and Water, % by volume	D2709		0.05	
Physical Distillation, °F	D86			
50% recovered		Report		
90% recovered		540	640	
End Point			690	
OR Simulated Distillation, °F	D2887			
50% recovered		Report		
90% recovered		572	673	
End Point			790	
Haze Rating @ 77°F	D4176		2	
Procedure 2				
Color Visual		Dyed		4
Dye Content, ppm (at Origin)	D6258 or	13.0	16.0	
Petrospec DT100				
Cetane Number	D613 or D6890	40		6
NACE	TM0172-2001	B+		7

NOTES:

- Test method D-56 may be used as an alternate to D-93 with the same limits. Test method D-93 is the referee method. Minimum flash at delivery is 125 °F.
- Cloud Point - September thru March
 Cloud Point - April thru August
 Maximum +15 °F / -9 °C
 Maximum +20 °F / -7 °C
- Pour Point - September thru March
 Pour Point - April thru August
 Maximum 0 °F / -18 °C
 Maximum +10 °F / -12 °C
- This product must contain red dye, standard solvent Red 26 or solvent Red 164, in concentrations of 4.6 lbs or 6.6 lbs., respectively, of active dry ingredient per 1,000 barrels. Product must meet a maximum color of 2.5 per ASTM D1500 prior to introduction of dye.
- The use of lubricity improver additives is prohibited.
- Where Cetane Number is not available, Cetane Index (D4737B) may be used as an approximation.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).
- Biofuel Components (e.g. biodiesel) are not permitted in this product.

BUCKEYE PARTNERS, L.P.
SPECIFICATIONS FOR FUNGIBLE LOW SULFUR DIESEL/FUEL OIL (ON ROAD)
GRADE 170 (EPA DESIGNATION: DMV2D500)

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Gravity, API @ 60°F	D287, D4052	30		
Flash Point, °F(at Origin)	D93 or D56	130		1
Color, ASTM	D1500		2.5	
Viscosity, cst @ 104°F	D445	1.9	3.4	
Cloud Point, °F	D2500, D5771, D5772, D5773, D3117			2
Pour Point, °F	D5985, D5949, D5950, D97			3
Total Sulfur, wt. %	D1266, D2622 or D4294 D5453		0.042	
Corrosion, 3 hrs. @ 122°F	D130		1	
Oxidation Stability, mg/100 ml or	D2274		2.5	
Thermal Stability, 90 minutes				
150°C Pad rating	DuPont		7	
Carbon Residue, wt. % on 10% bottom	D524 or D4530		0.35	
Ash, wt. %	D482		0.01	
Sediment and Water, % by volume	D2709		0.05	
Cetane Number	D613, D6890	40		
or				
Cetane Index	D4737	40		
Aromatics (Vol%)	D1319		31.7	
Or Aromatics by Cetane Index	D976	40		
Physical Distillation, °F	D86			
50% recovered		Report		
90% recovered		540	640	
End Point			690	
OR Simulated Distillation, °F	D2887			
50% recovered		Report		
90% recovered		572	673	
End Point			790	
Haze Rating @ 77°F	D4176		2	
Procedure 2				
Color Visual		Undyed		4
Additives				5
NACE	TM0172-2001	B+		7

NOTES:

- Test method D-56 may be used as an alternate to D-93 with the same limits. Test method D-93 is the referee method. Minimum flash at delivery is 125 °F.
- Cloud Point - September thru March
Cloud Point - April thru August
Maximum +15 °F / -9 °C
Maximum +20 °F / -7 °C
- Pour Point - September thru March
Pour Point - April thru August
Maximum 0 °F / -18 °C
Maximum +10 °F / -12 °C
- Product must exhibit no visible evidence of dye.
- Use of static dissipater additive or conductivity improver is prohibited.
- The use of lubricity improver additives is prohibited.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).
- This product is for On-Road use and should be designated as such in the EPA's Designate and Track reporting system (DMV2D500).
- Biofuel Components (e.g. biodiesel) are not permitted in this product.

BUCKEYE PARTNERS, L.P.
SPECIFICATIONS FOR FUNGIBLE LOW SULFUR DIESEL/FUEL OIL (ON ROAD)
GRADE 172 (EPA DESIGNATION: DMV2D500)
(BUCKEYE-MIDWEST PIPELINE SYSTEM AND WOOD RIVER SYSTEM)

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Gravity, API @ 60°F	D287, D4052	30		
Flash Point, °F(at Origin)	D93 or D56	130		1
Color, ASTM	D1500		2.5	
Viscosity, cst @ 104°F	D445	1.9	3.4	
Cloud Point, °F	D2500, D5771, D5772, D5773, D3117			2
Pour Point, °F	D5985, D5949, D5950, D97			3
Total Sulfur, wt. %	D1266, D2622 or D4294 D5453		0.0420	
Corrosion, 3 hrs. @ 122°F	D130		1	
Oxidation Stability, mg/100 ml or	D2274		2.5	
Thermal Stability, 90 minutes				
150°C Pad rating	DuPont		7	
Carbon Residue, wt. % on 10% bottom	D524 or D4530		0.35	
Ash, wt. %	D482		0.01	
Sediment and Water, % by volume	D2709		0.05	
Cetane Number	D613, D6890	40		
or				
Cetane Index	D4737	40		
Aromatics (Vol%)	D1319		31.7	
Or Aromatics by Cetane Index	D976	40		
Physical Distillation, °F	D86			
50% recovered		Report		
90% recovered		540	640	
End Point			690	
OR Simulated Distillation, °F	D2887			
50% recovered		Report		
90% recovered		572	673	
End Point			790	
Haze Rating @ 77°F	D4176		2	
Procedure 2				
Color Visual		Undyed		4
Additives				5
NACE	TM0172-2001	B+		7

NOTES:

- Test method D-56 may be used as an alternate to D-93 with the same limits. Test method D-93 is the referee method. Minimum flash at delivery is 125 °F.
- Cloud Point - September thru March
Cloud Point - April thru August
- Pour Point - September thru March
Pour Point - April thru August
- Product must exhibit no visible evidence of dye.
- Use of static dissipater additive or conductivity improver is prohibited.
- The use of lubricity improver additives is prohibited.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).
- This product is for On-Road use and should be designated as such in the EPA's Designate and Track reporting system (DMV2D500).
- Biofuel Components (e.g. biodiesel) are not permitted in this product.

BUCKEYE PARTNERS, L.P.
NORCO PIPE LINE COMPANY, LLC
WOOD RIVER PIPE LINES, LLC
SPECIFICATIONS FOR FUNGIBLE AVIATION KEROSENE - GRADE 182

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Appearance	White Bucket	Undyed		1
Color	D156, D6045	15		1
Gravity, API @ 60°F	D287, D1298, D4052	37	51	
Net Heat of Combustion, BTU/lb.	D3338, D4529, D4809	18,400		
Corrosion, 2 hrs. @ 212°F	D130		1	
Water Reaction	D1094			
Interface Rating			1b	
MSEP (at Origin)	D3948	85		
Sulfur, wt. %	D2622, D4294, D1266, D1552		0.30	
Doctor Test	D4952		Negative	
OR				
Mercaptan Sulfur, wt. %	D3227		0.003	3
Aromatics, vol. %	D1319		25	
Total Acidity, mg. KOH/g	D3242		0.10	
Existent Gum, mg/100 ml.	D381		7	
Thermal Stability (JFTOT)	D3241			
Test duration 2.5 hrs.				
Heater temperature 275°C				
Flow rate 3ml/min.				
Pressure drop in mm/Hg			25	
Tube deposit less than			Code 3	4
Flash Point, °F	D56, D3828	108		
Distillation, °F	D86			
10% recovered			400	
20% recovered		Report		
50% recovered		Report		
90% recovered		Report		
End Point			572	
Residue, %			1.5	
Loss, %			1.5	
OR Simulated Distillation, °F	D2887			
10% recovered			365	
50% recovered		Report		
90% recovered			579	
End Point			644	
Freezing Point, °F	D2386, D4305, D5901, D5972		-40	
Viscosity, cst. @ -4°F	D445		8.0	
Smoke Point or	D1322	25		
Smoke Point and	D1322	18		
Naphthalenes, vol. %	D1840		3.0	
Electrical Conductivity	D2624	Report		2
Additives		Report		2

NOTES:

- Product shall be clear and bright and free of suspended matter, and must not exhibit various shades of green, blue or red.
- Only those additives specified and within the concentration noted in Section 5.2 through 5.2.2.1 of ASTM D-1655 will be considered for acceptance. The use of any other additives is prohibited. Use of all additives must be approved by Buckeye prior to shipment and must be reported on the Certificate of Analysis and Preshipment Fax of Key Properties. In addition, scheduling and Measurement & Quality Control must be notified at least 48 hours prior to the scheduled shipment of any batches containing Metal Deactivator Additive (MDA). If MDA has been added to the product, Buckeye reserves the right to refuse shipment. If requesting to move a batch that has been treated with MDA, supply the following information to Buckeye Measurement & Quality Control: (1) the purpose for adding MDA, (2) a breakdown of total metals present in the jet fuel before treating with MDA, (3) JFTOT test results both prior to and after adding MDA, (4) MDA treat rate, and (5) MDA product used.
- Mercaptan Sulfur waived if fuel is negative by Doctor test.
- No peacock or abnormal color deposits.
- Product must comply with ASTM D1655 specifications in addition to Buckeye product specifications.

BUCKEYE PARTNERS, L.P.
SPECIFICATIONS FOR FUNGIBLE ULTRA LOW SULFUR DIESEL (ON ROAD)
GRADE 190 (EPA DESIGNATION: DMV2D015)

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Gravity, API @ 60°F	D287, D4052	30		
Flash Point, °F(at Origin)	D93 or D56	130		1
Color, ASTM	D1500		2.5	
Viscosity, cst @ 104°F	D445	1.9	3.4	
Cloud Point, °F	D2500, D5771, D5772, D5773, D3117			2
Pour Point, °F	D5985, D5949, D5950, D97			3
Total Sulfur, ppm (at Origin)	D5453, D3120			
Receipt from Refinery	D2622, D7039		9.0	
Receipt from Connecting Pipeline			11.0	7,8
Corrosion, 3 hrs. @ 122°F	D130		1	
Oxidation Stability, mg/100 ml or	D2274		2.5	
Thermal Stability, 90 minutes				
150°C Pad rating	DuPont		7	
Carbon Residue, wt. % on 10% bottom	D524 or D4530		0.35	
Ash, wt. %	D482		0.01	
Sediment and Water, % by volume	D2709		0.05	
Cetane Number	D613, D6890	40		
or				
Cetane Index	D4737	40		
Aromatics (Vol%)	D1319		31.7	
Or Aromatics by Cetane Index	D976	40		
Distillation, °F	D86			
50% recovered		Report		
90% recovered		540	640	
End Point			690	
or Simulated Distillation, °C(°F)	D2887			
50% recovered			Report	
90% recovered		300(572)	356(673)	
End Point			421(790)	
Haze Rating @ 77°F	D4176		2	
Procedure 2				
Color Visual		Undyed		4
Additives				5
NACE	TM0172-2001	B+		9

NOTES:

- Test method D-56 may be used as an alternate to D-93 with the same limits. Test method D-93 is the referee method. Minimum flash at delivery is 125 °F.
- Cloud Point - September thru March
Cloud Point - April thru August
- Pour Point - September thru March
Pour Point - April thru August
- Product must exhibit no visible evidence of dye.
- Use of static dissipater additive or conductivity improver is prohibited.
- The use of lubricity improver additives is prohibited.
- This product is for On-Road use and should be designated as such in the EPA's Designate and Track reporting system (DMV1D015).
- Sulfur level at delivery will vary depending upon the origin and delivery location.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).
- Biofuel Components (e.g. biodiesel) are not permitted in this product.

BUCKEYE PARTNERS, L.P.
SPECIFICATIONS FOR FUNGIBLE LOW RVP 87 OCTANE
MTBE-FREE CONVENTIONAL GASOLINE - GRADE 302

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	82.0		
Index, (R+M)/2		87.0		
Oxygenates, vol. %	D4815, D5599, D5845		Report	2
RVP, psi	D5191, D5482		9.00	
Benzene, vol. %	D3606, D4053		4.9	
Sulfur, wt. %	D2622, D5453, D3120		0.0080	8
Doctor Test	D4952		Negative	3
OR				
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237, D5059		0.01	
Phosphorous, gms/gal	D3231		0.004	
Gum, mg/100ml (after washing)	D381		4	
Oxidation Stability, minutes	D525	240		
Odor		Nonoffensive		4
Port Fuel Injector and Intake Valve Detergent Additives				5
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators - Refer to Table 1				
Volatility and Distillation - Refer to Table 2				
MMT				6
Driveability Index	D4814			7
Refer to Table 2				
Silver Strip Corrosion	D4814		1	
NACE	TM0172-2001	B+		9

NOTES:

- No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
- This product may not contain oxygenates, such as ethers or alcohols. The use of non-hydrocarbon blending components is prohibited. The di minimis limit of MTBE, ETBE, and TAME allowed is 0.3 vol. % maximum for each compound at origin.
- Mercaptan Sulfur waived if fuel is negative by Doctor test.
- Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
- The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
- The use of MMT octane enhancing additive is prohibited.
- The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2.
- This sulfur specification is effective December 15, 2005. Any batches moving prior to this are required to comply with the previous maximum of 0.0300 wt. %.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).

BUCKEYE PARTNERS, L.P.
SPECIFICATIONS FOR FUNGIBLE LOW RVP 93 OCTANE
MTBE-FREE CONVENTIONAL GASOLINE - GRADE 305

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	Report		
Index, (R+M)/2		93.0		
Oxygenates, vol. %	D4815, D5599, D5845		Report	2
RVP, psi	D5191, D5482		9.00	
Benzene, vol. %	D3606, D4053		4.9	
Sulfur, wt. %	D2622, D5453, D3120		0.0080	8
Doctor Test	D4952		Negative	3
OR				
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237, D5059		0.01	
Phosphorous, gms/gal	D3231		0.004	
Gum, mg/100ml (after washing)	D381		4	
Oxidation Stability, minutes	D525	240		
Odor		Nonoffensive		4
Port Fuel Injector and Intake Valve Detergent Additives				5
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators - Refer to Table 1				
Volatility and Distillation - Refer to Table 2				
MMT				6
Driveability Index	D4814			7
Refer to Table 2				
Silver Strip Corrosion	D4814		1	
NACE	TM0172-2001	B+		9

NOTES:

- No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
- This product may not contain oxygenates, such as ethers or alcohols. The use of non-hydrocarbon blending components is prohibited. The di minimis limit of MTBE, ETBE, and TAME allowed is 0.3 vol. % maximum for each compound at origin.
- Mercaptan Sulfur waived if fuel is negative by Doctor test.
- Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
- The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
- The use of MMT octane enhancing additive is prohibited.
- The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2.
- This sulfur specification is effective December 15, 2005. Any batches moving prior to this are required to comply with the previous maximum of 0.0300 wt. %.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).

BUCKEYE PARTNERS, L.P.
SPECIFICATIONS FOR FUNGIBLE LOW RVP 91 OCTANE
MTBE-FREE CONVENTIONAL GASOLINE - GRADE 307

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	Report		
Index, (R+M)/2		91.3		
Index, (R+M)/2 when additized with 10% Denatured Fuel Ethanol		93.0		
Oxygenates, vol. %	D4815, D5599, D5845		Report	2
RVP, psi	D5191, D5482		9.00	
Benzene, vol. %	D3606, D4053		4.9	
Sulfur, wt. %	D2622, D5453, D3120		0.0080	8
Doctor Test	D4952		Negative	3
OR				
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237, D5059		0.01	
Phosphorous, gms/gal	D3231		0.004	
Gum, mg/100ml (after washing)	D381		4	
Oxidation Stability, minutes	D525	240		
Odor		Nonoffensive		4
Port Fuel Injector and Intake Valve Detergent Additives				5
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators - Refer to Table 1				
Volatility and Distillation - Refer to Table 2				
MMT				6
Driveability Index	D4814			7
Refer to Table 2				
Silver Strip Corrosion	D4814		1	
NACE	TM0172-2001	B+		9

NOTES:

- No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
- This product may not contain oxygenates, such as ethers or alcohols. The use of non-hydrocarbon blending components is prohibited. The di minimis limit of MTBE, ETBE, and TAME allowed is 0.3 vol. % maximum for each compound at origin.
- Mercaptan Sulfur waived if fuel is negative by Doctor test.
- Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
- The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
- The use of MMT octane enhancing additive is prohibited.
- The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2. In the case of sub-octane gasoline, DI limits will apply after blending with 10% Denatured Fuel Ethanol.
- This sulfur specification is effective December 15, 2005. Any batches moving prior to this are required to comply with the previous maximum of 0.0300 wt. %.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).

BUCKEYE PARTNERS, L.P.
SPECIFICATIONS FOR FUNGIBLE LOW RVP SUB-OCTANE
MTBE-FREE CONVENTIONAL GASOLINE - GRADE 308

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	Report		
Index, (R+M)/2		83.5		
Index, (R+M)/2 when additized with 10% Denatured Fuel Ethanol		87.0		
Oxygenates, vol. %	D4815, D5599, D5845		Report	2
RVP, psi	D5191, D5482		9.00	
Benzene, vol. %	D3606, D4053		4.9	
Sulfur, wt. %	D2622, D5453, D3120		0.0080	8
Doctor Test	D4952		Negative	3
OR				
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237, D5059		0.01	
Phosphorous, gms/gal	D3231		0.004	
Gum, mg/100ml (after washing)	D381		4	
Oxidation Stability, minutes	D525	240		
Odor		Nonoffensive		4
Port Fuel Injector and Intake Valve Detergent Additives				5
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators - Refer to Table 1				
Volatility and Distillation - Refer to Table 2				
MMT				6
Driveability Index	D4814			7
Refer to Table 2				
Silver Strip Corrosion	D4814		1	
NACE	TM0172-2001	B+		9

NOTES:

- No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
- This product may not contain oxygenates, such as ethers or alcohols. The use of non-hydrocarbon blending components is prohibited. The di minimis limit of MTBE, ETBE, and TAME allowed is 0.3 vol. % maximum for each compound at origin.
- Mercaptan Sulfur waived if fuel is negative by Doctor test.
- Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
- The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
- The use of MMT octane enhancing additive is prohibited.
- The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2. In the case of sub-octane gasoline, DI limits will apply after blending with 10% Denatured Fuel Ethanol.
- This sulfur specification is effective December 15, 2005. Any batches moving prior to this are required to comply with the previous maximum of 0.0300 wt. %.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).

BUCKEYE PARTNERS, L.P.
SPECIFICATIONS FOR FUNGIBLE 87 OCTANE
MTBE-FREE CONVENTIONAL GASOLINE - GRADE 312

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	82.0		
Index, (R+M)/2		87.0		
Oxygenates, vol. %	D4815, D5599, D5845		Report	2
Benzene, vol. %	D3606, D4053		4.9	
Sulfur, wt. %	D2622, D5453, D3120		0.0080	8
Doctor Test	D4952		Negative	3
OR				
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237, D5059		0.01	
Phosphorous, gms/gal	D3231		0.004	
Gum, mg/100ml (after washing)	D381		4	
Oxidation Stability, minutes	D525	240		
Odor		Nonoffensive		4
Port Fuel Injector and Intake Valve Detergent Additives				5
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators – Refer to Table 1				
RVP (Eastern Products and Laurel)	D5191			10
September-October			12.9	
November-March			14.5	
All other Volatility and Distillation – Refer to Table 2				
MMT				6
Driveability Index	D4814			7
Refer to Table 2				
Silver Strip Corrosion	D4814		1	
NACE	TM0172-2001	B+		9

NOTES:

- No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
- This product may not contain oxygenates, such as ethers or alcohols. The use of non-hydrocarbon blending components is prohibited. The di minimis limit of MTBE, ETBE, and TAME allowed is 0.3 vol. % maximum for each compound at origin.
- Mercaptan Sulfur waived if fuel is negative by Doctor test.
- Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
- The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
- The use of MMT octane enhancing additive is prohibited.
- The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2.
- This sulfur specification is effective December 15, 2005. Any batches moving prior to this are required to comply with the previous maximum of 0.0300 wt. %.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).
- Eastern Products and Laurel:** RVP limit for 13.5 (D-4) months will be 12.90 psi; RVP limit for 15.0 months (E-5) will be 14.5 psi. **For all other product systems**, RVP limits will be 13.5 psi and 15.0 psi. Refer to Table 2.

BUCKEYE PARTNERS, L.P.
SPECIFICATIONS FOR FUNGIBLE 93 OCTANE
MTBE-FREE CONVENTIONAL GASOLINE – GRADE 315

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	Report		
Index, (R+M)/2		93.0		
Oxygenates, vol. %	D4815, D5599, D5845		Report	2
Benzene, vol. %	D3606, D4053		4.9	
Sulfur, wt. %	D2622, D5453, D3120		0.0080	8
Doctor Test	D4952		Negative	3
OR				
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237, D5059		0.01	
Phosphorous, gms/gal	D3231		0.004	
Gum, mg/100ml (after washing)	D381		4	
Oxidation Stability, minutes	D525	240		
Odor		Nonoffensive		4
Port Fuel Injector and Intake Valve Detergent Additives				5
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators – <i>Refer to Table 1</i>				
RVP (<i>Eastern Products and Laurel</i>)	D5191			10
September-October			12.9	
November-March			14.5	
All other Volatility and Distillation – <i>Refer to Table 2</i>				
MMT				6
Driveability Index	D4814			7
Refer to Table 2				
Silver Strip Corrosion	D4814		1	
NACE	TM0172-2001	B+		9

NOTES:

- No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
- This product may not contain oxygenates, such as ethers or alcohols. The use of non-hydrocarbon blending components is prohibited. The maximum limit of MTBE, ETBE, and TAME allowed is 0.3 vol. % maximum for each compound at origin.
- Mercaptan Sulfur waived if fuel is negative by Doctor test.
- Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
- The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
- The use of MMT octane enhancing additive is prohibited.
- The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2.
- This sulfur specification is effective December 15, 2005. Any batches moving prior to this are required to comply with the previous maximum of 0.0300 wt. %.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).
- Eastern Products and Laurel:*** RVP limit for 13.5 (D-4) months will be 12.90 psi; RVP limit for 15.0 months (E-5) will be 14.5 psi. ***For all other product systems,*** RVP limits will be 13.5 psi and 15.0 psi. Refer to Table 2.

BUCKEYE PARTNERS, L.P.
SPECIFICATIONS FOR FUNGIBLE 91 OCTANE
MTBE-FREE CONVENTIONAL GASOLINE - GRADE 317

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	Report		
Index, (R+M)/2		91.3		
Index, (R+M)/2 when additized with 10% Denatured Fuel Ethanol		93.0		
Oxygenates, vol. %	D4815, D5599, D5845		Report	2
Benzene, vol. %	D3606, D4053		4.9	
Sulfur, wt. %	D2622, D5453, D3120		0.0080	8
Doctor Test	D4952		Negative	3
OR				
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237, D5059		0.01	
Phosphorous, gms/gal	D3231		0.004	
Gum, mg/100ml (after washing)	D381		4	
Oxidation Stability, minutes	D525	240		
Odor		Nonoffensive		4
Port Fuel Injector and Intake Valve Detergent Additives				5
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators - Refer to Table 1				
Distillation –	D86			
50% Evap (T50) without ethanol		170		
50% Evap (T50) with 10% ethanol		150		
All other distillation - Refer to Table 2				
RVP	D5191			10
September-October			12.9	
November-March			14.5	
MMT				6
Driveability Index	D4814			7
Refer to Table 2				
Silver Strip Corrosion	D4814		1	
NACE	TM0172-2001	B+		9

NOTES:

- No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
- This product may not contain oxygenates, such as ethers or alcohols. The use of non-hydrocarbon blending components is prohibited. The di minimis limit of MTBE, ETBE, and TAME allowed is 0.3 vol. % maximum for each compound at origin.
- Mercaptan Sulfur waived if fuel is negative by Doctor test.
- Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
- The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
- The use of MMT octane enhancing additive is prohibited.
- The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2. In the case of sub-octane gasoline, DI limits will apply after blending with 10% Denatured Fuel Ethanol.
- This sulfur specification is effective December 15, 2005. Any batches moving prior to this are required to comply with the previous maximum of 0.0300 wt. %.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).
- RVP limit for 13.5 (D-4) months will be 12.90 psi; RVP limit for 15.0 months (E-5) will be 14.5 psi. Refer to Table 2.
- All specifications must be certified without ethanol, except as noted above.

BUCKEYE PARTNERS, L.P.
SPECIFICATIONS FOR FUNGIBLE SUB-OCTANE
MTBE-FREE CONVENTIONAL GASOLINE - GRADE 318

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	Report		
Index, (R+M)/2		83.5		
Index, (R+M)/2 when additized with 10% Denatured Fuel Ethanol		87.0		
Oxygenates, vol. %	D4815, D5599, D5845		Report	2
Benzene, vol. %	D3606, D4053		4.9	
Sulfur, wt. %	D2622, D5453, D3120		0.0080	8
Doctor Test	D4952		Negative	3
OR				
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237, D5059		0.01	
Phosphorous, gms/gal	D3231		0.004	
Gum, mg/100ml (after washing)	D381		4	
Oxidation Stability, minutes	D525	240		
Odor		Nonoffensive		4
Port Fuel Injector and Intake Valve Detergent Additives				5
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators - <i>Refer to Table 1</i>				
Distillation –	D86			
50% Evap (T50) without ethanol		170		
50% Evap (T50) with 10% ethanol		150		
All other distillation - <i>Refer to Table 2</i>				
RVP	D5191			10
September-October			12.9	
November-March			14.5	
MMT				6
Driveability Index	D4814			7
Refer to Table 2				
Silver Strip Corrosion	D4814		1	
NACE	TM0172-2001	B+		9

NOTES:

- No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
- This product may not contain oxygenates, such as ethers or alcohols. The use of non-hydrocarbon blending components is prohibited. The di minimis limit of MTBE, ETBE, and TAME allowed is 0.3 vol. % maximum for each compound at origin.
- Mercaptan Sulfur waived if fuel is negative by Doctor test.
- Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
- The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
- The use of MMT octane enhancing additive is prohibited.
- The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2. In the case of sub-octane gasoline, DI limits will apply after blending with 10% Denatured Fuel Ethanol.
- This sulfur specification is effective December 15, 2005. Any batches moving prior to this are required to comply with the previous maximum of 0.0300 wt. %.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).
- RVP limit for 13.5 (D-4) months will be 12.90 psi; RVP limit for 15.0 months (E-5) will be 14.5 psi. Refer to Table 2.
- All specifications must be certified without ethanol, except as noted above.

BUCKEYE PARTNERS, L.P.
SPECIFICATIONS FOR FUNGIBLE 87 OCTANE
MTBE-FREE CONVENTIONAL GASOLINE - GRADE 322

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	82.0		
Index, (R+M)/2		87.0		
Oxygenates, vol. %	D4815, D5599, D5845		Report	2
RVP, psi	D5191, D5482		7.8	
Benzene, vol. %	D3606, D4053		4.9	
Sulfur, wt. %	D2622, D5453, D3120		0.0080	8
Doctor Test	D4952		Negative	3
OR				
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237, D5059		0.01	
Phosphorous, gms/gal	D3231		0.004	
Gum, mg/100ml (after washing)	D381		4	
Oxidation Stability, minutes	D525	240		
Odor		Nonoffensive		4
Port Fuel Injector and Intake Valve Detergent Additives				5
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators – Refer to Table 1				
Volatility and Distillation – Refer to Table 2				
MMT				6
Driveability Index	D4814			7
Refer to Table 2				
Silver Strip Corrosion	D4814		1	
NACE	TM0172-2001	B+		9

NOTES:

- No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
- This product may not contain oxygenates, such as ethers or alcohols. The use of non-hydrocarbon blending components is prohibited. The di minimis limit of MTBE, ETBE, and TAME allowed is 0.3 vol. % maximum for each compound at origin.
- Mercaptan Sulfur waived if fuel is negative by Doctor test.
- Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
- The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
- The use of MMT octane enhancing additive is prohibited.
- The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2.
- This sulfur specification is effective December 15, 2005. Any batches moving prior to this are required to comply with the previous maximum of 0.0300 wt. %.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).

BUCKEYE PARTNERS, L.P.
SPECIFICATIONS FOR FUNGIBLE 93 OCTANE
MTBE-FREE CONVENTIONAL GASOLINE – GRADE 325

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	Report		
Index, (R+M)/2		93.0		
Oxygenates, vol. %	D4815, D5599, D5845		Report	2
RVP, psi	D5191, D5482		7.8	
Benzene, vol. %	D3606, D4053		4.9	
Sulfur, wt. %	D2622, D5453, D3120		0.0080	8
Doctor Test	D4952		Negative	3
OR				
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237, D5059		0.01	
Phosphorous, gms/gal	D3231		0.004	
Gum, mg/100ml (after washing)	D381		4	
Oxidation Stability, minutes	D525	240		
Odor		Nonoffensive		4
Port Fuel Injector and Intake Valve Detergent Additives				5
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators – Refer to Table 1				
Volatility and Distillation – Refer to Table 2				
MMT				6
Driveability Index	D4814			7
Refer to Table 2				
Silver Strip Corrosion	D4814		1	
NACE	TM0172-2001	B+		9

NOTES:

- No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
- This product may not contain oxygenates, such as ethers or alcohols. The use of non-hydrocarbon blending components is prohibited. The di minimis limit of MTBE, ETBE, and TAME allowed is 0.3 vol. % maximum for each compound at origin.
- Mercaptan Sulfur waived if fuel is negative by Doctor test.
- Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
- The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
- The use of MMT octane enhancing additive is prohibited.
- The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2.
- This sulfur specification is effective December 15, 2005. Any batches moving prior to this are required to comply with the previous maximum of 0.0300 wt. %.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).

BUCKEYE PARTNERS, L.P.
SPECIFICATIONS FOR FUNGIBLE 91 OCTANE
MTBE-FREE CONVENTIONAL GASOLINE - GRADE 327

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	Report		
Index, (R+M)/2		91.3		
Index, (R+M)/2 when additized with 10% Denatured Fuel Ethanol		93.0		
Oxygenates, vol. %	D4815, D5599, D5845		Report	2
RVP, psi	D5191, D5482		7.80	
Benzene, vol. %	D3606, D4053		4.9	
Sulfur, wt. %	D2622, D5453, D3120		0.0080	8
Doctor Test	D4952		Negative	3
OR				
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237, D5059		0.01	
Phosphorous, gms/gal	D3231		0.004	
Gum, mg/100ml (after washing)	D381		4	
Oxidation Stability, minutes	D525	240		
Odor		Nonoffensive		4
Port Fuel Injector and Intake Valve Detergent Additives				5
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators - Refer to Table 1				
Distillation –	D86			
50% Evap (T50) with 10% ethanol		170	250	
T V/L = 20 with 10% ethanol	D5188			
April-May		116		
June-September 15		124		
All other Volatility and Distillation – Refer to Table 2				
MMT				6
Driveability Index	D4814			7
Refer to Table 2				
Silver Strip Corrosion	D4814		1	
NACE	TM0172-2001	B+		9

NOTES:

- No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
- This product may not contain oxygenates, such as ethers or alcohols. The use of non-hydrocarbon blending components is prohibited. The di minimis limit of MTBE, ETBE, and TAME allowed is 0.3 vol. % maximum for each compound at origin.
- Mercaptan Sulfur waived if fuel is negative by Doctor test.
- Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
- The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
- The use of MMT octane enhancing additive is prohibited.
- The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2. In the case of sub-octane gasoline, DI limits will apply after blending with 10% Denatured Fuel Ethanol.
- This sulfur specification is effective December 15, 2005. Any batches moving prior to this are required to comply with the previous maximum of 0.0300 wt. %.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).

BUCKEYE PARTNERS, L.P.
SPECIFICATIONS FOR FUNGIBLE SUB-OCTANE
MTBE-FREE CONVENTIONAL GASOLINE - GRADE 328

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	Report		
Index, (R+M)/2		83.5		
Index, (R+M)/2 when additized with 10% Denatured Fuel Ethanol		87.0		
Oxygenates, vol. %	D4815, D5599, D5845		Report	2
RVP, psi	D5191, D5482		7.80	
Benzene, vol. %	D3606, D4053		4.9	
Sulfur, wt. %	D2622, D5453, D3120		0.0080	8
Doctor Test	D4952		Negative	3
OR				
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237, D5059		0.01	
Phosphorous, gms/gal	D3231		0.004	
Gum, mg/100ml (after washing)	D381		4	
Oxidation Stability, minutes	D525	240		
Odor		Nonoffensive		4
Port Fuel Injector and Intake Valve Detergent Additives				5
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators - Refer to Table 1				
Distillation –	D86			
50% Evap (T50) with 10% ethanol		170	250	
T V/L = 20 with 10% ethanol	D5188			
April-May		116		
June-September 15		124		
All other Volatility and Distillation – Refer to Table 2				
MMT				6
Driveability Index	D4814			7
Refer to Table 2				
Silver Strip Corrosion	D4814		1	
NACE	TM0172-2001	B+		9

NOTES:

- No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
- This product may not contain oxygenates, such as ethers or alcohols. The use of non-hydrocarbon blending components is prohibited. The di minimis limit of MTBE, ETBE, and TAME allowed is 0.3 vol. % maximum for each compound at origin.
- Mercaptan Sulfur waived if fuel is negative by Doctor test.
- Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
- The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
- The use of MMT octane enhancing additive is prohibited.
- The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2. In the case of sub-octane gasoline, DI limits will apply after blending with 10% Denatured Fuel Ethanol.
- This sulfur specification is effective December 15, 2005. Any batches moving prior to this are required to comply with the previous maximum of 0.0300 wt. %.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).

BUCKEYE PARTNERS, L.P.
SPECIFICATIONS FOR FUNGIBLE 87 OCTANE
MTBE-FREE CONVENTIONAL GASOLINE - GRADE 332
(S.E. MICHIGAN DESTINATIONS ONLY)

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	82.0		
Index, (R+M)/2		87.0		
Oxygenates, vol. %	D4815, D5599, D5845		Report	2
RVP, psi	D5191, D5482		6.8	
Benzene, vol. %	D3606, D4053		4.9	
Sulfur, wt. %	D2622, D5453, D3120		0.0080	8
Doctor Test	D4952		Negative	3
OR				
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237, D5059		0.01	
Phosphorous, gms/gal	D3231		0.004	
Gum, mg/100ml (after washing)	D381		4	
Oxidation Stability, minutes	D525	240		
Odor		Nonoffensive		4
Port Fuel Injector and Intake Valve Detergent Additives				5
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators – Refer to Table 1				
Volatility and Distillation – Refer to Table 2				
MMT				6
Driveability Index	D4814			7
Refer to Table 2				
Silver Strip Corrosion	D4814		1	
NACE	TM0172-2001	B+		9

NOTES:

- No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
- This product may not contain oxygenates, such as ethers or alcohols. The use of non-hydrocarbon blending components is prohibited. The di minimis limit of MTBE, ETBE, and TAME allowed is 0.3 vol. % maximum for each compound at origin.
- Mercaptan Sulfur waived if fuel is negative by Doctor test.
- Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
- The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
- The use of MMT octane enhancing additive is prohibited.
- The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2.
- This sulfur specification is effective December 15, 2005. Any batches moving prior to this are required to comply with the previous maximum of 0.0300 wt. %.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).

BUCKEYE PARTNERS, L.P.
SPECIFICATIONS FOR FUNGIBLE 93 OCTANE
MTBE-FREE CONVENTIONAL GASOLINE – GRADE 335
(S.E. MICHIGAN DESTINATIONS ONLY)

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	Report		
Index, (R+M)/2		93.0		
Oxygenates, vol. %	D4815, D5599, D5845		Report	2
RVP, psi	D5191, D5482		6.8	
Benzene, vol. %	D3606, D4053		4.9	
Sulfur, wt. %	D2622, D5453, D3120		0.0080	8
Doctor Test	D4952		Negative	3
OR				
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237, D5059		0.01	
Phosphorous, gms/gal	D3231		0.004	
Gum, mg/100ml (after washing)	D381		4	
Oxidation Stability, minutes	D525	240		
Odor		Nonoffensive		4
Port Fuel Injector and Intake Valve Detergent Additives				5
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators – Refer to Table 1				
Volatility and Distillation – Refer to Table 2				
MMT				6
Driveability Index	D4814			7
Refer to Table 2				
Silver Strip Corrosion	D4814		1	
NACE	TM0172-2001	B+		9

NOTES:

- No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
- This product may not contain oxygenates, such as ethers or alcohols. The use of non-hydrocarbon blending components is prohibited. The di minimis limit of MTBE, ETBE, and TAME allowed is 0.3 vol. % maximum for each compound at origin.
- Mercaptan Sulfur waived if fuel is negative by Doctor test.
- Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
- The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
- The use of MMT octane enhancing additive is prohibited.
- The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2.
- This sulfur specification is effective December 15, 2005. Any batches moving prior to this are required to comply with the previous maximum of 0.0300 wt. %.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).

BUCKEYE PARTNERS, L.P.
SPECIFICATIONS FOR FUNGIBLE 91 OCTANE
MTBE-FREE CONVENTIONAL GASOLINE - GRADE 337
(S.E. MICHIGAN DESTINATIONS ONLY)

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	Report		
Index, (R+M)/2		91.3		
Index, (R+M)/2 when additized with 10% Denatured Fuel Ethanol		93.0		
Oxygenates, vol. %	D4815, D5599, D5845		Report	2
RVP, psi	D5191, D5482		6.8	
Benzene, vol. %	D3606, D4053		4.9	
Sulfur, wt. %	D2622, D5453, D3120		0.0080	8
Doctor Test	D4952		Negative	3
OR				
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237, D5059		0.01	
Phosphorous, gms/gal	D3231		0.004	
Gum, mg/100ml (after washing)	D381		4	
Oxidation Stability, minutes	D525	240		
Odor		Nonoffensive		4
Port Fuel Injector and Intake Valve Detergent Additives				5
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators - Refer to Table 1				
Distillation –	D86			
50% Evap (T50) with 10% ethanol		170	250	
T V/L = 20 with 10% ethanol	D5188			
April-May		116		
June-September 15		124		
All other Volatility and Distillation – Refer to Table 2				
MMT				6
Driveability Index	D4814			7
Refer to Table 2				
Silver Strip Corrosion	D4814		1	
NACE	TM0172-2001	B+		9

NOTES:

- No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
- This product may not contain oxygenates, such as ethers or alcohols. The use of non-hydrocarbon blending components is prohibited. The di minimis limit of MTBE, ETBE, and TAME allowed is 0.3 vol. % maximum for each compound at origin.
- Mercaptan Sulfur waived if fuel is negative by Doctor test.
- Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
- The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
- The use of MMT octane enhancing additive is prohibited.
- The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2. In the case of sub-octane gasoline, DI limits will apply after blending with 10% Denatured Fuel Ethanol.
- This sulfur specification is effective December 15, 2005. Any batches moving prior to this are required to comply with the previous maximum of 0.0300 wt. %.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).

BUCKEYE PARTNERS, L.P.
SPECIFICATIONS FOR FUNGIBLE SUB-OCTANE
MTBE-FREE CONVENTIONAL GASOLINE - GRADE 338
(S.E. MICHIGAN DESTINATIONS ONLY)

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	Report		
Index, (R+M)/2		83.5		
Index, (R+M)/2 when additized with 10% Denatured Fuel Ethanol		87.0		
Oxygenates, vol. %	D4815, D5599, D5845		Report	2
RVP, psi	D5191, D5482		6.8	
Benzene, vol. %	D3606, D4053		4.9	
Sulfur, wt. %	D2622, D5453, D3120		0.0080	8
Doctor Test	D4952		Negative	3
OR				
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237, D5059		0.01	
Phosphorous, gms/gal	D3231		0.004	
Gum, mg/100ml (after washing)	D381		4	
Oxidation Stability, minutes	D525	240		
Odor		Nonoffensive		4
Port Fuel Injector and Intake Valve Detergent Additives				5
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators - Refer to Table 1				
Distillation –	D86			
50% Evap (T50) with 10% ethanol		170	250	
T V/L = 20 with 10% ethanol	D5188			
April-May		116		
June-September 15		124		
All other Volatility and Distillation – Refer to Table 2				
MMT				6
Driveability Index	D4814			7
Refer to Table 2				
Silver Strip Corrosion	D4814		1	
NACE	TM0172-2001	B+		9

NOTES:

- No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
- This product may not contain oxygenates, such as ethers or alcohols. The use of non-hydrocarbon blending components is prohibited. The di minimis limit of MTBE, ETBE, and TAME allowed is 0.3 vol. % maximum for each compound at origin.
- Mercaptan Sulfur waived if fuel is negative by Doctor test.
- Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
- The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
- The use of MMT octane enhancing additive is prohibited.
- The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2. In the case of sub-octane gasoline, DI limits will apply after blending with 10% Denatured Fuel Ethanol.
- This sulfur specification is effective December 15, 2005. Any batches moving prior to this are required to comply with the previous maximum of 0.0300 wt. %.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).

BUCKEYE PARTNERS, L.P.
(LONG ISLAND SYSTEM ONLY)
SPECIFICATIONS FOR FUNGIBLE VOC CONTROLLED REGION 2 — 87 OCTANE
REFORMULATED GASOLINE - GRADE 502

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	82.0		
Index, (R+M)/2		87.0		
Oxygenates, vol. %	D4815, GC-OFID		Report	2, 3
Oxygen, wt. %	D4815, GC-OFID	1.5	2.7	3
RVP, psi	D5191		7.8	
Benzene, vol. %	D3606		1.30	
Doctor Test	D4952		Negative	4
OR				
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237 or equiv.		0.01	
Phosphorous, gms/gal	D3231		0.004	
Gum, mg/100ml (after washing)	D381		4	
Oxidation Stability, minutes	D525	240		
Aromatics, vol. %	GCMS, D5769		50.0	3
Emissions Performance Reductions				
VOC Region 2, %	EPA	25.4		
Olefins, vol. %	D1319		25.0	
Sulfur, wt. %	D2622, D5453, D3120		.0080	9
Odor		Nonoffensive		4
Port Fuel Injector and Intake Valve Detergent Additives				6
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators - Refer to Table 1				
Volatility and Distillation - Refer to Table 2				
E200, vol. %	D86	30.0	70.0	
E300, vol. %	D86	70.0	100.0	
MMT				7
Driveability Index	D4814			8
Refer to Table 2				
Silver Strip Corrosion	D4814		1	
NACE	TM0172-2001	B+		10

NOTES:

- No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
- Non-hydrocarbon blending components are to be reported on the certified laboratory report by type and percent. This product is required to contain blends of aliphatic ethers. The use of any other non-hydrocarbons as blending components is prohibited.
- Refer to test methods published in 40 CFR Chapter 1, Part 80.46.
- Mercaptan Sulfur waived if fuel is negative by Doctor test.
- Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
- The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
- The use of MMT octane enhancing additive is prohibited.
- The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2.
- This sulfur specification is effective December 15, 2005. Any batches moving prior to this are required to comply with the previous maximum of 0.0300 wt. %.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).

BUCKEYE PARTNERS, L.P.
(LONG ISLAND SYSTEM ONLY)
SPECIFICATIONS FOR FUNGIBLE VOC CONTROLLED REGION 2 — 89 OCTANE
REFORMULATED GASOLINE - GRADE 503

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	83.0		
Index, (R+M)/2		89.0		
Oxygenates, vol. %	D4815, GC-OFID		Report	2, 3
Oxygen, wt. %	D4815, GC-OFID	1.5	2.7	3
RVP, psi	D5191		7.8	
Benzene, vol. %	D3606		1.30	
Doctor Test	D4952		Negative	4
OR				
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237 or equiv.		0.01	
Phosphorous, gms/gal	D3231		0.004	
Gum, mg/100ml (after washing)	D381		4	
Oxidation Stability, minutes	D525	240		
Aromatics, vol. %	GCMS, D5769		50.0	3
Emissions Performance Reductions				
VOC Region 2, %	EPA	25.4		
Olefins, vol. %	D1319		25.0	
Sulfur, wt. %	D2622, D5453, D3120		.0080	9
Odor		Nonoffensive		4
Port Fuel Injector and Intake Valve Detergent Additives				6
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators - Refer to Table 1				
Volatility and Distillation - Refer to Table 2				
E200, vol. %	D86	30.0	70.0	
E300, vol. %	D86	70.0	100.0	
MMT				7
Driveability Index	D4814			8
Refer to Table 2				
Silver Strip Corrosion	D4814		1	
NACE	TM0172-2001	B+		10

NOTES:

- No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
- Non-hydrocarbon blending components are to be reported on the certified laboratory report by type and percent. This product is required to contain blends of aliphatic ethers. The use of any other non-hydrocarbons as blending components is prohibited.
- Refer to test methods published in 40 CFR Chapter 1, Part 80.46.
- Mercaptan Sulfur waived if fuel is negative by Doctor test.
- Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
- The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
- The use of MMT octane enhancing additive is prohibited.
- The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2.
- This sulfur specification is effective December 15, 2005. Any batches moving prior to this are required to comply with the previous maximum of 0.0300 wt. %.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).

BUCKEYE PARTNERS, L.P.
(LONG ISLAND SYSTEM ONLY)
SPECIFICATIONS FOR FUNGIBLE VOC CONTROLLED REGION 2 — 93 OCTANE
REFORMULATED GASOLINE - GRADE 505

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	Report		
Index, (R+M)/2		93.0		
Oxygenates, vol. %	D4815, GC-OFID		Report	2, 3
Oxygen, wt. %	D4815, GC-OFID	1.5	2.7	3
RVP, psi	D5191		7.8	
Benzene, vol. %	D3606		1.30	
Doctor Test	D4952		Negative	4
OR				
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237 or equiv.		0.01	
Phosphorous, gms/gal	D3231		0.004	
Gum, mg/100ml (after washing)	D381		4	
Oxidation Stability, minutes	D525	240		
Aromatics, vol. %	GCMS, D5769		50.0	3
Emissions Performance Reductions				
VOC Region 2, %	EPA	25.4		
Olefins, vol. %	D1319		25.0	
Sulfur, wt. %	D2622, D5453, D3120		.0080	9
Odor		Nonoffensive		4
Port Fuel Injector and Intake Valve Detergent Additives				6
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators - Refer to Table 1				
Volatility and Distillation - Refer to Table 2				
E200, vol. %	D86	30.0	70.0	
E300, vol. %	D86	70.0	100.0	
MMT				7
Driveability Index (DI)	D4814			8
Refer to Table 2				
Silver Strip Corrosion	D4814		1	
NACE	TM0172-2001	B+		10

NOTES:

- No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
- Non-hydrocarbon blending components are to be reported on the certified laboratory report by type and percent. This product is required to contain blends of aliphatic ethers. The use of any other non-hydrocarbons as blending components is prohibited.
- Refer to test methods published in 40 CFR Chapter 1, Part 80.46.
- Mercaptan Sulfur waived if fuel is negative by Doctor test.
- Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
- The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
- The use of MMT octane enhancing additive is prohibited.
- The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2.
- This sulfur specification is effective December 15, 2005. Any batches moving prior to this are required to comply with the previous maximum of 0.0300 wt. %.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).

BUCKEYE PARTNERS, L.P.
(LONG ISLAND SYSTEM ONLY)
SPECIFICATIONS FOR FUNGIBLE NON-VOC CONTROLLED REGION 2 —
87 OCTANE REFORMULATED GASOLINE - GRADE 512

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	82.0		
Index, (R+M)/2		87.0		
Oxygenates, vol. %	D4815, GC-OFID		Report	2, 3
Oxygen, wt. %	D4815, GC-OFID	1.5	2.9	3
Benzene, vol. %	D3606		1.30	
Doctor Test	D4952		Negative	4
OR				
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237 or equiv.		0.01	
Phosphorous, gms/gal	D3231		0.004	
Gum, mg/100ml (after washing)	D381		4	
Oxidation Stability, minutes	D525	240		
Aromatics, vol. %	GCMS, D5769		50.0	3
Olefins, vol. %	D1319		25.0	
Sulfur, wt. %	D2622, D5453, D3120		.0080	9
Odor		Nonoffensive		4
Port Fuel Injector and Intake Valve Detergent Additives				6
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators –				
Refer to Table 1				
Volatility and Distillation –				
Refer to Table 2				
E200, vol. %	D86	30.0	70.0	
E300, vol. %	D86	70.0	100.0	
MMT				7
Driveability Index (DI)	D4814			8
Refer to Table 2				
Silver Strip Corrosion	D4814		1	
NACE	TM0172-2001	B+		10

NOTES:

- No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
- Non-hydrocarbon blending components are to be reported on the certified laboratory report by type and percent. This product is required to contain blends of aliphatic ethers. The use of any other non-hydrocarbons as blending components is prohibited.
- Refer to test methods published in 40 CFR Chapter 1, Part 80.46.
- Mercaptan Sulfur waived if fuel is negative by Doctor test.
- Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
- The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
- The use of MMT octane enhancing additive is prohibited.
- The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2.
- This sulfur specification is effective December 15, 2005. Any batches moving prior to this are required to comply with the previous maximum of 0.0300 wt. %.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).

BUCKEYE PARTNERS, L.P.
(LONG ISLAND SYSTEM ONLY)
SPECIFICATIONS FOR FUNGIBLE NON-VOC CONTROLLED REGION 2 —
89 OCTANE REFORMULATED GASOLINE - GRADE 513

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	83.0		
Index, (R+M)/2		89.0		
Oxygenates, vol. %	D4815, GC-OFID		Report	2, 3
Oxygen, wt. %	D4815, GC-OFID	1.5	2.9	3
Benzene, vol. %	D3606		1.30	
Doctor Test	D4952		Negative	4
OR				
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237 or equiv.		0.01	
Phosphorous, gms/gal	D3231		0.004	
Gum, mg/100ml (after washing)	D381		4	
Oxidation Stability, minutes	D525	240		
Aromatics, vol. %	GCMS, D5769		50.0	3
Olefins, vol. %	D1319		25.0	
Sulfur, wt. %	D2622, D5453, D3120		.0080	9
Odor		Nonoffensive		4
Port Fuel Injector and Intake Valve Detergent Additives				6
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators - Refer to Table 1				
Volatility and Distillation - Refer to Table				
E200, vol. %	D86	30.0	70.0	
E300, vol. %	D86	70.0	100.0	
MMT				7
Driveability Index (DI)	D4814			8
Refer to Table 2				
Silver Strip Corrosion	D4814		1	
NACE	TM0172-2001	B+		10

NOTES:

- No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
- Non-hydrocarbon blending components are to be reported on the certified laboratory report by type and percent. This product is required to contain blends of aliphatic ethers. The use of any other non-hydrocarbons as blending components is prohibited.
- Refer to test methods published in 40 CFR Chapter 1, Part 80.46.
- Mercaptan Sulfur waived if fuel is negative by Doctor test.
- Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
- The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
- The use of MMT octane enhancing additive is prohibited.
- The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2.
- This sulfur specification is effective December 15, 2005. Any batches moving prior to this are required to comply with the previous maximum of 0.0300 wt. %.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).

BUCKEYE PARTNERS, L.P.
(LONG ISLAND SYSTEM ONLY)
SPECIFICATIONS FOR FUNGIBLE NON-VOC CONTROLLED REGION 2 —
93 OCTANE REFORMULATED GASOLINE - GRADE 515

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		Motor
Number D2700, D2885	Report			
Index, (R+M)/2		93.0		
Oxygenates, vol. %	D4815, GC-OFID		Report	2, 3
Oxygen, wt. %	D4815, GC-OFID	1.5	2.9	3
Benzene, vol. %	D3606		1.30	
Doctor Test	D4952		Negative	4
OR				
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237 or equiv.		0.01	
Phosphorous, gms/gal	D3231		0.004	
Gum, mg/100ml (after washing)	D381		4	
Oxidation Stability, minutes	D525	240		
Aromatics, vol. %	GCMS, D5769		50.0	3
Olefins, vol. %	D1319		25.0	
Sulfur, wt. %	D2622, D5453, D3120		.0080	9
Odor		Nonoffensive		4
Port Fuel Injector and Intake Valve Detergent Additives				6
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators - Refer to Table 1				
Volatility and Distillation - Refer to Table 2				
E200, vol. %	D86	30.0	70.0	
E300, vol. %	D86	70.0	100.0	
MMT				7
Driveability Index (DI)	D4814			8
Refer to Table 2				
Silver Strip Corrosion	D4814		1	
NACE	TM0172-2001	B+		10

NOTES:

- No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
- Non-hydrocarbon blending components are to be reported on the certified laboratory report by type and percent. This product is required to contain blends of aliphatic ethers. The use of any other non-hydrocarbons as blending components is prohibited.
- Refer to test methods published in 40 CFR Chapter 1, Part 80.46.
- Mercaptan Sulfur waived if fuel is negative by Doctor test.
- Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
- The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
- The use of MMT octane enhancing additive is prohibited.
- The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2.
- This sulfur specification is effective December 15, 2005. Any batches moving prior to this are required to comply with the previous maximum of 0.0300 wt. %.
- All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).

BUCKEYE PARTNERS, L.P.
(LONG ISLAND SYSTEM AND WOOD RIVER SYSTEM)
SPECIFICATIONS FOR FUNGIBLE VOC CONTROLLED REGION 2
REFORMULATED REGULAR GASOLINE BLENDSTOCK (RBOB) FOR BLENDING WITH
10% DENATURED FUEL ETHANOL (92% PURITY) AS DEFINED IN ASTM D4806
GRADE 532
(Page 1 of 2)

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	80.0		
Index, (R+M)/2 when additized with 10% Denatured Fuel Ethanol		87.0		
Oxygen, wt. %	D5599, GC-OFID	Report		2,3, 9
RVP, psi	D5191		Report	3
Benzene, vol. %	D3606		1.30	
Doctor Test	D4952		Negative	4
OR				
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237 or equiv.		0.01	
Phosphorous, gms/gal	D3231		0.004	
Gum, mg/100ml (after washing)	D381		4	
Oxidation Stability, minutes	D525	240		
Aromatics, vol. %	GCMS, D5769		50.0	3
Emissions Performance Reductions				
VOC Region 2 (Long Island), %	EPA	25.4		11
VOC Region 2 (Chicago), %	EPA	23.4		
Olefins, vol. %	D1319		25.0	
Sulfur, wt. %	D2622, D5453, D3120		.0080	10
Odor		Nonoffensive		5
Port Fuel Injector and Intake Valve Detergent Additives				6
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators - Refer to Table 1				
Volatility and Distillation - Refer to Table 2				
E200, vol. %	D86	30.0	70.0	
E300, vol. %	D86	70.0	100.0	
MMT				7
Driveability Index	D4814			8
Refer to Table 2				
Silver Strip Corrosion	D4814		1	
NACE	TM0172-2001	B+		12

This RBOB may not be combined with any other RBOB except RBOB having the same requirement for oxygenate type and amount.

All parameters must be met after blending with denatured fuel ethanol unless noted.

BUCKEYE PARTNERS, L.P.
(LONG ISLAND SYSTEM AND WOOD RIVER SYSTEM)

**SPECIFICATIONS FOR FUNGIBLE VOC CONTROLLED REGION 2
REFORMULATED REGULAR GASOLINE BLENDSTOCK (RBOB) FOR BLENDING WITH
10% DENATURED FUEL ETHANOL (92% PURITY) AS DEFINED IN ASTM D4806
GRADE 532**

(Page 2 of 2)

NOTES:

1. No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
2. This product may not contain oxygenates such as ethers or alcohols. The use of non-hydrocarbon blending components is prohibited. The maximum limit of MTBE, ETBE, and TAME allowed is 0.3 vol.% maximum for each compound at origin.
3. Refer to test methods published in 40 CFR Chapter 1, Part 80.46.
4. Mercaptan Sulfur waived if fuel is negative by Doctor test.
5. Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
6. The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
7. The use of MMT octane enhancing additive is prohibited.
8. The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2 and will apply after blending with 10% Denatured Fuel Ethanol.
9. Oxygen content must meet a minimum of 1.5 wt. % and a maximum of 4.0 wt. % after blending with Denatured Fuel Ethanol.
10. This sulfur specification is effective December 15, 2005. Any batches moving prior to this are required to comply with the previous maximum of 0.0300 wt. %.
11. The listed VOC reduction is required at origin. The VOC reduction at delivery will meet EPA requirements.
12. All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).

BUCKEYE PARTNERS, L.P.
WOOD RIVER PIPE LINES LLC
(LONG ISLAND SYSTEM AND WOOD RIVER SYSTEM)
SPECIFICATIONS FOR FUNGIBLE VOC CONTROLLED REGION 2
REFORMULATED PREMIUM GASOLINE BLENDSTOCK (RBOB) FOR BLENDING WITH
10% DENATURED FUEL ETHANOL (92% PURITY) AS DEFINED IN ASTM D4806
GRADE 535
(Page 1 of 2)

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	Report		
Index, (R+M)/2 when additized with 10% Denatured Fuel Ethanol		93.0		
Oxygen, wt. %	D5599, GC-OFID	Report		2,3, 9
RVP, psi	D5191		Report	3
Benzene, vol. %	D3606		1.30	
Doctor Test	D4952		Negative	4
OR				
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237 or equiv.		0.01	
Phosphorous, gms/gal	D3231		0.004	
Gum, mg/100ml (after washing)	D381		4	
Oxidation Stability, minutes	D525	240		
Aromatics, vol. %	GCMS, D5769		50.0	3
Emissions Performance Reductions				
VOC Region 2, %	EPA	25.4		11
VOC Region 2 (Chicago), %	EPA	23.4		
Olefins, vol. %	D1319		25.0	
Sulfur, wt. %	D2622, D5453, D3120		.0080	10
Odor		Nonoffensive		5
Port Fuel Injector and Intake Valve Detergent Additives				6
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators - Refer to Table 1				
Volatility and Distillation - Refer to Table 2				
E200, vol. %	D86	30.0	70.0	
E300, vol. %	D86	70.0	100.0	
MMT				7
Driveability Index	D4814			8
Refer to Table 2				
Silver Strip Corrosion	D4814		1	
NACE	TM0172-2001	B+		12

This RBOB may not be combined with any other RBOB except RBOB having the same requirement for oxygenate type and amount.

All parameters must be met after blending with denatured fuel ethanol unless noted.

BUCKEYE PARTNERS, L.P.
(LONG ISLAND SYSTEM AND WOOD RIVER SYSTEM)

**SPECIFICATIONS FOR FUNGIBLE VOC CONTROLLED REGION 2
REFORMULATED PREMIUM GASOLINE BLENDSTOCK (RBOB) FOR BLENDING WITH
10% DENATURED FUEL ETHANOL (92% PURITY) AS DEFINED IN ASTM D4806
GRADE 535**

(Page 2 of 2)

NOTES:

1. No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
2. This product may not contain oxygenates such as ethers or alcohols. The use of non-hydrocarbon blending components is prohibited. The maximum limit of MTBE, ETBE, and TAME allowed is 0.3 vol.% maximum for each compound at origin.
3. Refer to test methods published in 40 CFR Chapter 1, Part 80.46.
4. Mercaptan Sulfur waived if fuel is negative by Doctor test.
5. Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
6. The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
7. The use of MMT octane enhancing additive is prohibited.
8. The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2 and will apply after blending with 10% Denatured Fuel Ethanol.
9. Oxygen content must meet a minimum of 1.5 wt. % and a maximum of 4.0 wt. % after blending with Denatured Fuel Ethanol.
10. This sulfur specification is effective December 15, 2005. Any batches moving prior to this are required to comply with the previous maximum of 0.0300 wt. %.
11. The listed VOC reduction is required at origin. The VOC reduction at delivery will meet EPA requirements.
12. All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).

BUCKEYE PARTNERS, L.P.
(LONG ISLAND SYSTEM AND WOOD RIVER SYSTEM)
SPECIFICATIONS FOR FUNGIBLE NON-VOC CONTROLLED REGIONS 1 & 2
REFORMULATED REGULAR GASOLINE BLENDSTOCK (RBOB) FOR BLENDING WITH
10% DENATURED FUEL ETHANOL (92% PURITY) AS DEFINED IN ASTM D4806
GRADE 542
 (Page 1 of 2)

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	80.0		
Index, (R+M)/2 when additized with 10% Denatured Fuel Ethanol		87.0		
Oxygen, wt. %	D5599, GC-OFID	Report		2,3, 9
Benzene, vol. %	D3606		1.30	
Doctor Test	D4952		Negative	4
OR				
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237 or equiv.		0.01	
Phosphorous, gms/gal	D3231		0.004	
Gum, mg/100ml (after washing)	D381		4	
Oxidation Stability, minutes	D525	240		
Aromatics, vol. %	GCMS, D5769		50.0	3
Olefins, vol. %	D1319		25.0	
Sulfur, wt. %	D2622, D5453, D3120		.0080	10
Odor	Nonoffensive			5
Port Fuel Injector and Intake Valve Detergent Additives			6	
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators - Refer to Table 1				
Volatility and Distillation - Refer to Table 2				
E200, vol. %	D86	30.0	70.0	
E300, vol. %	D86	70.0	100.0	
MMT				7
Driveability Index (DI) Refer to Table 2	D4814			8
Silver Strip Corrosion	D4814		1	
NACE	TM0172-2001	B+		11

This RBOB may not be combined with any other RBOB except RBOB having the same requirement for oxygenate type and amount.

All parameters must be met after blending with denatured fuel ethanol unless noted.

BUCKEYE PARTNERS, L.P.
(LONG ISLAND SYSTEM AND WOOD RIVER SYSTEM)

**SPECIFICATIONS FOR FUNGIBLE NON-VOC CONTROLLED REGIONS 1 & 2
REFORMULATED REGULAR GASOLINE BLENDSTOCK (RBOB) FOR BLENDING WITH
10% DENATURED FUEL ETHANOL (92% PURITY) AS DEFINED IN ASTM D4806
GRADE 542**

(Page 2 of 2)

NOTES:

1. No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
2. This product may not contain oxygenates such as ethers or alcohols. The use of non-hydrocarbon blending components is prohibited. The maximum limit of MTBE, ETBE, and TAME allowed is 0.3 vol.% maximum for each compound at origin.
3. Refer to test methods published in 40 CFR Chapter 1, Part 80.46.
4. Mercaptan Sulfur waived if fuel is negative by Doctor test.
5. Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
6. The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
7. The use of MMT octane enhancing additive is prohibited.
8. The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2 and will apply after blending with 10% Denatured Fuel Ethanol.
9. Oxygen content must meet a minimum of 1.5 wt. % and a maximum of 4.0 wt. % after blending with Denatured Fuel Ethanol.
10. This sulfur specification is effective December 15, 2005. Any batches moving prior to this are required to comply with the previous maximum of 0.0300 wt. %.
11. All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).

BUCKEYE PARTNERS, L.P.
(LONG ISLAND SYSTEM AND WOOD RIVER SYSTEM)
SPECIFICATIONS FOR FUNGIBLE NON-VOC CONTROLLED REGIONS 1 & 2
REFORMULATED PREMIUM GASOLINE BLENDSTOCK (RBOB) FOR BLENDING WITH
10% DENATURED FUEL ETHANOL (92% PURITY) AS DEFINED IN ASTM D4806
GRADE 545
(Page 1 of 2)

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	Report		
Index, (R+M)/2 when additized with 10% Denatured Fuel Ethanol		93.0		
Oxygen, wt. %	D5599, GC-OFID	Report		2,3, 9
Benzene, vol. %	D3606		1.30	
Doctor Test	D4952		Negative	4
OR				
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237 or equiv.		0.01	
Phosphorous, gms/gal	D3231		0.004	
Gum, mg/100ml (after washing)	D381		4	
Oxidation Stability, minutes	D525	240		
Aromatics, vol. %	GCMS, D5769		50.0	3
Olefins, vol. %	D1319		25.0	
Sulfur, wt. %	D2622, D5453, D3120		.0080	10
Odor	Nonoffensive			5
Port Fuel Injector and Intake Valve Detergent Additives			6	
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators - Refer to Table 1				
Volatility and Distillation - Refer to Table 2				
E200, vol. %	D86	30.0	70.0	
E300, vol. %	D86	70.0	100.0	
MMT				7
Driveability Index (DI) Refer to Table 2	D4814			8
Silver Strip Corrosion	D4814		1	
NACE	TM0172-2001	B+		11

This RBOB may not be combined with any other RBOB except RBOB having the same requirement for oxygenate type and amount.

All parameters must be met after blending with denatured fuel ethanol unless noted.

BUCKEYE PARTNERS, L.P.
(LONG ISLAND SYSTEM AND WOOD RIVER SYSTEM)

**SPECIFICATIONS FOR FUNGIBLE NON-VOC CONTROLLED REGIONS 1 & 2
REFORMULATED PREMIUM GASOLINE BLENDSTOCK (RBOB) FOR BLENDING WITH
10% DENATURED FUEL ETHANOL (92% PURITY) AS DEFINED IN ASTM D4806
GRADE 545**

(Page 2 of 2)

NOTES:

1. No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
2. This product may not contain oxygenates such as ethers or alcohols. The use of non-hydrocarbon blending components is prohibited. The maximum limit of MTBE, ETBE, and TAME allowed is 0.3 vol.% maximum for each compound at origin.
3. Refer to test methods published in 40 CFR Chapter 1, Part 80.46.
4. Mercaptan Sulfur waived if fuel is negative by Doctor test.
5. Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
6. The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
7. The use of MMT octane enhancing additive is prohibited.
8. The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2 and will apply after blending with 10% Denatured Fuel Ethanol.
9. Oxygen content must meet a minimum of 1.5 wt. % and a maximum of 4.0 wt. % after blending with Denatured Fuel Ethanol.
10. This sulfur specification is effective December 15, 2005. Any batches moving prior to this are required to comply with the previous maximum of 0.0300 wt. %.
11. All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).

WOOD RIVER PIPE LINES LLC
(WOOD RIVER SYSTEM – ST. LOUIS ONLY)
SPECIFICATIONS FOR FUNGIBLE VOC CONTROLLED REGION 1
REFORMULATED REGULAR GASOLINE BLENDSTOCK (RBOB) FOR BLENDING WITH
10% DENATURED FUEL ETHANOL (92% PURITY) AS DEFINED IN ASTM D4806
GRADE 552
(Page 1 of 2)

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	80.0		
Index, (R+M)/2 when additized with 10% Denatured Fuel Ethanol		87.0		
Oxygen, wt. %	D5599, GC-OFID	Report		2,3, 9
RVP, psi	D5191		Report	3
Benzene, vol. %	D3606		1.30	
Doctor Test	D4952		Negative	4
OR				
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237 or equiv.		0.01	
Phosphorous, gms/gal	D3231		0.004	
Gum, mg/100ml (after washing)	D381		4	
Oxidation Stability, minutes	D525	240		
Aromatics, vol. %	GCMS, D5769		50.0	3
Emissions Performance Reductions				
VOC Region 2, %	EPA	27.0		11
Olefins, vol. %	D1319		25.0	
Sulfur, wt. %	D2622, D5453, D3120		.0080	10
Odor		Nonoffensive		5
Port Fuel Injector and Intake Valve Detergent Additives				6
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators - Refer to Table 1				
Volatility and Distillation - Refer to Table 2				
E200, vol. %	D86	30.0	70.0	
E300, vol. %	D86	70.0	100.0	
MMT				7
Driveability Index	D4814			8
Refer to Table 2				
Silver Strip Corrosion	D4814		1	
NACE	TM0172-2001	B+		12

This RBOB may not be combined with any other RBOB except RBOB having the same requirement for oxygenate type and amount.

All parameters must be met after blending with denatured fuel ethanol unless noted.

**WOOD RIVER PIPE LINES LLC
(WOOD RIVER SYSTEM – ST. LOUIS ONLY)**

**SPECIFICATIONS FOR FUNGIBLE VOC CONTROLLED REGION 1
REFORMULATED REGULAR GASOLINE BLENDSTOCK (RBOB) FOR BLENDING WITH
10% DENATURED FUEL ETHANOL (92% PURITY) AS DEFINED IN ASTM D4806
GRADE 552**

(Page 2 of 2)

NOTES:

1. No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
2. This product may not contain oxygenates such as ethers or alcohols. The use of non-hydrocarbon blending components is prohibited. The maximum limit of MTBE, ETBE, and TAME allowed is 0.3 vol.% maximum for each compound at origin.
3. Refer to test methods published in 40 CFR Chapter 1, Part 80.46.
4. Mercaptan Sulfur waived if fuel is negative by Doctor test.
5. Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
6. The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
7. The use of MMT octane enhancing additive is prohibited.
8. The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2 and will apply after blending with 10% Denatured Fuel Ethanol.
9. Oxygen content must meet a minimum of 1.5 wt. % and a maximum of 4.0 wt. % after blending with Denatured Fuel Ethanol.
10. This sulfur specification is effective December 15, 2005. Any batches moving prior to this are required to comply with the previous maximum of 0.0300 wt. %.
11. The listed VOC reduction is required at origin. The VOC reduction at delivery will meet EPA requirements.
12. All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).

WOOD RIVER PIPE LINES LLC
(WOOD RIVER SYSTEM – ST. LOUIS ONLY)
SPECIFICATIONS FOR FUNGIBLE VOC CONTROLLED REGION 1
REFORMULATED PREMIUM GASOLINE BLENDSTOCK (RBOB) FOR BLENDING WITH
10% DENATURED FUEL ETHANOL (92% PURITY) AS DEFINED IN ASTM D4806
GRADE 555
(Page 1 of 2)

PRODUCT PROPERTY	ASTM TEST METHODS	TEST RESULTS		NOTE
		MINIMUM	MAXIMUM	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	Report		
Index, (R+M)/2 when additized with 10% Denatured Fuel Ethanol		93.0		
Oxygen, wt. %	D5599, GC-OFID	Report		2,3, 9
RVP, psi	D5191		Report	3
Benzene, vol. %	D3606		1.30	
Doctor Test	D4952		Negative	4
OR				
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237 or equiv.		0.01	
Phosphorous, gms/gal	D3231		0.004	
Gum, mg/100ml (after washing)	D381		4	
Oxidation Stability, minutes	D525	240		
Aromatics, vol. %	GCMS, D5769		50.0	3
Emissions Performance Reductions				
VOC Region 2, %	EPA	27.0		11
Olefins, vol. %	D1319		25.0	
Sulfur, wt. %	D2622, D5453, D3120		.0080	10
Odor		Nonoffensive		5
Port Fuel Injector and Intake Valve Detergent Additives				6
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators - Refer to Table 1				
Volatility and Distillation - Refer to Table 2				
E200, vol. %	D86	30.0	70.0	
E300, vol. %	D86	70.0	100.0	
MMT				7
Driveability Index	D4814			8
Refer to Table 2				
Silver Strip Corrosion	D4814		1	
NACE	TM0172-2001	B+		12

This RBOB may not be combined with any other RBOB except RBOB having the same requirement for oxygenate type and amount.

All parameters must be met after blending with denatured fuel ethanol unless noted.

**WOOD RIVER PIPE LINES LLC
(WOOD RIVER SYSTEM – ST. LOUIS ONLY)**

**SPECIFICATIONS FOR FUNGIBLE VOC CONTROLLED REGION 1
REFORMULATED PREMIUM GASOLINE BLENDSTOCK (RBOB) FOR BLENDING WITH
10% DENATURED FUEL ETHANOL (92% PURITY) AS DEFINED IN ASTM D4806
GRADE 555**

(Page 2 of 2)

NOTES:

1. No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
2. This product may not contain oxygenates such as ethers or alcohols. The use of non-hydrocarbon blending components is prohibited. The maximum limit of MTBE, ETBE, and TAME allowed is 0.3 vol.% maximum for each compound at origin.
3. Refer to test methods published in 40 CFR Chapter 1, Part 80.46.
4. Mercaptan Sulfur waived if fuel is negative by Doctor test.
5. Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
6. The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
7. The use of MMT octane enhancing additive is prohibited.
8. The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2 and will apply after blending with 10% Denatured Fuel Ethanol.
9. Oxygen content must meet a minimum of 1.5 wt. % and a maximum of 4.0 wt. % after blending with Denatured Fuel Ethanol.
10. This sulfur specification is effective December 15, 2005. Any batches moving prior to this are required to comply with the previous maximum of 0.0300 wt. %.
11. The listed VOC reduction is required at origin. The VOC reduction at delivery will meet EPA requirements.
12. All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).

BUCKEYE PARTNERS, L.P.
(LONG ISLAND SYSTEM ONLY)
SPECIFICATIONS FOR FUNGIBLE VOC CONTROLLED REGION 2
REFORMULATED REGULAR GASOLINE BLENDSTOCK (RBOB) FOR BLENDING WITH
5.7% DENATURED FUEL ETHANOL (92% PURITY) AS DEFINED IN ASTM D4806
GRADE 732
(Page 1 of 2)

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	80.0		
Index, (R+M)/2		85.4		
Index, (R+M)/2 when additized with 5.7% Denatured Fuel Ethanol		87.0		
Oxygen, wt. %	D5599, GC-OFID		Report	2,3, 9
RVP, psi	D5191		Report	3
Benzene, vol. %	D3606		1.30	
Doctor Test	D4952		Negative	4
OR				
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237 or equiv.		0.01	
Phosphorous, gms/gal	D3231		0.004	
Gum, mg/100ml (after washing)	D381		4	
Oxidation Stability, minutes	D525	240		
Aromatics, vol. %	GCMS, D5769		50.0	3
Emissions Performance Reductions				
VOC Region 2, %	EPA	25.4		
Olefins, vol. %	D1319	25.0		
Sulfur, wt. %	D2622, D5453, D3120		.0080	10
Odor		Nonoffensive		5
Port Fuel Injector and Intake Valve Detergent Additives				6
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators - Refer to Table 1				
Volatility and Distillation - Refer to Table 2				
E200, vol. %	D86	30.0	70.0	
E300, vol. %	D86	70.0	100.0	
MMT				7
Driveability Index	D4814			8
Refer to Table 2				
Silver Strip Corrosion	D4814		1	
NACE	TM0172-2001	B+		11

This RBOB may not be combined with any other RBOB except RBOB having the same requirement for oxygenate type and amount.

All parameters must be met after blending with denatured fuel ethanol unless noted.

**BUCKEYE PARTNERS, L.P.
(LONG ISLAND SYSTEM ONLY)**

**SPECIFICATIONS FOR FUNGIBLE VOC CONTROLLED REGION 2
REFORMULATED REGULAR GASOLINE BLENDSTOCK (RBOB) FOR BLENDING WITH
5.7% DENATURED FUEL ETHANOL (92% PURITY) AS DEFINED IN ASTM D4806
GRADE 732**

(Page 2 of 2)

NOTES:

1. No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
2. This product may not contain oxygenates such as ethers or alcohols. The use of non-hydrocarbon blending components is prohibited. The maximum limit of MTBE, ETBE, and TAME allowed is 0.3 vol.% maximum for each compound at origin.
3. Refer to test methods published in 40 CFR Chapter 1, Part 80.46.
4. Mercaptan Sulfur waived if fuel is negative by Doctor test.
5. Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
6. The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
7. The use of MMT octane enhancing additive is prohibited.
8. The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2 and will apply after blending with 5.7% Denatured Fuel Ethanol.
9. Oxygen content must meet a minimum of 1.5 wt. % and a maximum of 2.4 wt. % after blending with Denatured Fuel Ethanol.
10. This sulfur specification is effective December 15, 2005. Any batches moving prior to this are required to comply with the previous maximum of 0.0300 wt. %.
11. All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).

BUCKEYE PARTNERS, L.P.
(LONG ISLAND SYSTEM ONLY)
SPECIFICATIONS FOR FUNGIBLE VOC CONTROLLED REGION 2
REFORMULATED PREMIUM GASOLINE BLENDSTOCK (RBOB) FOR BLENDING WITH
5.7% DENATURED FUEL ETHANOL (92% PURITY) AS DEFINED IN ASTM D4806
GRADE 735
(Page 1 of 2)

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	Report		
Index, (R+M)/2		92.1		
Index, (R+M)/2 when additized with 5.7% Denatured Fuel Ethanol		93.0		
Oxygen, wt. %	D5599, GC-OFID	Report		2,3, 9
RVP, psi	D5191		Report	3
Benzene, vol. %	D3606		1.30	
Doctor Test	D4952		Negative	4
OR				
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237 or equiv.		0.01	
Phosphorous, gms/gal	D3231		0.004	
Gum, mg/100ml (after washing)	D381		4	
Oxidation Stability, minutes	D525	240		
Aromatics, vol. %	GCMS, D5769		50.0	3
Emissions Performance Reductions				
VOC Region 2, %	EPA	25.4		
Olefins, vol. %	D1319			25.0
Sulfur, wt. %	D2622, D5453, D3120		.0080	10
Odor		Nonoffensive		5
Port Fuel Injector and Intake Valve Detergent Additives				6
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators - Refer to Table 1				
Volatility and Distillation - Refer to Table 2				
E200, vol. %	D86	30.0	70.0	
E300, vol. %	D86	70.0	100.0	
MMT				7
Driveability Index	D4814			8
Refer to Table 2				
Silver Strip Corrosion	D4814		1	
NACE	TM0172-2001	B+		11

This RBOB may not be combined with any other RBOB except RBOB having the same requirement for oxygenate type and amount.

All parameters must be met after blending with denatured fuel ethanol unless noted.

**BUCKEYE PARTNERS, L.P.
(LONG ISLAND SYSTEM ONLY)**

**SPECIFICATIONS FOR FUNGIBLE VOC CONTROLLED REGION 2
REFORMULATED PREMIUM GASOLINE BLENDSTOCK (RBOB) FOR BLENDING WITH
5.7% DENATURED FUEL ETHANOL (92% PURITY) AS DEFINED IN ASTM D4806
GRADE 735**

(Page 2 of 2)

NOTES:

1. No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
2. This product may not contain oxygenates such as ethers or alcohols. The use of non-hydrocarbon blending components is prohibited. The maximum limit of MTBE, ETBE, and TAME allowed is 0.3 vol.% maximum for each compound at origin.
3. Refer to test methods published in 40 CFR Chapter 1, Part 80.46.
4. Mercaptan Sulfur waived if fuel is negative by Doctor test.
5. Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
6. The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
7. The use of MMT octane enhancing additive is prohibited.
8. The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2 and will apply after blending with 5.7% Denatured Fuel Ethanol.
9. Oxygen content must meet a minimum of 1.5 wt. % and a maximum of 2.4 wt. % after blending with Denatured Fuel Ethanol.
10. This sulfur specification is effective December 15, 2005. Any batches moving prior to this are required to comply with the previous maximum of 0.0300 wt. %.
11. All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).

BUCKEYE PARTNERS, L.P.
(LONG ISLAND SYSTEM ONLY)
SPECIFICATIONS FOR FUNGIBLE NON-VOC CONTROLLED REGION 2
REFORMULATED REGULAR GASOLINE BLENDSTOCK (RBOB) FOR BLENDING WITH
5.7% DENATURED FUEL ETHANOL (92% PURITY) AS DEFINED IN ASTM D4806
GRADE 742
(Page 1 of 2)

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	80.0		
Index, (R+M)/2		85.4		
Index, (R+M)/2 when additized with 5.7% Denatured Fuel Ethanol		87.0		
Oxygen, wt. %	D5599, GC-OFID	Report		2,3,9
Benzene, vol. %	D3606		1.30	
Doctor Test	D4952		Negative	4
OR				
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237 or equiv.		0.01	
Phosphorous, gms/gal	D3231		0.004	
Gum, mg/100ml (after washing)	D381		4	
Oxidation Stability, minutes	D525	240		
Aromatics, vol. %	GCMS, D5769		50.0	3
Olefins, vol. %	D1319		25.0	
Sulfur, wt. %	D2622, D5453, D3120		.0080	10
Odor	Nonoffensive			5
Port Fuel Injector and Intake Valve Detergent Additives				6
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators - Refer to Table 1				
Volatility and Distillation - Refer to Table 2				
E200, vol. %	D86	30.0	70.0	
E300, vol. %	D86	70.0	100.0	
MMT				7
Driveability Index (DI)	D4814			8
Refer to Table 2				
Silver Strip Corrosion	D4814		1	
NACE	TM0172-2001	B+		11

This RBOB may not be combined with any other RBOB except RBOB having the same requirement for oxygenate type and amount.

All parameters must be met after blending with denatured fuel ethanol unless noted.

**BUCKEYE PARTNERS, L.P.
(LONG ISLAND SYSTEM ONLY)**

**SPECIFICATIONS FOR FUNGIBLE NON-VOC CONTROLLED REGION 2
REFORMULATED REGULAR GASOLINE BLENDSTOCK (RBOB) FOR BLENDING WITH
5.7% DENATURED FUEL ETHANOL (92% PURITY) AS DEFINED IN ASTM D4806
GRADE 742**

(Page 2 of 2)

NOTES:

1. No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
2. This product may not contain oxygenates such as ethers or alcohols. The use of non-hydrocarbon blending components is prohibited. The maximum limit of MTBE, ETBE, and TAME allowed is 0.3 vol.% maximum for each compound at origin.
3. Refer to test methods published in 40 CFR Chapter 1, Part 80.46.
4. Mercaptan Sulfur waived if fuel is negative by Doctor test.
5. Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
6. The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
7. The use of MMT octane enhancing additive is prohibited.
8. The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2 and will apply after blending with 5.7% Denatured Fuel Ethanol.
9. Oxygen content must meet a minimum of 1.5 wt. % and a maximum of 2.4 wt. % after blending with Denatured Fuel Ethanol.
10. This sulfur specification is effective December 15, 2005. Any batches moving prior to this are required to comply with the previous maximum of 0.0300 wt. %.
11. All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).

BUCKEYE PARTNERS, L.P.
(LONG ISLAND SYSTEM ONLY)
SPECIFICATIONS FOR FUNGIBLE NON-VOC CONTROLLED REGION 2
REFORMULATED PREMIUM GASOLINE BLENDSTOCK (RBOB) FOR BLENDING WITH
5.7% DENATURED FUEL ETHANOL (92% PURITY) AS DEFINED IN ASTM D4806
GRADE 745
(Page 1 of 2)

<u>PRODUCT PROPERTY</u>	<u>ASTM TEST METHODS</u>	<u>TEST RESULTS</u>		<u>NOTE</u>
		<u>MINIMUM</u>	<u>MAXIMUM</u>	
Color			Undyed	
Gravity, API @ 60°F	D287, D1298, D4052	Report		
Corrosion, 3 hrs. @ 122°F	D130		1	1
Octane Rating				
Research Number	D2699, D2885	Report		
Motor Number	D2700, D2885	Report		
Index, (R+M)/2		92.1		
Index, (R+M)/2 when additized with 5.7% Denatured Fuel Ethanol		93.0		
Oxygen, wt. %	D5599, GC-OFID	Report		2,3,9
Benzene, vol. %	D3606		1.30	
Doctor Test	D4952		Negative	4
OR				
Mercaptan Sulfur, wt. %	D3227		0.002	
Lead Content, gms/gal	D3237 or equiv.		0.01	
Phosphorous, gms/gal	D3231		0.004	
Gum, mg/100ml (after washing)	D381		4	
Oxidation Stability, minutes	D525	240		
Aromatics, vol. %	GCMS, D5769		50.0	3
Olefins, vol. %	D1319		25.0	
Sulfur, wt. %	D2622, D5453, D3120		.0080	10
Odor		Nonoffensive		5
Port Fuel Injector and Intake Valve Detergent Additives				6
Corrosion Inhibitors, Gum Inhibitors and Metal Deactivators - Refer to Table 1				
Volatility and Distillation - Refer to Table 2				
E200, vol. %	D86	30.0	70.0	
E300, vol. %	D86	70.0	100.0	
MMT				7
Driveability Index (DI)	D4814			8
Refer to Table 2				
Silver Strip Corrosion	D4814		1	
NACE	TM0172-2001	B+		11

This RBOB may not be combined with any other RBOB except RBOB having the same requirement for oxygenate type and amount.

All parameters must be met after blending with denatured fuel ethanol unless noted.

**BUCKEYE PARTNERS, L.P.
(LONG ISLAND SYSTEM ONLY)**

**SPECIFICATIONS FOR FUNGIBLE NON-VOC CONTROLLED REGION 2
REFORMULATED PREMIUM GASOLINE BLENDSTOCK (RBOB) FOR BLENDING WITH
5.7% DENATURED FUEL ETHANOL (92% PURITY) AS DEFINED IN ASTM D4806
GRADE 745**

(Page 2 of 2)

NOTES:

1. No additives or corrosion inhibitors containing phosphorus may be used in this gasoline.
2. This product may not contain oxygenates such as ethers or alcohols. The use of non-hydrocarbon blending components is prohibited. The maximum limit of MTBE, ETBE, and TAME allowed is 0.3 vol.% maximum for each compound at origin.
3. Refer to test methods published in 40 CFR Chapter 1, Part 80.46.
4. Mercaptan Sulfur waived if fuel is negative by Doctor test.
5. Any gasoline exhibiting an offensive odor and/ or poses a personal health hazard will not be accepted for shipment. Any gasoline containing more than 0.50 wt. % of dicyclopentadiene will not be accepted for shipment. The referee method will be based on a gas chromatograph test.
6. The use of Port Fuel Injector (PFI) and intake valve detergent additives is prohibited.
7. The use of MMT octane enhancing additive is prohibited.
8. The Driveability Index (DI) specification limits are applicable at the refinery or import facility as defined by 40 CFR Part 80.2 and will apply after blending with 5.7% Denatured Fuel Ethanol.
9. Oxygen content must meet a minimum of 1.5 wt. % and a maximum of 2.4 wt. % after blending with Denatured Fuel Ethanol.
10. This sulfur specification is effective December 15, 2005. Any batches moving prior to this are required to comply with the previous maximum of 0.0300 wt. %.
11. All products (except aviation grades 152, 153, 155 and 182) must meet a minimum level of corrosion protection, indicated by a minimum rating of B+ as determined by NACE Standard Test Method TM0172-2001 (Determining Corrosive Properties of Cargoes in Petroleum Product Pipelines).